



INTERIOR COLLECTION

ARA™

ARCHITECTURAL SQUARE STRIP

OVERVIEW

Lumens

Delivers up to 150 lumens per watt

CRI

80+

CCT

3000K, 3500K, 4000K, 5000K, 6500K

Voltage

120-277V

Dimming

0-10V dimming standard

Operating Temperature

-4°F to +122°F

Projected Lifetime

>100,000 Hours

Standard Finish

White



Introducing the Ara™ [a-ra] Architectural Strip series – a versatile and durable lighting solution designed for a wide range of applications. With premium performance and construction durability, Ara™ is the perfect choice for commercial, industrial, institutional, and retail settings.

Features

- Sizing options include standard lengths of 4' or 8' for flexibility in fitting your space.
- Selectable wattage and color temperature (CCT) to your preferences for personalized lighting.
- Premium Performance: enhancing visibility and productivity in any environment.
- Premium Build: durable aluminum with a refined powder coat finish, our fixtures ensure long-lasting quality.
- Create seamless, uninterrupted illumination with the ability connect luminaires for a continuous run.
- Wide Range of Applications: From storage/utility areas to display cases, shops, and general area lighting, Ara™ excels in various environments.

Pending UL & DLC

10 YR

Warranty
Available³



M20® ARCHITECTURAL • Ph: 800-323-8107

© 2026 PQL, Inc. All Rights Reserved. • 2285 Ward Avenue • Simi Valley, CA 93065

M20LIGHTING.COM

Photos and drawings may not be to scale and are for general reference only.

Rev: 07/13/2026

BUILD WORKSHEET

Contact sales representative to order.

ARAS1			5C	U	W		
SERIES	LENGTH	OUTPUT	CCT	VOLTAGE	FINISH	EMERGENCY	WARRANTY
ARAS1 Ara TM Architectural Square Strip	4 4FT	P34 Selectable: 17W, 21W, 26W, 34W	5C Selectable: 3000K, 3500K, 4000K, 5000K, 6500K	U 120-277V	W White	E Pre-installed Emergency Backup (55703)	10 10 Year Option
	8 8FT	P68 Selectable: 34W, 42W, 52W, 68W					Blank Standard 5 Year
						Blank None	

* Fixture comes set/standard at highest wattage, 4000K.


¹ 5 Year Warranty is Standard unless specified.

ACCESSORIES (Ordered separately for field installation)



55703	8W EMERGENCY PACK/90 MIN
-------	--------------------------

DIMENSIONS

4FT



8FT



Size	4FT	8FT
Length - X1	47.3"	94.2"
Width - X2	3.3"	
Height - X3	3.7"	
Height - X4	3.5"	

Pending UL & DLC



Quick-Ship Program
Select sizes, finishes and
configurations in stock,
and ready to ship.

PERFORMANCE DETAILS

Length	4FT	8FT
Electrical		
Wattage (Selectable)	17W / 21W / 26W / 36W	34W / 42W / 52W / 68W
Voltage	120-277V - 50/60Hz	
Power Factor	0.9	
THD	20	
Optical		
Lumens	2550 / 3150 / 3900 / 5100	5100 / 6000 / 7050 / 7950
Lumens Per Watt	150	
CCT (Selectable)	3000K / 3500K / 4000K / 5000K / 6500K	
CRI	80	
Beam Angle	130°	
Dimming	0-10V, 100% down to 10%	
Environment		
Operating Temperature	-4°F ~ 122°F	
Suitable Location	Indoors, Dry and Damp	
IP Rating	IP20	
Construction		
Housing	Aluminum	
Lens	PC/ Frosted	
Finish	White	
Lifespan		
Years	5-Year Standard, 10-Year Optional	
Listings		
Qualifications	Pending UL & DLC®	