

# ARA™

SQ | ARCHITECTURAL STRIP

## OVERVIEW

### Lumens

Delivers up to 130 lumens per watt

### CRI

80+

### CCT Selectable

3500K, 4100K, 5000K

### Voltage

120-277V

### Dimming

0-10V dimming standard

### Operating Temperature

-4°F to +122°F

### Projected Lifetime

>50,000 Hours

### Standard Finish

White

### Customization

Integrated Sensor Option (ISO)



Introducing the Ara™ Architectural Strip series – a versatile and durable lighting solution designed for a wide range of applications. With premium performance and construction durability, Ara™ is the perfect choice for commercial, industrial, institutional, and retail settings.

### Features

- Sizing options include standard lengths of 4' or 8' for flexibility in fitting your space.
- Spec-Select™, tailor wattage and color temperature (CCT) to your preferences for personalized lighting.
- Premium Performance: enhancing visibility and productivity in any environment.
- Premium Build: durable aluminum with a refined powder coat finish, our fixtures ensure long-lasting quality.
- Upgrade with an integrated sensor option for improved energy efficiency and automated control.
- Create seamless, uninterrupted illumination with the ability connect luminaires for a continuous run.
- Wide Range of Applications: From storage/utility areas to display cases, shops, and general area lighting, Ara™ excels in various environments.



**ORDERING WORKSHEET**

Contact sales representative to order.

**FIXTURE**

ORDERING CODE	LENGTH	WATTAGE	CCT	VOLTAGE	CASE QTY
55759	4FT	34W/38W/45W	35/41/50	120-277V	6
55760	8FT	65W/75W/90W			4

**ACCESSORIES** *(Ordered separately)*


SENSOR*	EMERGENCY	MOUNTING
54871 PIR Bi-Level Motion & Daylight	55703 8W/90 Min.	55454 Row Aligner
54872 Microwave Bi-Level Motion & Daylight		45001 V-Hooks (2 per set)
54876 Adjustable Elbow, External Swivel, Quick Connect		

**REPLACEMENT PARTS** *(Ordered separately)*

LENS	DRIVER	OTHER
557598 4FT Lens	SIF40-I1000-SS For 4FT Fixture	54875 Quick Connect Socket Base for ISO
557608 8FT Lens	SIL80-I2000-SS For 8FT Fixture	OBC-DS Outlet Cover Box

\* Sensors require Adjustable Elbow (#54876) for best performance.

<sup>6</sup> 5 Year Warranty is Standard unless specified.



**Quick-Ship Program**  
 Select sizes, finishes  
 and configurations  
 in stock, and ready  
 to ship.

Project:	_____
Catalog #:	_____
Quantity:	_____ Date: _____


**PERFORMANCE DETAILS**

Length	4FT	8FT
Ordering Code	55759	55760
<b>Electrical</b>		
Wattage (Selectable)	34W / 38W / 45W	65W / 75W / 90W
Voltage	120-277V - 50/60Hz	
Current	45W @ 120V = 0.375A	90W @ 120V = 0.75A
Power Factor	0.9	
Total Harmonic Distortion (THD)	8.6	5
<b>Optical</b>		
Lumens	4420 / 4940 / 5850	8645 / 9975 / 11970
Lumens Per Watt	130	133
Color Temperature (CCT Selectable)	3500K / 4100K / 5000K	
Color Rendering (CRI)	81	82
Beam Angle	130°	
Light Distribution	Type II, Very Short	Type II, Very Short
BUG Rating (Backlight, Uplight, and Glare)	B2 - U3 - G2	N/A
Dimming	From optional 12VDC sensor, or customer 0-10V controls.	
<b>Environment</b>		
Operating Temperature	-4°F ~ 122°F	
Suitable Location	Indoors, Dry and Damp	
IP Rating	IP40	
<b>Construction</b>		
LED Chip	Bridgelux	
Driver	SIF40-I1000-SS	SIL80-I2000-SS
Sensor Socket	12VDC AUX.	
Housing	Aluminum	
Lens	PC/ Frosted	
Finish	White	
<b>Listings</b>		
Qualifications	cUL, DLC® Standard	
DLC® Product ID	S-QYKTE2	S-2XEBHP
<b>Warranty</b>		
Limited Warranty	5 Years	


Default settings; lowest wattage, highest CCT. • Visit [www.designlights.org/search](http://www.designlights.org/search) to confirm qualification. • Published lumens on LED products are approximate and may vary slightly.

**ADDITIONAL INFORMATION**

- The color temperature and wattage may be adjusted by two slide switches integrated into the driver. For additional information refer to the install instructions.



**DIMENSIONS**



Size	4FT	8FT
Length - X1	47.3"	94.2"
Length - X2	1.9	
Height - X3	2.5"	

**SHIPPING**

Packaging	4FT	8FT
Ordering Code	55759	55760
Master Case Quantity	6	4
Master Case Size (LxWxH)	49.3" x 7.2" x 8.7"	96.6" x 5" x 5.8"
Master Gross Weight (Lbs)	--	44.3
Master Case UPC	10811768022909	10811768020707
Individual Box (LxWxH)	48.6" x 2.2" x 2.7"	95.5" x 2.2" x 2.7"
Individual Box Gross Weight (Lbs)	--	11
Individual UPC	811768022902	811768020700

COO: China • Tariff: 9405.11.6020