

STEALTH™

Elevate your exterior with Stealth™ Area Lights—an energy-efficient alternative to conventional Metal Halide or HPS fixtures. Engineered for optimal performance and energy efficiency, these lights provide brilliant, uniform illumination but also boast an extended lifespan, substantially cutting down on maintenance expenses throughout the fixture's life. The sleek and modern design is specifically designed for outdoor use.

Perfect for commercial and industrial settings, these fixtures excel in various applications such as parking areas, outdoor parks, dealerships, roadways, airports, as well as security and perimeter lighting. Illuminate your spaces with confidence and efficiency.



WATTAGE RANGE

60W-300W

LUMENS PER WATT

145

LOCATION RATING

WET

DIMMING

0-10V

WARRANTY

5 YEARS

FEATURES & SPECIFICATIONS

ELECTRICAL

- Choose from a range of wattage options: 60W, 80W, 100W, 150W, 185W, 240W or 300W
- Input voltage of 100-277V
- Built-in surge protection

OPTICS

- CCT options: 3000K, 4000K or 5000K
- Available distributions: Type III, IV, V, or 60° Narrow
- CRI of >70

ENVIRONMENT

- Operating temperature of -22°F to 131°F
- IP65 rating
- IK08 impact rating

CONSTRUCTION

- Heavy duty aluminum housing
- PC optical lens
- Standard finishes: Dark Bronze and White. Custom colors available upon request, contact sales representative.

INSTALLATION

- Easily installs to most surfaces with quick-mount system.
- Pole mount, adapts to round or flat poles.
- Slip Fitter installs over a pole, adjustable angle.
- Trunnion mounts to a variety of surfaces, adjustable angle

CONTROLS

- 3 Pin receptacle.
- Optional photo control or motion sensor accessories available.

STEALTH™



ORDERING INFORMATION

AST1	U					
1	2	3	4	5	6	7

1. SERIES	2. VOLTAGE	3. FINISH	4. CHASSIS	5. LUMENS	6. DISTRIBUTION	7. CCT
AST1 Stealth Area Light	U 100-277V	B Bronze W White C Custom color code provided on item number later ¹	A Low B Med C High	08 8700 (60W) 11 11600 (80W) 14 14500 (100W) 21 21750 (150W) 26 26825 (185W) 34 34800 (240W) 43 43500 (300W)	3 Type III 4 Type IV 5 Type V N Narrow, 60°	30 3000K 40 4000K 50 5000K

¹ Consult with sales representative for MOQ and lead time on custom finishes.

ACCESSORIES (Sold Separately)

MOUNTING	
AST-PM-B 83954	Round or Flat Pole Bracket, Dark Bronze Round or Flat Pole Bracket, White
AST-SF-B 83953	Slip Fitter Bracket, Dark Bronze Slip Fitter Bracket, White
AST-SFA-B	Slip Fitter Adapter, Dark Bronze
AST-TR-B 83961	Trunnion Bracket, Dark Bronze Trunnion Bracket, White



AST-PM-B



AST-SF-B



AST-SFA-B



AST-TR-B

SENSOR	
54892	PIR Bi-Level Motion & Daylight
83963	Photo Control - 120-277V



54892



83963

REPLACEMENT PARTS (Sold Separately)

COMPONENTS	
JL208	Shorting Cap



Project: _____
 Catalog #: _____
 Quantity: _____ Date: _____


STEALTH™**PQL**
PREMIUM QUALITY LIGHTING®**PERFORMANCE DATA**

ELECTRICAL							
Wattage	60W	80W	100W	150W	185W	240W	300W
Current @ 120V	0.5A	0.66A	0.83A	1.25A	1.54A	2A	2.5A
Current @ 277V	0.21A	0.28A	0.36A	0.54A	0.66A	0.86A	1.08A
Power Factor	0.9						
Total Harmonic Distortion (THD)	20						
OPTICAL							
Lumens	8700	11600	14500	21750	26825	34800	43500
Lumens Per Watt	145						
Color Temperature (CCT)	3000K / 4000K / 5000K						
Color Rendering (CRI)	70						
Light Distribution	Type III, Type IV, Type V, Narrow 60°						
BUG Rating (Backlight, Uplight, and Glare)	--	--	--	--	--	--	--
Dimming	0-10V, Range 10%-100%						
ENVIRONMENT							
Operating Temperature	-22°F ~ 131°F						
Suitable Location	Wet						
IP Rating	IP65						
Effective Projected Area (EPA)	0.23ft ²				0.42ft ²		
Wind Sheer Rating	118.6mph						
CONSTRUCTION							
LED Chip	LumiLEDs						
Driver	--	--	--	--	--	--	--
Housing	Aluminum						
Lens	PC						
Finish	Standard Dark Bronze or White						
Net Weight (Lbs)	9.5	9.5	9.5	10.1	10.1	13.7	13.7
LISTINGS							
Model Number	ASTI-U-[B,W,C]-[1,1B,2]-[60W,80W, 100W, 150W, 185W, 240W, 300W]-[3,4,5,N]-K						
Qualifications	ETL						
WARRANTY							
Years	Standard 5 Years, 10 Years Optional						
<i>Published lumens on LED products are approximate and may vary slightly. - Full warranty terms can be found on our website.</i>							



STEALTH™

DIMENSIONS



SHIPPING INFORMATION

PACKAGING	WATTAGE						
	60W	80W	100W	150W	185W	240W	300W
Master Case							
Quantity	1						
Size (LxWxH)	18.5" x 13.8" x 6.5"					24.9" x 13.8" x 7.3"	
Gross Weight (Lbs)	--	--	--	--	--	--	--
COO: China • Tariff: N/A							