

ORDERING CODE
CDR1

Tone-Select™ Designer Surface Mount LED Lights, combine energy efficiency with versatility, with a slim low-profile design and the ability to choose your preferred color temperature.

APPLICATION

Perfect for a wide range of applications including offices, hospitals, retail spaces, schools, lobbies, commercial buildings, and work areas.



Project _____	Date _____
Catalog # _____	Quantity _____ Type _____

PRODUCT INFORMATION

ELECTRICAL	
Wattages	11W / 14W / 20W
Voltage	120V
Power Factor	0.9
THD	20

OPTICAL	
Efficiency (LPW)	Up to 60
CCT (Selectable)	2700K / 3000K / 3500K / 4000K / 5000K
CRI	90
Beam Angle	120°
Dimming	See compatibility chart

ENVIRONMENT	
Operating Temperature	-4° ~ 104°F
Suitable Location	Damp
IP Rating	IP20

CONSTRUCTION	
LED Chip	Smalite
Driver	Internal
Housing Diameters	5" / 7" / 9"
Lens	PC
Base / Power Supply	Hard Wired
Finish	White

WARRANTY <i>(Complete terms can be found on our website.)</i>	
Standard	5-year

LISTINGS	
Model Number	See page 2



ORDERING

CDR1			5C	W
SERIES	SIZE	WATTAGE	CCT	FINISH
CDR1 Designer Surface Mount	05 5" Diameter	11 11W / 650LM	5C Selectable: 2700K, 3000K, 3500K, 4000K, 5000K	W White
	07 7" Diameter (JA8/T24)	14 14W / 830LM		
	09 9" Diameter	20 20W / 1190LM		

ACCESSORIES

CODE	DESCRIPTION	CASE
83872	5/6IN DOWNLIGHT E26 MOUNTING ACCESSORY FOR 7 OR 9IN DESIGNER SURFACE MOUNTED FIXTURES	100

PACKAGING



MASTER CASE	CDR105115CW	CDR107145CW	CDR109205CW
Quantity	60	40	20
Size (LxWxH)	19.8" x 15.5" x 17.5"	19.8" x 15.7" x 18.4"	19.8" x 11.3" x 19.1"
UPC	--	10811768029663	--
Individual Box (LxWxH)	7.3" x 5.5" x 1.9"	8.7" x 7.4" x 1.9"	10.4" x 9.1" x 1.9"
UPC	--	811768029666	--

COO: China • Tariff: 8539.52.0010

PERFORMANCE DATA

DIAMETER	WATTAGE	LUMENS	LPW	CURRENT	DRIVER	MODEL NUMBER
				120V		
5"	11W	650	60	0.09A	INTERNAL	CDR105115CW
7"	14W	830		0.12A		CDR107145CW
9"	20W	1190		0.17A		CDR109205CW

DIMENSIONS



SIZE	05	07	09
Diameter (D)	5"	7"	9"
Height (H)	0.6"		