



TEST REPORT

For

P.Q.L., Inc.

2285 Ward Avenue / Simi Valley, CA 93065

Model Number:	HLT1CP1152CUW - 4000K HLT1CP1152CUW - 5000K	
Report Type:	Electrical, Photometric and ISTMT tests according to the following standards and show the compliance to DLC Program SSL Technical Requirements V5.1	
Standards:	ANSI/IES LM-79-19: Approved Method: Optical and Electrical Measurements of Solid-State Lighting Products ANSI C82.77-10-2014: Harmonic Emission Limits – Related Power Quality Requirements for Lighting ANSI/UL 1598-2008: Standard for Safety of Luminaires CIE 190:2010 Calculation and presentation of unified glare rating tables for indoor lighting luminaires IES TM-30-18*: IES Method for Evaluating Light Source Color Rendition	
Project Engineer:	Allen Pan	<i>Allen Pan</i>
Report Number:	RKSB250918008-10	
Sample Size:	One sample was received on 2025-09-18 and used for testing.	
Test Date:	2025-09-20 to 2025-09-23	
Report Date:	2025-09-28	
Reviewed By:	Seven Xia/ EE Engineer	<i>Seven Xia</i>
Prepared By:	Bay Area Compliance Laboratories Corp. (Kunshan). No. 248 Chenghu Road, Kunshan, Jiangsu, People's Republic of China Tel: +86-0512-86175000 Fax: +86-0512-88934268	



1. Product Information and Description

Product Primary Use: High-Bay Luminaires for Commercial and Industrial Buildings
 Voltage and Frequency: 120-277VAC, 60Hz
 LED Source Manufacturer: Seoul Semiconductor Co., LTD
 LED Source Model: STW8A32E
 Driver Model: SIG120-I0530 120-277 W D1S
 Auxiliary Ballast Model: NA
 Auxiliary Housing Model: NA
 White Tunable: Yes
 Field-Adjustable Light Output: Yes



2. Product Rated Values#

Test Model	CCT(K)	Light Output (lm)	Power(W)	Luminous Efficacy (lm/W)
HLT1CP1152CUW	4000	17250	115	150
		14260	92	155
		12480	78	160
HLT1CP1152CUW	5000	17250	115	150
		14260	92	155
		12480	78	160

3. Test List

Test Model	Power(W)	Test Item			
		Goniophotometer Test	Integrating Sphere Test	THDi and PF Test	In-Situ Temperature Measurement Test
HLT1CP1152CUW 4000K	115	Yes	Yes	Yes	Yes
	92	NA	Yes	Yes	NA
	78	NA	Yes	Yes	NA
HLT1CP1152CUW 5000K	115	NA	Yes	Yes	NA

4. Product Photo



LED Driver Photo



5. Test Result

Test Model: HLT1CP1152CUW

Control setting: 115W

Integrating Sphere Test; Orientation: Downward; Test Voltage: 120V 60Hz;

Test Item	Test Result	DLC Requirements	DLC Requirements(With tolerances only)	Conclusion
Light Output(lm)	29198.8	≥10000	≥9000	Pass
Power(W)	189.91	None.	None.	N/A
Total Efficacy(lm/W)	153.75	≥135	≥130.95	Pass
CCT(K)	4121	None ⁱ	None.	N/A
Duv	-0.00067	None ⁱ	None.	N/A
IES R _r	82	70	69	Pass
IES R _g	95	89	88	
IES Rcs,h1	-13%	-18%~23%	-19%~24%	
R _a	82	≥70	≥69	
R ₉	5	≥-40	≥-41	

Note:

- i. White-tunable products are not required to meet the chromaticity requirements in DLC V5.1.

Goniophotometer Test; Orientation: Downward; Test Voltage: 120V 60Hz;

Test Item	Test Result	DLC Requirements	DLC Requirements(With tolerances only)	Conclusion
Light Output(lm)	29209.1	≥10000	≥9000	Pass
Power(W)	192.04	None.	None.	N/A
Total Efficacy(lm/W)	152.15	≥135	≥130.95	Pass
Zonal Lumen Distribution(20-50°)	60.33%	20-50°≥30%	20-50°≥20%	Pass
UGR crosswise view	23.4	<28	No tolerances	Pass
UGR endwise view	22.6	<28	No tolerances	Pass

Integrating Sphere THDi \ PF Test; Orientation: Downward;


Test Voltage	Test Item	Test Result	DLC Requirements	DLC Requirements(With tolerances and/or allowances)	Conclusion
120	Power Factor	0.9968	≥0.9	≥0.87	Pass
120	THDi	2.69%	≤20%	≤25%	Pass
277	Power Factor	0.958	≥0.9	≥0.87	Pass
277	THDi	6.41%	≤20%	≤25%	Pass


In-Situ Temperature Measurement Test: Test Voltage: 120V 60Hz;

Test Item	Test Result	DLC Requirements	DLC Requirements(With tolerances and/or allowances)	Conclusion
TMP _{LED1} (°C)	59	≤105	With tolerance of ≤ 1.1°C or 0.4%, whichever is greater due to thermocouple tolerance	Pass
TMP _{LED2} (°C)	57.7	≤105	With tolerance of ≤ 1.1°C or 0.4%, whichever is greater due to thermocouple tolerance	Pass
TMP _c (°C)	51	≤90	With tolerance of ≤ 1.1°C or 0.4%, whichever is greater due to thermocouple tolerance	Pass
Drive Current/Individual LED source(mA) _{#1}	29.4	≤100	With +5% Tolerance	Pass
Drive Current/Individual LED source(mA) _{#2}	36.3	≤100	With +5% Tolerance	Pass
L ₉₀ Lumen Maintenance Life (Hours)	48000	≥36000	None.	Pass
Color Maintenance	0.0032	≤0.007	≤0.0074	Pass

Note:

- The test results were measured directly from the test equipment.
- The DLC requirements were listed according to DLC Technical Requirements V5.1.
- The conclusion is for reference only. Test report that indicate product performance meets DLC Technical Requirements do not represent official DLC product qualification. All decisions regarding product qualification are made by the DLC.





Test Data

[Integrating Sphere System]


Photometric and Electrical Measurement Result

Voltage (V)	Frequency (Hz)	Current (A)	Power (W)	Power Factor	Luminous Flux(lm)	Efficacy (lm/W)
120.0	60	0.9773	116.8	0.9963	17179.8	147.09

Radiant Flux (W)	CCT (K)	Duv	x	y	u'	v'
52.175	4030	-0.00262	0.3774	0.3693	0.2261	0.4978

Color Rendering Index

Ra			
82.6			
R1	R2	R3	R4
82	93	94	79
R5	R6	R7	R8
82	89	81	61
R9	R10	R11	R12
5	83	77	64
R13	R14	R15	
85	98	76	









ANSI/IES TM-30-18 Color Rendition Report

Source: User SPD

Manufacturer: P.Q.L., Inc.

Date: 2025/9/23

Model: HLT1CP1152CUW 4000K




Notes: This is a recommended method for displaying ANSI/IES TM-30-18 information.

x 0.3774
 y 0.3693
 u' 0.2261
 v' 0.4978


CIE 13.3-1995 (CRI)	
R_a	83
R_9	4

Colors are for visual orientation purposes only. Created with the ANSI/IES TM-30-18 Calculator Version 2.00.


Relative Spectral Power Distribution



CIE 1931 x y Chromaticity Diagram



ANSI C78.377-2017 Chromaticity Quadrangles



[Goniophotometer System]


Electrical Measurement

Input Voltage (V)	Frequency (Hz)	Input Current (A)	Power (W)	Power Factor
120.0	60	0.977	117.18	0.999

Photometric Measurement

Luminous Flux (lm)	Efficacy (lm/W)	I _{max} (cd)	S/MH (C0/180)	S/MH (C90/270)
17180.2	146.66	8606.2	1.23	1.20

Luminous Intensity Distribution



	C0/180	C45/225	C90/270	C135/315	AVG.
Beam Angle (50% I _{max}):	92.3	87.5	82.9	87.5	87.6
Field Angle (10% I _{max}):	141.8	132.3	123.9	132.3	132.6

Luminous Intensity (cd) Distribution Data

$\begin{matrix} C \\ \backslash \\ Y \end{matrix}$	0°	22.5°	45°	67.5°	90°	112.5°	135°	157.5°
0.0°	8593.9	8593.9	8593.9	8593.9	8593.9	8593.9	8593.9	8593.9
5.0°	8555.3	8550.8	8551.0	8542.7	8535.8	8529.2	8546.8	8550.8
10.0°	8432.1	8419.1	8415.5	8402.3	8421.4	8404.6	8424.2	8438.0
15.0°	8246.9	8217.4	8198.4	8175.4	8205.1	8186.2	8229.5	8257.1
20.0°	7968.1	7913.5	7882.6	7852.4	7900.5	7857.9	7915.0	7967.6
25.0°	7602.0	7563.3	7487.5	7452.5	7500.5	7471.4	7502.6	7602.9
30.0°	7149.6	7076.8	6947.7	6783.2	6750.1	6798.1	7006.4	7152.0
35.0°	6523.9	6454.2	6054.4	5694.0	5595.3	5743.2	6124.9	6517.9
40.0°	5603.7	5329.3	4853.0	4485.4	4292.5	4536.5	4944.0	5434.9
45.0°	4532.0	3950.4	3769.7	3485.1	3091.5	3518.2	3855.2	4045.7
50.0°	3578.0	2730.8	2698.3	2547.0	2050.2	2604.6	2779.3	2780.5
55.0°	2672.2	1729.4	1772.7	1804.9	1276.3	1856.6	1833.3	1776.2
60.0°	1903.1	1044.2	1151.6	1330.1	876.4	1368.9	1188.1	1075.4
65.0°	1363.7	763.5	873.8	1031.1	711.0	1045.4	885.9	772.2
70.0°	928.0	687.9	706.5	764.1	566.7	769.5	721.1	694.3
75.0°	568.1	557.3	531.6	535.5	449.9	536.7	544.3	562.3
80.0°	341.5	380.2	340.2	327.8	317.5	331.4	350.6	387.6
85.0°	168.2	143.6	123.8	102.3	86.9	102.0	139.1	164.8
90.0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95.0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100.0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105.0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110.0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115.0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120.0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125.0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130.0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135.0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140.0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145.0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150.0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155.0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160.0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165.0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170.0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175.0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180.0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

Luminous Intensity (cd) Distribution Data (cont.)

$\frac{C}{\gamma}$	180°	202.5°	225°	247.5°	270°	292.5°	315°	337.5°
0.0°	8593.9	8593.9	8593.9	8593.9	8593.9	8593.9	8593.9	8593.9
5.0°	8548.8	8561.0	8566.8	8578.1	8569.7	8581.2	8584.6	8555.2
10.0°	8435.2	8461.9	8482.7	8507.0	8491.7	8489.1	8471.6	8432.8
15.0°	8249.3	8294.0	8332.2	8333.0	8331.0	8330.6	8299.9	8260.9
20.0°	7975.6	8030.0	8051.3	8072.8	8060.8	8060.2	8027.6	7982.0
25.0°	7633.8	7689.8	7698.8	7731.2	7708.7	7695.0	7665.4	7641.8
30.0°	7164.6	7240.6	7275.9	7247.3	7207.8	7218.5	7213.8	7163.9
35.0°	6540.9	6674.7	6599.3	6383.3	6283.6	6348.3	6526.7	6578.0
40.0°	5612.2	5756.4	5474.8	5199.4	5066.7	5195.5	5415.8	5626.0
45.0°	4522.8	4397.3	4285.1	4069.7	3780.1	4076.5	4219.8	4244.3
50.0°	3557.2	3119.9	3167.4	3109.6	2637.9	3124.9	3093.5	2980.2
55.0°	2637.1	2022.0	2125.9	2228.8	1693.6	2272.9	2053.8	1917.4
60.0°	1882.0	1210.4	1332.7	1608.2	1081.1	1634.2	1280.1	1154.4
65.0°	1350.1	821.9	935.2	1212.4	802.0	1222.4	919.2	803.7
70.0°	921.9	719.0	768.5	923.7	656.0	911.2	765.1	711.4
75.0°	567.4	599.0	601.9	656.0	512.0	651.7	603.7	592.4
80.0°	339.8	416.4	420.4	449.0	406.8	439.2	413.8	408.2
85.0°	160.4	203.8	219.5	227.2	229.5	222.5	215.6	181.5
90.0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
95.0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
100.0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
105.0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
110.0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115.0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
120.0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
125.0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
130.0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
135.0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
140.0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
145.0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
150.0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
155.0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
160.0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
165.0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
170.0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
175.0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
180.0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

Test Model: HLT1CP1152CUW

Control setting: 92W

Integrating Sphere THDi · PF Test; Orientation: Downward;

Test Voltage	Test Item	Test Result	DLC Requirements	DLC Requirements(With tolerances and/or allowances)	Conclusion
120	Power Factor	0.9949	≥0.9	≥0.87	Pass
120	THDi	5.68%	≤20%	≤25%	Pass
277	Power Factor	0.9459	≥0.9	≥0.87	Pass
277	THDi	10.66%	≤20%	≤25%	Pass

Note:

1. The test results were measured directly from the test equipment.
2. The DLC requirements were listed according to DLC Technical Requirements V5.1.
3. The conclusion is for reference only. Test report that indicate product performance meets DLC Technical Requirements do not represent official DLC product qualification. All decisions regarding product qualification are made by the DLC.

Test Data

[Integrating Sphere System]


Photometric and Electrical Measurement Result

Voltage (V)	Frequency (Hz)	Current (A)	Power (W)	Power Factor	Luminous Flux(lm)	Efficacy (lm/W)
120.0	60	0.7373	88.06	0.9949	13564	154.04

Radiant Flux (W)	CCT (K)	Duv	x	y	u'	v'
41.099	3995	-0.0025	0.3789	0.3705	0.2266	0.4986

Color Rendering Index

Ra			
82.7			
R1	R2	R3	R4
82	93	94	79
R5	R6	R7	R8
82	89	82	61
R9	R10	R11	R12
5	83	78	64
R13	R14	R15	
85	98	76	









ANSI/IES TM-30-18 Color Rendition Report

Source: User SPD

Manufacturer: P.Q.L., Inc.

Date: 2025/9/23

Model: HLT1CP1152CUW 4000K




Notes: This is a recommended method for displaying ANSI/IES TM-30-18 information.

x 0.3789
 y 0.3705
 u' 0.2266
 v' 0.4986


CIE 13.3-1995 (CRI)
 R_a 83
 R_9 5

Colors are for visual orientation purposes only. Created with the ANSI/IES TM-30-18 Calculator Version 2.00.


Relative Spectral Power Distribution



CIE 1931 x y Chromaticity Diagram



ANSI C78.377-2017 Chromaticity Quadrangles



Test Model: HLT1CP1152CUW

Control setting: 78W

Integrating Sphere THDi · PF Test; Orientation: Downward;

Test Voltage	Test Item	Test Result	DLC Requirements	DLC Requirements(With tolerances and/or allowances)	Conclusion
120	Power Factor	0.9941	≥0.9	≥0.87	Pass
120	THDi	5.55%	≤20%	≤25%	Pass
277	Power Factor	0.9265	≥0.9	≥0.87	Pass
277	THDi	13.61%	≤20%	≤25%	Pass

Note:

1. The test results were measured directly from the test equipment.
2. The DLC requirements were listed according to DLC Technical Requirements V5.1.
3. The conclusion is for reference only. Test report that indicate product performance meets DLC Technical Requirements do not represent official DLC product qualification. All decisions regarding product qualification are made by the DLC.

Test Data

[Integrating Sphere System]


Photometric and Electrical Measurement Result

Voltage (V)	Frequency (Hz)	Current (A)	Power (W)	Power Factor	Luminous Flux(lm)	Efficacy (lm/W)
120.0	60	0.6201	74	0.9941	11746	158.73

Radiant Flux (W)	CCT (K)	Duv	x	y	u'	v'
35.509	3953	-0.0024	0.3808	0.3719	0.2273	0.4995

Color Rendering Index

Ra			
82.8			
R1	R2	R3	R4
82	93	94	79
R5	R6	R7	R8
82	89	82	61
R9	R10	R11	R12
5	83	78	63
R13	R14	R15	
85	98	76	









ANSI/IES TM-30-18 Color Rendition Report

Source: User SPD

Manufacturer: P.Q.L., Inc.

Date: 2025/9/23

Model: HLT1CP1152CUW 4000K




Notes: This is a recommended method for displaying ANSI/IES TM-30-18 information.

x 0.3808
y 0.3719
u' 0.2273
v' 0.4995


CIE 13.3-1995 (CRI)
R_a 83
R_g 5

Colors are for visual orientation purposes only. Created with the ANSI/IES TM-30-18 Calculator Version 2.00.


Relative Spectral Power Distribution



CIE 1931 x y Chromaticity Diagram



ANSI C78.377-2017 Chromaticity Quadrangles



Test Model: HLT1CP1152CUW
Control setting: 115W

Integrating Sphere Test; Orientation: Downward; Test Voltage: 120V 60Hz:

Test Item	Test Result	DLC Requirements	DLC Requirements(With tolerances only)	Conclusion
Light Output(lm)	17544.8	≥10000	≥9000	Pass
Power(W)	119.21	None.	None.	N/A
Total Efficacy(lm/W)	147.18	≥135	≥130.95	Pass
CCT(K)	4999	None ⁱ	None.	N/A
Duv	0.00182	None ⁱ	None.	N/A
IES R _r	81	70	69	Pass
IES R _g	92	89	88	
IES Rcs,h1	-15%	-18%~23%	-19%~24%	
R _a	80.2	≥70	≥69	
R ₉	-10	≥-40	≥-41	

Note:

- i. White-tunable products are not required to meet the chromaticity requirements in DLC V5.1.

Integrating Sphere THDi、PF Test; Orientation: Downward;

Test Voltage	Test Item	Test Result	DLC Requirements	DLC Requirements(With tolerances and/or allowances)	Conclusion
120	Power Factor	0.9964	≥0.9	≥0.87	Pass
120	THDi	5.19%	≤20%	≤25%	Pass
277	Power Factor	0.9649	≥0.9	≥0.87	Pass
277	THDi	8.28%	≤20%	≤25%	Pass

Note:

- The test results were measured directly from the test equipment.
- The DLC requirements were listed according to DLC Technical Requirements V5.1.
- The conclusion is for reference only. Test report that indicate product performance meets DLC Technical Requirements do not represent official DLC product qualification. All decisions regarding product qualification are made by the DLC.

Test Data

[Integrating Sphere System]


Photometric and Electrical Measurement Result

Voltage (V)	Frequency (Hz)	Current (A)	Power (W)	Power Factor	Luminous Flux(lm)	Efficacy (lm/W)
120.0	60	0.997	119.21	0.9964	17544.8	147.18

Radiant Flux (W)	CCT (K)	Duv	x	y	u'	v'
53.150	4999	0.00182	0.3455	0.3556	0.2102	0.4867

Color Rendering Index

Ra			
80.2			
R1	R2	R3	R4
78	89	94	76
R5	R6	R7	R8
78	84	83	60
R9	R10	R11	R12
-10	74	74	54
R13	R14	R15	
81	97	71	









ANSI/IES TM-30-18 Color Rendition Report

Source: User SPD

Manufacturer: P.Q.L., Inc.

Date: 2025/9/23

Model: HLT1CP1152CUW 5000K




Notes: This is a recommended method for displaying ANSI/IES TM-30-18 information.

x 0.3455
 y 0.3556
 u' 0.2102
 v' 0.4867


CIE 13.3-1995 (CRI)
 R_a 80
 R_g -12

Colors are for visual orientation purposes only. Created with the ANSI/IES TM-30-18 Calculator Version 2.00.


Relative Spectral Power Distribution



CIE 1931 x y Chromaticity Diagram



ANSI C78.377-2017 Chromaticity Quadrangles



6. Description of Test Equipment

Device	Manufacture	Model No	Serial No	Calibration date	Calibration due date
Integrating Sphere	INVENTFINE	Dia 1.5m	JWWCV090112	2025-06-18	2026-06-17
Power Meter	INVENTFINE	WT500	GSJWQ20009	2025-04-10	2026-04-09
Spectral photometer	INVENTFINE	CMS-3S	GSGSE100017	2025-06-18	2026-06-17
AC Power Supply	INVENTFINE	CHP500	JWJSD010071	2025-04-10	2026-04-09
Standard Light Source	Osram	24V/50W	JWWCR020104	2025-07-10	2027-07-09
Thermal Meter	ANYMETRE	TH-20E	N/A	2025-06-10	2026-06-09
DC Power Supply	INVENTFINE	WL3005	JWWCP020069	2025-04-10	2026-04-09
AC Power Supply	INVENTFINE	CHP-5KVA	900511765	2025-04-10	2026-04-09
DC Power Supply	INVENTFINE	WL3010	JWDMP030001	2025-04-10	2026-04-09
Power Meter	INVENTFINE	WT500	GSDSQ200007	2025-04-10	2026-04-09
Goniophotometer	INVENTFINE	GPM-1900	YWGCF120001	2025-06-03	2026-06-02
Wireless Weather Station	ZHONGXING	KG218	N/A	2025-04-08	2026-04-07
Standard Light Source	INVENTFINE	N/A	JWBYR040008	2023-11-18	2025-11-17
Digital Multimeter	FLUKE	115C	37840512WS	2025-04-10	2026-04-09
Hybrid Recorder	YOKOGAWA	DR230	47JH0903	2025-04-10	2026-04-09
Power Supply	SC	SC/BP-11003	1608110030553	2025-04-10	2026-04-09

Statement of Traceability: Bay Area Compliance Laboratories Corp. (Kunshan) attested that all calibration has been performed using suitable standards traceable to National Primary Standards and International System of Units (SI).

7. Test Method

Product was tested with no seasoning. All stabilization and measurements were made in compliance with IES LM-79-19. The ambient temperature of the sample was maintained at $25^{\circ}\text{C}\pm 1^{\circ}\text{C}$ during measurement. And relative humidity is less than 65%. The product was operated in its intended orientation in application during all testing.

Integrating Sphere System

The system includes AC power source, digital power meter, DC power supply, Spectroradiometer, and integrating sphere. The integrating sphere system is calibrated by standard spectrum light source before measurement. 4π geometry was used during measurement.

Goniophotometer System

Type C goniophotometer was used for measuring luminous intensity distribution. The vertical angle (γ) test intervals were set no more than 1 degree while data for 5 degree intervals is reported. The horizontal angle (C plane) test intervals were set no more than 22.5 degree.

ISTMT Test

The LED which has the highest temperature was measured at the location of LED case which is specified by LED source manufacturer and detailed by LM-80 report. The drive current of LED package/module/ array was calculated as the total output current of the driver measured by multimeter, divided by the number of branches in parallel of LEDs.

Declarations

1. The laboratory is not responsible for the authenticity of any information provided by the applicant. Information from the applicant that may affect test results is marked with "#".
2. The test data was only valid for the test sample(s). This report must not be duplicated or used in part without prior written consent from the laboratory.
3. This report may contain data that are not covered by the accreditation scope and marked with "★".
4. Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.
5. The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval.
6. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

*****END OF REPORT*****