



ORDERING CODE

HLT1

FEATURES

Spec-Select™ Linear High Bays provide the versatility of six fixtures in one, delivering energy-efficient, customizable lighting for any space.

- Selectable Wattage & CCT: Field adjustable output.
- High Lumen Output: Bright and energy-efficient.
- Integrated LED: Maintenance-free.
- HID/Fluorescent Replacement: Easy upgrade.
- Wide Beam Angle: Uniform light distribution.
- Durable Construction: Painted steel with smooth edges and rounded corners.
- Sensor Ready: Supports the Integrated Sensor Option (ISO) and is compatible with plug-in motion and daylight sensors (sold separately).
- Designed for suspended or pendant mounting, with V-hooks and 41.3" chains included.

APPLICATION

Larger warehouses, retail applications, commercial buildings and work areas.

Project _____

Date _____

Catalog # _____

Quantity _____

Type _____

PRODUCT INFORMATION

ELECTRICAL	
Wattages (Selectable)	78-92-115W / 100-115-135W / 155-185-200W 200-230-270W / 270-340-400W
Voltage	120-277V
Surge Protection	Built-In
Power Factor	0.9
THD	≤20
OPTICAL	
Efficiency (LPW)	Up to 150
CCT (Selectable)	4000K / 5000K
CRI	83
Beam Angle	120°
Dimming	0-10V
ENVIRONMENT	
Operating Temperature	-40° ~ 122°F
Suitable Location	Damp
CONSTRUCTION	
Housing	Sheet Metal
Lens	PC
Base / Power Supply	Hard Wired
Finish	White
LIFESPAN (Complete terms can be found on our website.)	
Life Hours	100,000
Warranty (Years)	5-Year Standard
LISTINGS	
Primary Use Designation	High-Bay Luminaires for Commercial and Industrial Buildings



ORDERING

HLT1	C		2C	U	W	
SERIES	LENGTH	OUTPUT ¹	CCT ¹	VOLTAGE	FINISH	SENSOR Pre-Installed
HLT1 Spec-Select™ Linear High Bay - 2 Panel	C 1.4FT	P115 Selectable: 78W, 92W, 115W P135 Selectable: 100W, 115W, 135W	2C Selectable: 4000K, 5000K	U 120-277V	W White	P1 Bi-Level Dimming, 100FT DIA (55708) Blank None
	C 1.9FT	P200 Selectable: 155W, 185W, 200W				
	C 2.6FT	P270 Selectable: 200W, 230W, 270W				
	C 3.7FT	P400 Selectable: 270W, 340W, 400W				

¹ Our fixtures come preset to the highest wattage and 5000K.**ACCESSORIES** (Field Installation)

CODE	DESCRIPTION	CASE
55708	PHOTO/MICROWAVE BI-LEVEL DIMMING SENSOR FOR ISO POWER-SELECT™ HB	56
55709	REMOTE CONTROL FOR PHOTO/MICROWAVE MOTION SENSOR	150
45002	100FT ROLL NO. 12 JACK CHAIN	Per Foot

PACKAGING

MASTER CASE	HLT1CP1152CUW	HLT1CP1352CUW	HLT1CP2002CUW	HLT1CP2702CUW	HLT1CP4002CUW
Quantity	4				2
Size (LxWxH)	17.7" x 8.7" x 11"		24.1" x 8.6" x 11"	32.4" x 8.7" x 11"	45.6" x 10.9" x 4.4"
Gross Weight (Lbs)	25.7		32.1	43.8	29.2
UPC	10811768027355	10811768028734	10811768028727	10811768028680	10811768029533
INDIVIDUAL BOX					
Size (LxWxH)	17.2" x 10.6" x 2"		23.6" x 10.6" x 2"	31.9" x 10.6" x 2"	44.8" x 10.6" x 2"
Gross Weight (Lbs)	6.4		8	10.9	14.6
UPC	811768027358	811768028737	811768028720	811768028683	811768029536

Tariff: 9405.11.6020

PERFORMANCE DATA

WATTAGE	LUMENS	LPW	CRI	CURRENT		POWER FACTOR	THD
				120V	277V		
78W	11,700	150	83	0.65A	0.28A	0.9	≤20
92W	13,800			0.76A	0.33A		7.7
100W	15,000			0.83A	0.36A		
115W	17,250			0.95A	0.41A		
135W	20,250			1.12A	0.48A		6.2
155W	23,250			1.29A	0.56A		
185W	27,750			1.54A	0.66A		5.8
200W	30,000			1.66A	0.72A		
230W	34,500			1.91A	0.83A		7.3
270W	40,500			2.25A	0.97A		
340W	51,000			2.83A	1.22A		
400W	60,000			3.33A	1.44A		

DIMENSIONS

