

VEGA FORMS IHEX Ambient Linear LED

CRI

95 min with R9 of 69 or better

CCT

2700K, 3000K, 3500K, 4000K, 5 Channel Color Tuning

Projected Lifetime

240,000 Hours (L80); 110,000 Hours (L90)

Dimming

0-10V dimming standard

Operating Temperature

-30°C to +55°C (-22°F to +131°F)

Location

Approved for dry and damp locations

Warranty

5 year Standard 10 year Optional

FIXTURE SERIES

 Client:______
 Order #:______

 Project Name:______
 Type: _______

Oty:______







Description

The $Vega^{\infty}$ Hex is a $2^{7/16}$ wide ambient linear architectural luminaire. Featuring a slim profile and robust construction, it provides a bold, design-driven lighting solution for modern offices, themed public areas, laboratories, libraries, and other indoor spaces. The Hex is available in standard widths of 4', 5', and 7' (measured edge to edge) with a range of lumen packages and color temperatures available, including 5-Channel Color Tuning.

Features

- Up to 1200 lm/ft direct, 1,400 lm/ft indirect at 4000K
- Profile Dimensions: 2.44" wide x 5" high
- End Caps: Die cast aluminum with powder coat finish
- Housing: Extruded Aluminum with powder coat finish
- Direct Lens: Extruded Satin Acrylic
- Indirect Lens: Extruded clear Acrylic
- Light Engine: Aluminum core LED board mounted to a white extruded chassis with integral driver and quick electrical disconnects for rapid tool-less servicing

OPTIONS

Ordering Options contact sales representative to order.

I IXTORE OFFICE	
HX2P	Hex 2 Pendant
DISTRIBUTION	
1	Direct/Indirect
D	Direct
WIDTH	
2	2'
3	3'
4	4'
OUTPUT DOWN	
L	7.5W/ft
М	10W/ft
Н	15W/ft
OUTPUT UP*	
L	7.5W/ft
М	10W/ft
Н	15W/ft

CCT DOWN	
27	2700K
30	3000K
35	3500K
40	4000K
5W	5 Channel Color Tuning ¹
CCT UP*	
27	2700K
30	3000K
35	3500K
40	4000K
5W	5 Channel Color Tuning ¹
VOLTAGE	
U	120-277V

С	Cable in Corner
CABLE LENGTH	
Α	24" Cable
В	48" Cable
D	60" Cable
F	72" Cable
G	96" Cable
FINISH ²	
W	Textured White
S	Textured Silver
В	Textured Black
C Textur	red Custom Colors

MOUNTING STYLE

DC	Dual Circuit for Up/Down ³
E	Emergency Battery Backup
Т	Daylight Sensor
М	Motion Sensor ⁴
V	Daylight/Occupancy Sensor ⁴
CONTRO	DLS
LE	LUTRON Ecosystem
LV	LUTRON VIVE
PE	PHILIPS Easysense
NL	nLight
EO	EnlightedONE System ⁴
WARRANTY ⁵	
-	5 Year Warranty
10	10 Year Warranty
10L	10 Year Warranty including labor



- *Only available when direct/indirect distribution is selected
- ² All finishes are textured unless specified otherwise by the customer
- Dual circuit offered with 6 wire cord two hots, neutral, ground, and 0-10V dimming
 Default sensor is the Enlighted One.
 Year Warranty is Standard unless specified

Dimensions

