



ENVIRO-LUME™ HALOGEN PARS

TRADITIONAL LIGHTING

Superior Life® Enviro-Lume™ Halogen lamps are engineered with the latest technology in filament design to deliver the longest lasting halogen on the market. PARs are ideal for retail and merchandise displays, accenting lighting, lobbies and offices.

FEATURES

- Up to 40% longer life
- Optimized lumen output
- Uniform beam without hot spots

Dimmable

APPLICATION

RESIDENTIAL & COMMERCIAL



Accent Lighting
Recessed Cans
Track Lighting
Merchandise Displays

WARRANTY



EISA COMPLIANT - Meets United States Minimum
Efficiency Standards. Highly Efficient.



Enviro-Lume IR™

Superior Life® Enviro-Lume IR™ Halogen lamps use the latest **infrared heat technology** which allows the lamp to burn cooler, generating less heat and last longer than a standard halogen. This allows for maximum efficiency, added energy savings and quality light output.



Infrared Technology

WATTS	ITEM#	DESCRIPTION	CEC STATUS	CCT	LUMENS	LM/W	BEAM	MOL	VOLTS	BASE	AVG. LIFE HOURS	STD HALOGEN EQUIV.	CASE
PAR30/LN - DIMMABLE													
53	96049	53PAR30/LN/FLOOD - ENVIRO-LUME IR™		3000K	1050	20	FLOOD	4.5"	120	MEDIUM	3,500	75W	15
	96053	53PAR30/LN/SPOT - ENVIRO-LUME IR™		3000K	1050	20	SPOT	4.4"	120	MEDIUM	3,500	75W	15

Enviro-Lume™

Superior Life® Enviro-Lume™ Halogen are an **energy efficient** alternative to the standard halogen.



Energy Efficient Alternative

WATTS	ITEM#	DESCRIPTION	CEC STATUS	CCT	LUMENS	LM/W	BEAM	MOL	VOLTS	BASE	AVG. LIFE HOURS	STD HALOGEN EQUIV.	CASE
PAR20 - DIMMABLE													
38	92009	38PAR20/FLOOD - ENVIRO-LUME™		3000K	500	13	FLOOD	3.1"	120	MEDIUM	1,500	50W	15
PAR30/SN - DIMMABLE													
38	92017	38PAR30/FLOOD - ENVIRO-LUME™		3000K	530	14	FLOOD	3.5"	120	MEDIUM	1,500	50W	15
60	92041	60PAR30/FLOOD - ENVIRO-LUME™		3000K	1070	18	FLOOD	3.5"	120	MEDIUM	1,500	75W	15
PAR30/LN - DIMMABLE													
38	92025	38PAR30/FLOOD/LN - ENVIRO-LUME™		3000K	520	14	FLOOD	4.5"	120	MEDIUM	1,500	50W	15
60	92049	60PAR30/FLOOD/LN - ENVIRO-LUME™		3000K	1070	18	FLOOD	4.5"	120	MEDIUM	1,500	75W	15
PAR38 - DIMMABLE													
38	92001	38PAR38/FLOOD - ENVIRO-LUME™		3000K	550	14	FLOOD	5.1"	120	MEDIUM	1,500	50W	15
70	92057	70PAR38/FLOOD - ENVIRO-LUME™		3000K	1310	19	FLOOD	5.1"	120	MEDIUM	1,500	90W	15
	92061	70PAR38/SPOT - ENVIRO-LUME™		3000K	1310	19	SPOT	5.1"	120	MEDIUM	1,500	90W	15

Note: CEC Status identifies items listed on the MAEDBS database that are in compliance with Title 20 or Title 24 Regulations. Visit www.cacertappliances.energy.ca.gov to confirm compliance. - Published lumens on products are approximate and may vary slightly. - Specifications are subject to change without notice. - Photos and drawings may not be to scale and are for general reference only.

