

Superior
Life



REMOTE
PHOSPHOR
LED TECHNOLOGY



WITH POWER

WITHOUT POWER

LED HIGH WATTAGE 360° REMOTE PHOSPHOR

DIRECT WIRE • HIGH BRIGHTNESS • ENERGY SAVING

Superior Life® High Wattage LED lamps with Remote Phosphors deliver high brightness with a uniform 360-degree light distribution. Our Remote Phosphor LED technology provides better lumen maintenance, color stability, and longer life, as well as eliminating the glare found in typical corn cob LEDs. The superior life hours of this lamp make it ideal for hard to reach places reducing maintenance.

FEATURES

- High Efficiency, Energy Saving
- High Performance LEDs - Highest lumens per watt light output.
- Superior Life® design
- Bright and consistent illumination
- Compact lightweight and easy installation
- Mercury Free - Environmentally friendly.
- Suitable for totally enclosed fixtures

APPLICATION

COMMERCIAL & INDUSTRIAL



Outdoor Spaces Warehouses
Parking Lots Roadways

WARRANTY*



QUALIFICATIONS*



*Warranty and Qualifications can vary per item, see technical data sheets (TDS) for specific information.



PREMIUM QUALITY LIGHTING® • Phone: 800-323-8107

© P.Q.L., Inc. • 2285 Ward Avenue • Simi Valley, CA 93065

www.PQLighting.com

Rev: 12/03/2020



REMOTE PHOSPHOR LAMPS

WATTS	ITEM#	DESCRIPTION	DLC*	CCT	LUMENS	LM/W	BEAM	CRI	MOL	VOLTS	BASE	AVG. LIFE HOURS	TRAD. EQUIV.	CASE
MEDIUM BASE - NON-DIMMABLE														
12	91800	12WT21/360°/30K//MED/120-277V - SL*		3000K	1620	135	270°	80	5.6"	120-277	MEDIUM	50,000	50W	30
	91801	12WT21/360°/50K//MED/120-277V - SL*		5000K	1740	145	270°	80	5.6"	120-277	MEDIUM	50,000	50W	30
18	91802	18WT21/360°/30K/MED/120-277V - SL*		3000K	2430	135	270°	80	6"	120-277	MEDIUM	50,000	75W	30
	91803	18WT21/360°/50K/MED/120-277V - SL*		5000K	2610	145	270°	80	6"	120-277	MEDIUM	50,000	75W	30
25	91804	25WT26/360°/30K/MED/120-277V - SL*		3000K	3375	135	270°	80	7"	120-277	MEDIUM	50,000	100W	20
	91805	25WT26/360°/50K/MED/120-277V - SL*		5000K	3625	145	270°	80	7"	120-277	MEDIUM	50,000	100W	20
42	91806	42WT30/360°/30K/MED/120-277V - SL*		3000K	5670	135	270°	80	8.7"	120-277	MEDIUM	50,000	175W	20
	91807	42WT30/360°/50K/MED/120-277V - SL*		5000K	6090	145	270°	80	8.7"	120-277	MEDIUM	50,000	175W	20

MOGUL BASE - NON-DIMMABLE (DLC* lists watts and lumens efficacy of the whole fixture.)

65	91808	65WT40/360°/30K/MOG/120-277V - SL*	★	3000K	8775	135	270°	80	10.9"	120-277	MOGUL	50,000	200W	8
	91809	65WT40/360°/50K/MOG/120-277V - SL*	★	5000K	9425	145	270°	80	10.9"	120-277	MOGUL	50,000	200W	8
77	91810	77WT40/360°/30K/MOG/120-277V - SL*	★	3000K	10780	140	270°	72	12"	120-277	MOGUL	50,000	250W	8
	91811	77WT40/360°/50K/MOG/120-277V - SL*	★	5000K	12000	156	270°	72	12"	120-277	MOGUL	50,000	250W	8

ACCESSORIES

ITEM#	DESCRIPTION	CASE
82234	E39 (MOGUL) TO E26 (MEDIUM) LAMPHOLDER REDUCER	10
82235	E26 (MEDIUM) TO E39 (MOGUL) LAMPHOLDER ENLARGER	10



82234



82235

Key: SL = Superior Life® / P = Pending / LM = Lumens / TRAD. EQUIV. = Traditional Equivalent

Note: Not all product variations listed on this page are DLC qualified. Visit www.designlights.org/search to confirm qualification. • Published lumens on LED products are approximate and may vary slightly. • Specifications are subject to change without notice. • Photos and drawings may not be to scale and are for general reference only.



PREMIUM QUALITY LIGHTING® • Phone: 800-323-8107
© P.Q.L., Inc. • 2285 Ward Avenue • Simi Valley, CA 93065

www.PQLighting.com
Rev: 12/03/2020