



LOW PROFILE  
CANOPY



V3 CANOPY



ORIGINAL & V2 CANOPY



V4 CANOPY

# LED CANOPY FIXTURES

EXTERIOR LIGHTING • HIGH LUMEN OUTPUT

Superior Life® LED Canopy lights are excellent replacements for traditional HID fixtures. They deliver bright uniform light providing added security lighting. With no bulbs to replace they are virtually maintenance free, save energy and have a long life (50,000 hrs) significantly reducing operational costs over the life of the fixture, quickly paying for itself.

## FEATURES

- High Efficiency, Energy Saving
- High Performance LEDs - High lumens per watt light output.
- Durable Construction
- Compact low profile design
- Mercury Free - Environmentally friendly.
- Lightweight and easy installation
- Wet Location Rated
- Customizable - available in a variety of finishes and color temperatures. Contact your sales representative to discuss your specific needs.

## APPLICATION

COMMERCIAL & INDUSTRIAL



Gas Stations      Storage Areas

Pathways          Underpasses

Perimeter Lighting

Parking Structures

## WARRANTY\*



## QUALIFICATIONS\*



\*Warranty and Qualifications can vary per item, see technical data sheets (TDS) for specific information.

Fixtures are available in a variety of finishes and color temperatures.  
Contact your sales representative to discuss your specific needs.



## CANOPY FIXTURES

WATTS	ITEM#	DESCRIPTION	DLC®	UL/ETL	CCT	LUMENS	LM/W	BEAM	CRI	VOLTS	FINISH	AVG. LIFE HOURS	TRAD. EQUIV.	CASE
<b>0-10V DIMMING</b>														
21	83086	CANOPY 21W/50K/120-277V/BLACK/DIMM/V4 - SL®	★	ETL	5000K	2890	138	100° x 60°	80	120-277	BLACK	50,000	100W	4
	83086-W	CANOPY 21W/50K/120-277V/WHITE/DIMM/V4 - SL®	★	ETL	5000K	2890	138	100° x 60°	80	120-277	WHITE	50,000	100W	4
40	83088	CANOPY 40W/50K/120-277V/BLACK/DIMM/V4 - SL®	★	ETL	5000K	4800	120	100° x 60°	80	120-277	BLACK	50,000	175W	4
	83088-W	CANOPY 40W/50K/120-277V/WHITE/DIMM/V4 - SL®	★	ETL	5000K	4800	120	100° x 60°	80	120-277	WHITE	50,000	175W	4
60	83089	CANOPY 60W/40K/120-277V/BLACK/DIMM/V4 - SL®	★	ETL	4000K	6720	112	100° x 60°	80	120-277	BLACK	50,000	400W	4
	83090	CANOPY 60W/50K/120-277V/BLACK/DIMM/V4 - SL®	★	ETL	5000K	6900	115	100° x 60°	80	120-277	BLACK	50,000	400W	4
	83090-W	CANOPY 60W/50K/120-277V/WHITE/DIMM/V4 - SL®	★	ETL	5000K	6900	115	100° x 60°	80	120-277	WHITE	50,000	400W	4
75	83092	CANOPY 75W/50K/120-277V/BLACK/DIMM/V4 - SL®	★	ETL	5000K	8625	115	100° x 60°	80	120-277	BLACK	50,000	400W	4
	83092-W	CANOPY 75W/50K/120-277V/WHITE/DIMM/V4 - SL®	★	ETL	5000K	8625	115	100° x 60°	80	120-277	WHITE	50,000	400W	4
<b>NON-DIMMABLE</b>														
40	83338	CANOPY 40W/40K/120-277V/BLACK/V3 - SL®	★	UL	4000K	5350	134	160°	70	120-277	BLACK	50,000	100W	6

## WILDLIFE FRIENDLY CANOPY FIXTURES

WATTS	ITEM#	DESCRIPTION	DLC®	UL/ETL	CCT	LUMENS	LM/W	BEAM	CRI	VOLTS	FINISH	AVG. LIFE HOURS	TRAD. EQUIV.	CASE
<b>NON-DIMMABLE</b>														
45	83228	CANOPY 45W/AMBER/100-277V/BLACK - SL® <i>Qualification Model # L-CNPY-45-MV-22K-B</i>	N/A		AMBER	746	17	160°	19	100-277	BLACK	50,000	150W	1

## LOW PROFILE CANOPY FIXTURES

WATTS	ITEM#	DESCRIPTION	DLC®	UL/ETL	CCT	LUMENS	LM/W	BEAM	CRI	VOLTS	FINISH	AVG. LIFE HOURS	TRAD. EQUIV.	CASE
<b>0-10V DIMMING</b>														
75	90004	LOW PROFILE CANOPY 75W/50K/100-277V/DIMM - SL®	★	ETL	5000K	9300	124	110°	80	100-277	WHITE	50,000	250W	1
100	90005	LOW PROFILE CANOPY 100W/50K/100-277V/DIMM - SL®	★	ETL	5000K	12400	124	110°	80	100-277	WHITE	50,000	400W	1
130	90006	LOW PROFILE CANOPY 130W/50K/100-277V/DIMM - SL®	★	ETL	5000K	16120	124	110°	80	100-277	WHITE	50,000	400W	1

## ACCESSORIES

ITEM#	DESCRIPTION	CASE
54888	360° BI-LEVEL AND DAYLIGHT HARVESTING MICROWAVE SENSOR 26" DIA., 8-40' HEIGHT 800W/1200W • 120/277V - SL®	100



54888

Key: DIMM = DIMMABLE / SL = Superior Life® / P = Pending / LM = Lumens / TRAD. EQUIV. = Traditional Equivalent

NOTE: Not all product variations listed on this page are DLC® qualified. Visit [www.designlights.org/search](http://www.designlights.org/search) to confirm qualification. • Published lumens on LED products are approximate and may vary slightly. • Specifications are subject to change without notice. • Photos and drawings may not be to scale and are for general reference only.



**PREMIUM QUALITY LIGHTING®** • Phone: 800-323-8107  
© P.Q.L., Inc. • 2285 Ward Avenue • Simi Valley, CA 93065

**www.PQLighting.com**  
Rev: 08/17/2020