



LOW PROFILE CANOPY



ORIGINAL & V2 CANOPY



V3 CANOPY

LED CANOPY FIXTURES

EXTERIOR LIGHTING • HIGH LUMEN OUTPUT

Superior Life® LED Canopy lights are excellent replacements for traditional HID fixtures. They deliver bright uniform light providing added security lighting. With no bulbs to replace they are virtually maintenance free, save energy and have a long life (50,000 hrs) significantly reducing operational costs over the life of the fixture, quickly paying for itself.

FEATURES

- High Efficiency, Energy Saving
- High Performance LEDs - Bright and high lumens per watt light output.
- Durable Construction
- Compact low profile design
- Mercury Free - Environmentally friendly.
- Lightweight and easy installation
- Wet Location Rated

APPLICATIONS

COMMERCIAL & INDUSTRIAL



- Gas Stations
- Storage Areas
- Pathways
- Underpasses
- Perimeter Lighting
- Parking Structures

WARRANTY



QUALIFICATIONS



Qualifications vary, see technical data for specific information.



LED CANOPY FIXTURES



CANOPY FIXTURES

LED OUTDOOR FIXTURE - LED CANOPY

WATTS	ITEM#	DESCRIPTION	DLC*	UL/ETL	CCT	LUMENS	LM/W	BEAM	CRI	VOLTS	FINISH	LIFE	TRAD. EQUIV.	CASE
-------	-------	-------------	------	--------	-----	--------	------	------	-----	-------	--------	------	--------------	------

DIMMABLE

65	83232	CANOPY 65W/40K/120-277V/BLACK/DIMMABLE - SL*	★	UL	4000K	6500	100	160°	70	120-277	BLACK	50K	200W	1
----	-------	--	---	----	-------	------	-----	------	----	---------	-------	-----	------	---

NON-DIMMABLE

27	83245	CANOPY 27W/50K/120-277V/BLACK - SL* <i>Qualification Model # L-CNPY-27-MV-50K-B</i>	★	UL	5000K	3800	141	160°	70	120-277	BLACK	50K	100W	6
	83229	CANOPY 27W/50K/120-277V/WHITE - SL* <i>Qualification Model # L-CNPY-27-MV-50K-W</i>	★	UL	5000K	3800	141	160°	70	120-277	WHITE	50K	100W	6
40	83344	CANOPY 40W/50K/120-277V/BLACK/V3 - SL*	★	UL	5000K	5450	136	160°	70	120-277	BLACK	50K	100W	6
45	83230	CANOPY 45W/40K/120-277V/BLACK - SL*	★	UL	4000K	4005	92	160°	84	100-277	BLACK	50K	150W	1
60	83347	CANOPY 60W/40K/120-277V/BLACK/V3 - SL* <i>Qualification Model # L-CNPY-60-MV-40K-B</i>	★	UL	4000K	7800	130	160°	72	120-277	BLACK	50K	400W	6
	83348	CANOPY 60W/50K/120-277V/BLACK/V3 - SL* <i>Qualification Model # L-CNPY-60-MV-50K-B</i>	★	UL	5000K	8000	133	160°	70	120-277	BLACK	50K	400W	6

WILDLIFE FRIENDLY

LED OUTDOOR FIXTURE - LED CANOPY - AMBER

WATTS	ITEM#	DESCRIPTION	DLC	UL/ETL	CCT	LUMENS	LM/W	BEAM	CRI	VOLTS	FINISH	LIFE	TRAD. EQUIV.	CASE
-------	-------	-------------	-----	--------	-----	--------	------	------	-----	-------	--------	------	--------------	------

NON-DIMMABLE

45	83228	CANOPY 45W/AMBER/100-277V/BLACK - SL*			AMBER	746	17	160°	19	100-277	BLACK	50K	150W	1
----	-------	---------------------------------------	--	--	-------	-----	----	------	----	---------	-------	-----	------	---

LOW PROFILE CANOPY FIXTURES

LED OUTDOOR FIXTURE - LED CANOPY

WATTS	ITEM#	DESCRIPTION	DLC*	UL/ETL	CCT	LUMENS	LM/W	BEAM	CRI	VOLTS	FINISH	LIFE	TRAD. EQUIV.	CASE
-------	-------	-------------	------	--------	-----	--------	------	------	-----	-------	--------	------	--------------	------

DIMMABLE

75	90004	LOW PROFILE CANOPY 75W/50K/100-277V/DIMMABLE - SL*	★	ETL	5000K	9300	124	110°	80	100-277	WHITE	50K	250W	1
100	90005	LOW PROFILE CANOPY 100W/50K/100-277V/DIMMABLE - SL*	★	ETL	5000K	12400	124	110°	80	100-277	WHITE	50K	400W	1
130	90006	LOW PROFILE CANOPY 130W/50K/100-277V/DIMMABLE - SL*	★	ETL	5000K	16120	124	110°	80	100-277	WHITE	50K	400W	1

Key: BLK = Black / SL = Superior Life® / LM = Lumens / TRAD. EQUIV. = Traditional Equivalent

Note: Some items are not compatible with dimming devices. • Not all product variations listed on this page are DLC qualified. Visit www.designlights.org/search to confirm qualification. • Published lumens on LED products are approximate and may vary slightly. • Specifications are subject to change without notice. • Photos and drawings may not be to scale and are for general reference only.

