



LED EXTERIOR LIGHTING

CANOPY FIXTURES

Superior Life® LED Canopy lights are excellent replacements for traditional HID fixtures. They deliver bright uniform light providing added security lighting. With no bulbs to replace they are virtually maintenance free, save energy and have a long life (50,000 hrs) significantly reducing operational costs over the life of the fixture, quickly paying for itself.

Application: Ideal for commercial and industrial applications; gas stations, underpasses, storage areas, covered walkways, and security lighting.

Fixtures are available in a variety of finishes and color temperatures.

Contact your sales representative to discuss your specific needs.



LED EXTERIOR LIGHTING CANOPY FIXTURES

PQL
PREMIUM QUALITY LIGHTING®

FEATURES

- High Efficiency, Energy Saving
- High Performance LEDs - High lumens per watt light output.
- Durable Construction
- Compact low profile design
- Mercury Free - Environmentally friendly.
- Lightweight and easy installation
- Wet Location Rated
- Customizable - available in a variety of finishes and color temperatures.
Contact your sales representative to discuss your specific needs.



CANOPY FIXTURES



RECESSED CANOPY

Note: Warranty and Qualifications can vary per item, see technical data sheets (TDS) for specific information. • Not all product variations listed are DLC® qualified. Visit www.designlights.org/search to confirm qualification. • Published lumens on LED products are approximate and may vary slightly. • Specifications are subject to change without notice. • Photos and drawings may not be to scale and are for general reference only.



PREMIUM QUALITY LIGHTING® • Phone: 800-323-8107
© P.Q.L., Inc. • 2285 Ward Avenue • Simi Valley, CA 93065

www.PQLighting.com
Rev: 08/25/2022

LED EXTERIOR LIGHTING CANOPY FIXTURES & ACCESSORIES



CANOPY FIXTURES

WATTS	ITEM#	DESCRIPTION	DLC®	CCT	LUMENS	LPW	BEAM	CRI	VOLTS	FINISH	LIFE HOURS	TRAD. EQUIV.	CASE
SPEC-SELECT™ - 0-10V DIMMING (Selectable Wattage & CCT - 3000K / 4000K / 5000K)													
21/30/40	83100	CANOPY/21-30-40W/30-50K/DIMM/120-277V/BLK <i>Qualification Model # SSC-A-FSCI-1-MV-BLK</i>	★	30-50K	2894-5500	138	100° x 60°	82	120-277	BLACK	50,000	175W	4
	83099	CANOPY/21-30-40W/30-50K/DIMM/120-277V/WHT <i>Qualification Model # SSC-A-FSCI-1-MV-WHT</i>	★	30-50K	2894-5500	138	100° x 60°	82	120-277	WHITE	50,000	175W	4
40/50/60	83101	CANOPY/40-50-60W/30-50K/DIMM/120-277V/BLK <i>Qualification Model # SSC-B-FSCI-1-MV-BLK</i>	★	30-50K	5320-8000	133	100° x 60°	81	120-277	BLACK	50,000	400W	4
0-10V DIMMING													
21	83086	CANOPY/21W/50K/DIMM/120-277V/BLK	★	5000K	2890	138	100° x 60°	80	120-277	BLACK	50,000	100W	4
40	83088	CANOPY/40W/50K/DIMM/120-277V/BLK	★	5000K	4800	120	100° x 60°	80	120-277	BLACK	50,000	175W	4
60	83089	CANOPY/60W/40K/DIMM/120-277V/BLK	★	4000K	6720	112	100° x 60°	85	120-277	BLACK	50,000	400W	4
	83090	CANOPY/60W/50K/DIMM/120-277V/BLK	★	5000K	6900	115	100° x 60°	85	120-277	BLACK	50,000	400W	4
	83090-W	CANOPY/60W/50K/DIMM/120-277V/WHT	★	5000K	6900	115	100° x 60°	85	120-277	WHITE	50,000	400W	4
75	83092	CANOPY/75W/50K/DIMM/120-277V/BLK	★	5000K	8625	115	100° x 60°	85	120-277	BLACK	50,000	400W	4
	83092-W	CANOPY/75W/50K/DIMM/120-277V/WHT	★	5000K	8625	115	100° x 60°	85	120-277	WHITE	50,000	400W	4

RECESSED CANOPY FIXTURE

WATTS	ITEM#	DESCRIPTION	DLC®	CCT	LUMENS	LPW	BEAM	CRI	VOLTS	FINISH	LIFE HOURS	TRAD. EQUIV.	CASE
WATTAGE SELECTABLE - 0-10V DIMMING													
80/100 120/150	90010	CANOPY/80-100-120-150W/50K/DIMM/120-277V/WHT <i>Qualification Model # PSRC-150-50K-[PD,CL,WM]-WHT</i>	★	5000K	12080- 22700	151	100° x 100°	70	120-277	WHITE	50,000	400W	1

WILDLIFE FRIENDLY CANOPY FIXTURES

WATTS	ITEM#	DESCRIPTION	DLC®	CCT	LUMENS	LPW	BEAM	CRI	VOLTS	FINISH	LIFE HOURS	TRAD. EQUIV.	CASE
0-10V DIMMING													
40	83088-A	CANOPY/40W/AMBER/DIMM/120-277V/BLK	N/A	AMBER	--	--	100° x 60°	--	120-277	BLACK	50,000	150W	4
60	83090-A	CANOPY/60W/AMBER/DIMM/120-277V/BLK	N/A	AMBER	--	--	100° x 60°	--	120-277	BLACK	50,000	150W	4

ACCESSORIES

Check fixture TDS to confirm compatibility of accessories.

ITEM#	DESCRIPTION	CASE
54888	360° BI-LEVEL AND DAYLIGHT HARVESTING MICROWAVE SENSOR 26' DIA, 8-40' HEIGHT 800W/1200W • 120/277V	100



54888

Key: P = Pending / LPW = Lumens Per Watt / TRAD. EQUIV. = Traditional Equivalent

Note: Warranty and Qualifications can vary per item, see technical data sheets (TDS) for specific information. • Not all product variations listed are DLC® qualified. Visit www.designlights.org/search to confirm qualification. • Published lumens on LED products are approximate and may vary slightly. • Specifications are subject to change without notice. • Photos and drawings may not be to scale and are for general reference only.



PREMIUM QUALITY LIGHTING® • Phone: 800-323-8107
© P.Q.L., Inc. • 2285 Ward Avenue • Simi Valley, CA 93065

www.PQLighting.com
Rev: 08/25/2022