



# LED SURFACE FIXTURES

INDOOR • INTERIOR LIGHTING • INTEGRATED LED

The Superior Life® LED Surface Interior Fixtures are high quality with integrated LEDs for excellent efficiency and optimal performance. They consume less energy than traditional lighting, significantly reducing operating costs and are environmentally friendly.

## FEATURES

- High Efficiency, Energy Saving
- Sturdy construction - Die form cold-rolled steel housing.
- Designed for Surface or Suspended Chain Mounting
- Lightweight and easy installation
- Mercury Free - Environmentally friendly.
- Low heat reduces AC costs
- Dimmable (0-10V, Range 10% - 100%)

## APPLICATION

### COMMERCIAL & INDUSTRIAL



|               |             |
|---------------|-------------|
| Offices       | Schools     |
| Retail Stores | Warehouses  |
| Banking       | Work Spaces |

## WARRANTY\*



## QUALIFICATIONS\*



\*Warranty and Qualifications can vary per item, see technical data sheets (TDS) for specific information.



PREMIUM QUALITY LIGHTING® - Phone: 800-323-8107  
© P.Q.L., Inc. • 2285 Ward Avenue • Simi Valley, CA 93065

www.PQLighting.com

Rev: 11/20/2020



### DESIGNER STRIP FIXTURES - 120-277V

| WATTS                      | ITEM# | DESCRIPTION   | DLC® | CCT   | LUMENS | LM/W | BEAM | CRI | VOLTS   | AVG. LIFE HOURS | TRAD. EQUIV. | CASE |
|----------------------------|-------|---|------|-------|--------|------|------|-----|---------|-----------------|--------------|------|
| <b>2FT - 0-10V DIMMING</b> |       |   |      |       |        |      |      |     |         |                 |              |      |
| 20                         | 55458 | 24" DESIGNER STRIP - 20W/40K/120-277V/DIMMABLE/V2 - SL® | ★    | 4000K | 2620   | 131  | 130° | 82  | 120-277 | 50,000          | 100W         | 6    |
|                            | 55459 | 24" DESIGNER STRIP - 20W/50K/120-277V/DIMMABLE/V2 - SL® | ★    | 5000K | 2640   | 132  | 130° | 82  | 120-277 | 50,000          | 100W         | 6    |
| <b>4FT - 0-10V DIMMING</b> |       |   |      |       |        |      |      |     |         |                 |              |      |
| 18                         | 55461 | 48" DESIGNER STRIP - 18W/40K/120-277V/DIMMABLE/V2 - SL® | ★    | 4000K | 2502   | 139  | 130° | 82  | 120-277 | 50,000          | 100W         | 6    |
|                            | 55462 | 48" DESIGNER STRIP - 18W/50K/120-277V/DIMMABLE/V2 - SL® | ★    | 5000K | 2520   | 140  | 130° | 82  | 120-277 | 50,000          | 100W         | 6    |
| 35                         | 55464 | 48" DESIGNER STRIP - 35W/40K/120-277V/DIMMABLE/V2 - SL® | ★    | 4000K | 4585   | 131  | 130° | 82  | 120-277 | 50,000          | 150W         | 6    |
|                            | 55465 | 48" DESIGNER STRIP - 35W/50K/120-277V/DIMMABLE/V2 - SL® | ★    | 5000K | 4620   | 132  | 130° | 82  | 120-277 | 50,000          | 150W         | 6    |
| <b>8FT - 0-10V DIMMING</b> |       |   |      |       |        |      |      |     |         |                 |              |      |
| 38                         | 55467 | 96" DESIGNER STRIP - 38W/40K/120-277V/DIMMABLE/V2 - SL® | ★    | 4000K | 5282   | 139  | 130° | 82  | 120-277 | 50,000          | 150W         | 4    |
| 65                         | 55470 | 96" DESIGNER STRIP - 65W/40K/120-277V/DIMMABLE/V2 - SL® | ★    | 4000K | 8515   | 131  | 130° | 82  | 120-277 | 50,000          | 200W         | 4    |
|                            | 55471 | 96" DESIGNER STRIP - 65W/50K/120-277V/DIMMABLE/V2 - SL® | ★    | 5000K | 8580   | 132  | 130° | 82  | 120-277 | 50,000          | 200W         | 4    |

### WRAP-A-ROUND FIXTURES - 120-277V

| WATTS                      | ITEM# | DESCRIPTION   | DLC® | CCT   | LUMENS | LM/W | BEAM | CRI | VOLTS   | AVG. LIFE HOURS | TRAD. EQUIV. | CASE |
|----------------------------|-------|---|------|-------|--------|------|------|-----|---------|-----------------|--------------|------|
| <b>4FT - 0-10V DIMMING</b> |       |   |      |       |        |      |      |     |         |                 |              |      |
| 42                         | 55259 | WRAP A-ROUND 48" 42W/40K/FR/120-277V/DIMMABLE - SL® | ★    | 4000K | 4410   | 105  | 100° | 80  | 120-277 | 50,000          | 150W         | 4    |
|                            | 55260 | WRAP A-ROUND 48" 42W/50K/FR/120-277V/DIMMABLE - SL® | ★    | 5000K | 4452   | 106  | 100° | 80  | 120-277 | 50,000          | 150W         | 4    |

### SPEC-SELECT™ FIXTURES - 120-277V (Selectable Wattage & CCT - Warm White / Cool White / Sky-Brite®)

| WATTS  | ITEM#       | DESCRIPTION   | DLC® | CCT    | LUMENS     | LM/W | BEAM | CRI | VOLTS   | AVG. LIFE HOURS | TRAD. EQUIV. | CASE |
|--|-------------|---|------|--------|------------|------|------|-----|---------|-----------------|--------------|------|
| <b>4FT DESIGNER STRIP - 0-10V DIMMING</b>      |             |   |      |        |            |      |      |     |         |                 |              |      |
| 18/25/30                                       | 55610       | 48" DESIGNER STRIP - 18/25/30W/35-50K/DIMM - SL®                | ★    | 35-50K | 2340-3900  | 130  | 130° | 82  | 120-277 | 50,000          | 100W         | 6    |
|  | 55610-8WEM  | 48" DESIGNER STRIP - 18/25/30W/35-50K/DIMM/8W EM BATTERY - SL®  | P    | 35-50K | 2340-3900  | 130  | 130° | 82  | 120-277 | 50,000          | 100W         | 6    |
| 34/38/45                                       | 55611       | 48" DESIGNER STRIP - 34/38/45W/35-50K/DIMM - SL®                | ★    | 35-50K | 4454-5895  | 131  | 130° | 82  | 120-277 | 50,000          | 150W         | 6    |
|  | 55611-8WEM  | 48" DESIGNER STRIP - 34/38/45W/35-50K/DIMM/8W EM BATTERY - SL®  | P    | 35-50K | 4454-5895  | 131  | 130° | 82  | 120-277 | 50,000          | 150W         | 6    |
| <b>8FT DESIGNER STRIP - 0-10V DIMMING</b>      |             |   |      |        |            |      |      |     |         |                 |              |      |
| 38/46/54                                       | 55612       | 96" DESIGNER STRIP - 38/46/54W/35-50K/DIMM - SL®                | ★    | 35-50K | 4940-7020  | 130  | 130° | 82  | 120-277 | 50,000          | 150W         | 4    |
|  | 55612-8WEM  | 96" DESIGNER STRIP - 38/46/54W/35-50K/DIMM/8W EM BATTERY - SL®  | P    | 35-50K | 4940-7020  | 130  | 130° | 82  | 120-277 | 50,000          | 150W         | 4    |
| 65/75/90                                       | 55613       | 96" DESIGNER STRIP - 65/75/90W/35-50K/DIMM - SL®                | ★    | 35-50K | 8450-11790 | 131  | 130° | 82  | 120-277 | 50,000          | 200W         | 4    |
|  | 55613-16WEM | 96" DESIGNER STRIP - 65/75/90W/35-50K/DIMM/16W EM BATTERY - SL® | P    | 35-50K | 8450-11790 | 131  | 130° | 82  | 120-277 | 50,000          | 200W         | 4    |
| <b>DESIGNER STRIP RETROFIT - 0-10V DIMMING</b> |             |   |      |        |            |      |      |     |         |                 |              |      |
| 22/30/40                                       | 55594       | 48" DESIGNER STRIP RETROFIT - 22/30/40W/35-50K/DIMM - SL®       | ★    | 35-50K | 2992-5200  | 130  | 130° | 82  | 120-277 | 50,000          | 150W         | 2    |
| 45/60/75                                       | 55597       | 96" DESIGNER STRIP RETROFIT - 45/60/75W/35-50K/DIMM - SL®       | ★    | 35-50K | 6120-9900  | 130  | 130° | 82  | 120-277 | 50,000          | 200W         | 1    |
| <b>4FT WRAP-A-ROUND - 0-10V DIMMING</b>        |             |   |      |        |            |      |      |     |         |                 |              |      |
| 30/35/40                                       | 55617       | 48" WRAP-A-ROUND - 30/35/40W/35-50K/DIMM - SL®                  | ★    | 35-50K | 3990-5320  | 133  | 100° | 82  | 120-277 | 50,000          | 150W         | 4    |
|  | 55617-8WEM  | 48" WRAP-A-ROUND - 30/35/40W/35-50K/DIMM/8W EM BATTERY - SL®    | P    | 35-50K | 3990-5320  | 133  | 100° | 82  | 120-277 | 50,000          | 150W         | 4    |

Accessories on the next page...

Key: DIMM = Dimmable / SL = Superior Life® / P = Pending / LM = Lumens / TRAD. EQUIV. = Traditional Equivalent

Note: Not all product variations listed on this page are DLC® qualified. Visit [www.designlights.org/search](http://www.designlights.org/search) to confirm qualification. • CEC Status identifies items listed on the MAEDBS database that are in compliance with Title 20 or Title 24 Regulations. Visit [www.cacertappliances.energy.ca.gov](http://www.cacertappliances.energy.ca.gov) to confirm compliance. • Published lumens on LED products are approximate and may vary slightly. • Specifications are subject to change without notice. • Photos and drawings may not be to scale and are for general reference only.



PREMIUM QUALITY LIGHTING® • Phone: 800-323-8107  
© P.Q.L., Inc. • 2285 Ward Avenue • Simi Valley, CA 93065

www.PQLighting.com  
Rev: 11/20/2020



## ACCESSORIES

| WATTS | ITEM# | DESCRIPTION  | CEC STATUS | CASE |
|-------|-------|--|------------|------|
|       | 54896 | 360° LOW/HIGH BAY FIXTURE OCCUPANCY PIR SENSOR 30' DIA, 8-40'HEIGHT 800W/1200W - 120/277V - SL®                |            | 50   |
|       | 54897 | 360° LOW BAY BI-LEVEL AND DAYLIGHT HARVEST MICROWAVE SENSOR 48' DIA, 8-20' HEIGHT 800W/1200W - 120/277V - SL®  |            | 50   |
|       | 54898 | 360° HIGH BAY BI-LEVEL AND DAYLIGHT HARVEST MICROWAVE SENSOR 60' DIA, 8-50' HEIGHT 800W/1200W - 120/277V - SL® |            | 50   |
|       | 54894 | EXTENDER MOUNT FOR SENSOR 54896/54897/54898 - SUPERIOR LIFE®   |            | 100  |
|       | 55456 | ROW ALIGNER FOR DESIGNER STRIP/V2 - SUPERIOR LIFE®   |            | 100  |
| 8     | 55390 | EMERGENCY PACK FOR LED FIXTURE 8W/90 MIN - SPLIT TYPE/L - SL® (For use with drivers that are 100W or less.)    | T20        | 10   |
| 16    | 55391 | EMERGENCY PACK FOR LED FIXTURE 16W/90 MIN - SPLIT TYPE/L - SL® (For use with drivers that are 100W or less.)   | T20        | 10   |
| 25    | 55392 | EMERGENCY PACK FOR LED FIXTURE 25W/90 MIN - SPLIT TYPE/L - SL® (For use with drivers that are 100W or less.)   | T20        | 1    |



54896



54897



54898



54894

IMAGE  
COMING SOON

55456



55390 / 55391  
55392

Key: DIMM = Dimmable / SL = Superior Life® / P = Pending / LM = Lumens / TRAD. EQUIV. = Traditional Equivalent

Note: Not all product variations listed on this page are DLC® qualified. Visit [www.designlights.org/search](http://www.designlights.org/search) to confirm qualification. • CEC Status identifies items listed on the MAEDBS database that are in compliance with Title 20 or Title 24 Regulations. Visit [www.cacertappliances.energy.ca.gov](http://www.cacertappliances.energy.ca.gov) to confirm compliance. • Published lumens on LED products are approximate and may vary slightly. • Specifications are subject to change without notice. • Photos and drawings may not be to scale and are for general reference only.



PREMIUM QUALITY LIGHTING® • Phone: 800-323-8107

© P.Q.L., Inc. • 2285 Ward Avenue • Simi Valley, CA 93065

[www.PQLighting.com](http://www.PQLighting.com)

Rev: 11/20/2020