



LED TROFFER FIXTURES

INDOOR • INTERIOR LIGHTING • INTEGRATED LED

The Superior Life® LED Troffer Fixtures are high quality with integrated LEDs for excellent efficiency and optimal performance. They consume less energy than traditional lighting, significantly reducing operating costs and are environmentally friendly.

FEATURES

- High Efficiency, Energy Saving
- Sturdy construction - Die form cold-rolled steel housing.
- Compatible with traditional ceiling grids
- Lightweight and easy installation
- Mercury Free - Environmentally friendly.
- Low heat reduces AC costs
- Dimmable (0-10V, Range 10% - 100%)

APPLICATION

COMMERCIAL & INDUSTRIAL



- | | |
|---------------|-------------|
| Offices | Schools |
| Retail Stores | Warehouses |
| Banking | Work Spaces |

WARRANTY*



QUALIFICATIONS*



*Warranty and Qualifications can vary per item, see technical data sheets (TDS) for specific information.



PREMIUM QUALITY LIGHTING® • Phone: 800-323-8107
© P.Q.L., Inc. • 2285 Ward Avenue • Simi Valley, CA 93065

www.PQLighting.com
Rev: 06/15/2020



TROFFERS - 120-277V

WATTS	ITEM#	DESCRIPTION	DLC*	CCT	LUMENS	LM/W	BEAM	CRI	VOLTS	AVG. LIFE HOURS	TRAD. EQUIV.	CASE
0-10V DIMMING												
34	55270	2X2 TROFFER - 34W/40K/120-277V/DIMMABLE - SL*	★	4000K	3400	100	100°	80	120-277	50,000	150W	1
42	55272	2X4 TROFFER - 42W/40K/120-277V/DIMMABLE - SL*	★	4000K	4536	108	100°	80	120-277	50,000	150W	1

CENTER BASKET FIXTURES - 120-277V

WATTS	ITEM#	DESCRIPTION	DLC*	CCT	LUMENS	LM/W	BEAM	CRI	VOLTS	AVG. LIFE HOURS	TRAD. EQUIV.	CASE
0-10V DIMMING												
30	55075	2X2 CENTER BASKET - 30W/40K/120-277V/DIMMABLE/V2 - SL*	★	4000K	3810	127	120°	80	120-277	50,000	150W	1
34	55079	2X4 CENTER BASKET - 34W/40K/120-277V/DIMMABLE - SL*	★	4000K	4318	127	120°	82	120-277	50,000	150W	1
	55267	2X4 CENTER BASKET - 34W/50K/120-277V/DIMMABLE - SL*	★	5000K	4318	127	120°	80	120-277	50,000	150W	1
	55080	2X4 CENTER BASKET - 34W/50K/120-277V/DIMMABLE - SL*	★	5000K	4352	128	120°	82	120-277	50,000	150W	1

CENTER BASKET TROFFER RETROFIT - 120-277V

WATTS	ITEM#	DESCRIPTION	DLC*	CCT	LUMENS	LM/W	BEAM	CRI	VOLTS	AVG. LIFE HOURS	TRAD. EQUIV.	CASE
0-10V DIMMING												
34	55171	2X2 CB TROFFER RETROFIT - 34W/40K/120-277V/DIMM - SL*	★	4000K	4216	125	100°	80	120-277	50,000	150W	1
42	55084	2X4 CB TROFFER RETROFIT - 42W/40K/120-277V/DIMM - SL*	★	4000K	5292	126	100°	82	120-277	50,000	175W	1

SPEC-SELECT™ FIXTURES - 120-277V (Selectable Wattage & CCT - Warm White / Cool White / Sky-Brite®)

WATTS	ITEM#	DESCRIPTION	DLC*	CCT	LUMENS	LM/W	BEAM	CRI	VOLTS	AVG. LIFE HOURS	TRAD. EQUIV.	CASE
CENTER BASKET TROFFER - 0-10V DIMMING												
30/35/40	55600	2X2 CB TROFFER - 30/35/40W/35-50K/DIMM - SL*	★	35-50K	3750-5000	125	100°	82	120-277	50,000	150W	1
	55600-8WEM	2X2 CB TROFFER - 30/35/40W/35-50K/DIMM/8W EM BATTERY - SL*	P	35-50K	3750-5000	125	100°	82	120-277	50,000	150W	1
34/38/45	55602	2X4 CB TROFFER - 34/38/45W/35-50K/120-277V/DIMM - SL*	★	35-50K	4318-5715	127	100°	82	120-277	50,000	175W	1
	55602-8WEM	2X4 CB TROFFER - 34/38/45W/35-50K/DIMM/8W EM BATTERY - SL*	P	35-50K	4318-5715	127	100°	82	120-277	50,000	175W	1

CENTER BASKET TROFFER RETROFIT - 0-10V DIMMING

30/35/40	55620	2X2 CB TROFFER RETROFIT - 30/35/40W/35-50K/DIMM - SL*	★	35-50K	3780-5040	126	100°	82	120-277	50,000	150W	1
34/38/45	55622	2X4 CB TROFFER RETROFIT - 34/38/45W/35-50K/DIMM - SL*	★	35-50K	4386-5805	129	100°	82	120-277	50,000	175W	1

ACCESSORIES

WATTS	ITEM#	DESCRIPTION	CEC STATUS	CASE
8	55319	EMERGENCY PACK FOR LED FIXTURE 8W/90 MIN - INTEGRATION TYPE - SL* (For use with drivers that are 100W or less.)	T20	1
16	55320	EMERGENCY PACK FOR LED FIXTURE 16W/90 MIN - INTEGRATION TYPE - SL* (For use with drivers that are 100W or less.)	T20	1
25	55321	EMERGENCY PACK FOR LED FIXTURE 25W/90 MIN - INTEGRATION TYPE - SL* (For use with drivers that are 100W or less.)	T20	1



55319 / 55320
55321

Key: DIMM = Dimmable / SL = Superior Life® / P = Pending / LM = Lumens / TRAD. EQUIV. = Traditional Equivalent

Note: Not all product variations listed on this page are DLC* qualified. Visit www.designlights.org/search to confirm qualification. • CEC Status identifies items listed on the MAEDBS database that are in compliance with Title 20 or Title 24 Regulations. Visit www.cacertappliances.energy.ca.gov to confirm compliance. • Published lumens on LED products are approximate and may vary slightly. • Specifications are subject to change without notice. • Photos and drawings may not be to scale and are for general reference only.



PREMIUM QUALITY LIGHTING® • Phone: 800-323-8107
© P.Q.L., Inc. • 2285 Ward Avenue • Simi Valley, CA 93065

www.PQLighting.com
Rev: 06/15/2020