



LED LINEAR HYBRID

BI PIN • DUAL MODE INTERNAL DRIVER • UL TYPE A & B

The Superior Life® LED T8 Hybrid tubes provide exceptional LED lighting with reduced energy and maintenance costs. The Hybrid tube works as a ballast bypass lamp, making it a universal replacement for standard fluorescent lamps. The superior life hours of this lamp make it ideal for hard to reach places, reducing maintenance and reduces the type of lamps you need to stock.

FEATURES

- High Efficiency, Energy Saving.
- Premium Construction - Longer lamp life and durability.
- High Performance LEDs - Bright and high lumens per watt light output.
- Mercury Free - Environmentally friendly.
- Little to no UV or Projected Heat - Reduces fading and AC costs.
- Vibration and Shock Resistant with Safety Coating.
- Works with or without a ballast.*
- Compatible with Shunted and Non-Shunted Sockets.*

* See install instructions for specific wiring and further details.

APPLICATIONS

COMMERCIAL & INDUSTRIAL



Offices

Schools

Retail Stores

Warehouses

Banking

Work Spaces

WARRANTY



QUALIFICATIONS



Qualifications vary, see technical data for specific information.



LED HYBRID TUBES



T8 TUBES

| WATTS | ITEM# | DESCRIPTION | DLC* | CEE | UL/ETL | CCT | LUMENS | LM/W | BEAM | CRI | MOL | VOLTS | BASE | LIFE | CASE |
|-----------------------------------|-------|---------------------------------------|------|-----|--------|-------|--------|------|------|-----|-----|---------|---|------|------|
| 4' - FROST | | | | | | | | | | | | | LED TUBE - 4FT LED TUBE HYBRID | | |
| 14 | 91466 | 14WT8/35K/FR/HYBRID - SL® | ★ | | UL | 3500K | 1800 | 125 | -- | 82 | 48" | 120-277 | MED BI PIN | 50K | 25 |
| | 91467 | 14WT8/40K/FR/HYBRID - SL® | ★ | | UL | 4000K | 1800 | 125 | -- | 82 | 48" | 120-277 | MED BI PIN | 50K | 25 |
| | 91468 | 14WT8/50K/FR/HYBRID - SL® | ★ | | UL | 5000K | 1800 | 125 | -- | 82 | 48" | 120-277 | MED BI PIN | 50K | 25 |
| 4' - FROST - SAFETY COATED | | | | | | | | | | | | | LED TUBE - SAFETY COATED - 4FT LED TUBE HYBRID | | |
| 14 | 90417 | 14WT8/35K/FR/SUPER HYBRID/SC/V5 - SL® | ★ | ☑ | UL | 3500K | 2000 | 114 | 160° | 83 | 48" | 120-277 | MED BI PIN | 50K | 25 |
| | 90418 | 14WT8/40K/FR/SUPER HYBRID/SC/V5 - SL® | ★ | ☑ | UL | 4000K | 2100 | 120 | 160° | 83 | 48" | 120-277 | MED BI PIN | 50K | 25 |
| | 90419 | 14WT8/50K/FR/SUPER HYBRID/SC/V5 - SL® | ★ | ☑ | UL | 5000K | 2200 | 126 | 160° | 83 | 48" | 120-277 | MED BI PIN | 50K | 25 |

Key: FR = Frosted / SC = Safety Coated / SL = Superior Life® / LM = Lumens

Note: Not all product variations listed on this page are DLC qualified. Visit www.designlights.org/search to confirm qualification. • Published lumens on LED products are approximate and may vary slightly. • Specifications are subject to change without notice. • Photos and drawings may not be to scale and are for general reference only.

