



LED LINEAR HYBRID

BI PIN • DUAL MODE INTERNAL DRIVER • UL TYPE A & B

The Superior Life® LED T8 Hybrid tubes provide exceptional LED lighting with reduced energy and maintenance costs. The Hybrid tube works as a ballast bypass lamp, making it a universal replacement for standard fluorescent lamps. The superior life hours of this lamp make it ideal for hard to reach places, reducing maintenance and reduces the type of lamps you need to stock.

FEATURES

- High Efficiency, Energy Saving
- Premium Construction - Longer lamp life and durability.
- High Performance LEDs - Bright and high lumens per watt light output.
- Mercury Free - Environmentally friendly.
- Little to no UV or Projected Heat - Reduces fading and AC costs.
- Vibration and Shock Resistant with Safety Coating
- Works with or without a ballast*
- Compatible with Shunted and Non-Shunted Sockets*

* See install instructions for specific wiring and further details.

APPLICATION

COMMERCIAL & INDUSTRIAL



Offices	Warehouses
Schools	Banking
Retail Stores	Work Spaces

WARRANTY



QUALIFICATIONS*



*Qualifications can vary per item, see technical data sheets (TDS) for specific information.



PREMIUM QUALITY LIGHTING® • Phone: 800-323-8107
© P.Q.L., Inc. • 2285 Ward Avenue • Simi Valley, CA 93065

www.PQLighting.com
Rev: 02/03/2021



T8 TUBES

WATTS	ITEM#	DESCRIPTION	DLC®	CEE	UL/ETL	CCT	LUMENS	LM/W	BEAM	CRI	MOL	VOLTS	BASE	AVG. LIFE HOURS	CASE
4' - FROST															
14	91466	14WT8/35K/FR/HYBRID - SL®	★		UL	3500K	1800	125	--	82	48"	120-277	MED BI PIN	50,000	25
	91467	14WT8/40K/FR/HYBRID - SL®	★		UL	4000K	1800	125	--	82	48"	120-277	MED BI PIN	50,000	25
	91468	14WT8/50K/FR/HYBRID - SL®	★		UL	5000K	1800	125	--	82	48"	120-277	MED BI PIN	50,000	25
4' - FROST - SAFETY COATED															
14	90417	14WT8/35K/FR/SUPER HYBRID/SC/V5 - SL®	★	☑	UL	3500K	2150	123	160°	83	48"	120-277	MED BI PIN	50,000	25
	90418	14WT8/40K/FR/SUPER HYBRID/SC/V5 - SL®	★	☑	UL	4000K	2100	126	160°	83	48"	120-277	MED BI PIN	50,000	25
	90419	14WT8/50K/FR/SUPER HYBRID/SC/V5 - SL®	★	☑	UL	5000K	2200	126	160°	83	48"	120-277	MED BI PIN	50,000	25
2'/U1 5/8" - FROST															
15	90884	15WT8/U1 5/8"/50K/FR/SUPER HYBRID - SL®	P		UL	5000K	2200	147	140°	83	22.4"	120-277	MED BI PIN	50,000	24
2'/U6 - FROST															
13	90439	13WT8/U6/35K/FR/ SUPER HYBRID - SL®	★		UL	3500K	1950	122	160°	83	22.4"	120-277	MED BI PIN	50,000	12
	90440	13WT8/U6/40K/FR/ SUPER HYBRID - SL®	★		UL	4000K	1900	125	160°	83	22.4"	120-277	MED BI PIN	50,000	12
	90441	13WT8/U6/50K/FR/ SUPER HYBRID - SL®	★		UL	5000K	2000	125	160°	83	22.4"	120-277	MED BI PIN	50,000	12

Key: FR = Frosted / SC = Safety Coated / SL = Superior Life® / LM = Lumens

Note: Not all product variations listed on this page are DLC qualified. Visit www.designlights.org/search to confirm qualification. • Published lumens on LED products are approximate and may vary slightly. • Specifications are subject to change without notice. • Photos and drawings may not be to scale and are for general reference only.



PREMIUM QUALITY LIGHTING® • Phone: 800-323-8107
© P.Q.L., Inc. • 2285 Ward Avenue • Simi Valley, CA 93065

www.PQLighting.com
Rev: 02/03/2021

