



EACH MODULE INCLUDES



Power Cord Connector



2 ea. Mounting Brackets



Linking Butt Connector

LED SNAP & GO™ MINI MODULES

LINEAR RETROFIT KITS • QUICK CONNECT

The Superior Life® LED Snap & Go™ Module Kits are simple and quick LED retrofits for traditional fluorescent fixtures and recessed troffers in drop-in ceilings. The kit can be easily installed with minimum modification to the existing housing, avoiding the removal of existing fixtures.

FEATURES

- **Fast and easy installation** - Installs in minutes.
- **Minimal modification to existing housing**
- **Internal Driver** - Quick connection.
- **Linkable** - Max. linked wattage of 150W combined.
- **Bright and consistent light.**
- **Energy efficient.**
- **Mercury Free** - Environmentally friendly.

APPLICATION

COMMERCIAL & INDUSTRIAL



Warehouses

Workshops

Schools

Large Areas

Retail

Work Spaces

WARRANTY*



QUALIFICATIONS*



*Warranty and Qualifications can vary per item, see technical data sheets (TDS) for specific information.



PREMIUM QUALITY LIGHTING® • Phone: 800-323-8107

© P.Q.L., Inc. • 2285 Ward Avenue • Simi Valley, CA 93065

www.PQLighting.com

Rev: 02/28/2020

LED MINI MODULES

LED MODULE

WATTS	ITEM#	DESCRIPTION	DLC*	CCT	LUMENS	LM/W	BEAM	CRI	MOL	VOLTS	FINISH	AVG. LIFE HOURS	TRAD. EQUIV.	CASE
2' - NON-DIMMABLE														
9	87005	MINI SNAP & GO™ MODULE 2'/10W/40K/FR - SL®	P	4000K	1269	137	120°	80	21.5"	120	WHITE	50,000	75W	36
	87006	MINI SNAP & GO™ MODULE 2'/10W/50K/FR - SL®	P	5000K	1289	138	120°	80	21.5"	120	WHITE	50,000	75W	36
3' - NON-DIMMABLE														
11	87010	MINI SNAP & GO™ MODULE 3'/12W/40K/FR - SL®	P	4000K	1513	139	120°	80	33.3"	120	WHITE	50,000	75W	36
	87011	MINI SNAP & GO™ MODULE 3'/12W/50K/FR - SL®	P	5000K	1538	141	120°	80	33.3"	120	WHITE	50,000	75W	36
4' - NON-DIMMABLE														
11	87015	MINI SNAP & GO™ MODULE 4'/12W/40K/FR - SL®	P	4000K	1511	135	120°	80	45.6"	120	WHITE	50,000	75W	36
	87016	MINI SNAP & GO™ MODULE 4'/12W/50K/FR - SL®	P	5000K	1535	137	120°	80	45.6"	120	WHITE	50,000	75W	36
14	87020	MINI SNAP & GO™ MODULE 4'/15W/40K/FR - SL®	P	4000K	1824	129	120°	80	45.6"	120	WHITE	50,000	100W	36
	87021	MINI SNAP & GO™ MODULE 4'/15W/50K/FR - SL®	P	5000K	1853	131	120°	80	45.6"	120	WHITE	50,000	100W	36
18	87025	MINI SNAP & GO™ MODULE 4'/18W/40K/FR - SL®	P	4000K	2321	129	120°	80	45.6"	120	WHITE	50,000	100W	36
	87026	MINI SNAP & GO™ MODULE 4'/18W/50K/FR - SL®	P	5000K	2359	131	120°	80	45.6"	120	WHITE	50,000	100W	36

ACCESSORIES

ITEM#	DESCRIPTION	CASE
87036	MINI SNAP & GO™ SET OF (2) MAGNETIC BRACKETS - SUPERIOR LIFE®	1
87038	MINI SNAP & GO™ FLEXIBLE LINKING CORD CONNECTOR - SUPERIOR LIFE®	1
87030	MINI SNAP & GO™ POWER CONNECTOR FOR 2 FIXTURES - SUPERIOR LIFE®	1
87031	MINI SNAP & GO™ POWER CONNECTOR FOR 3 FIXTURES - SUPERIOR LIFE®	1
87032	MINI SNAP & GO™ POWER CONNECTOR FOR 4 FIXTURES - SUPERIOR LIFE®	1

Maximum linked wattage of 150W combined.

Maximum total power per input cord should not exceed 250W.



87036

87038

87030

87031

87032

Key: SL = Superior Life® / P = Pending / LM = Lumens / TRAD. EQUIV. = Traditional Equivalent

NOTE: Not all product variations listed on this page are DLC® qualified. Visit www.designlights.org/search to confirm qualification. • Published lumens on LED products are approximate and may vary slightly. • Specifications are subject to change without notice. • Photos and drawings may not be to scale and are for general reference only.