



LED INTERIOR LIGHTING

MINI MODULES

The Superior Life® LED Snap & Go™ Module Kits are simple and quick LED retrofits for traditional fluorescent fixtures and recessed troffers in drop-in ceilings. The kit can be easily installed with minimum modification to the existing housing, avoiding the removal of existing fixtures.

Application: Ideal for retrofitting existing fluorescent fixtures and recessed troffers in warehouses, schools, retail stores, workshops, large areas, and work spaces.

LED INTERIOR LIGHTING SNAP & GO™ MINI MODULES



FEATURES

- **Fast and easy installation** - Installs in minutes.
- **Minimal modification to existing housing**
- **Internal Driver** - Quick connection.
- **Linkable** - Max. linked wattage of 150W combined.
- **Bright and consistent light**
- **Energy efficient**
- **Mercury Free** - Environmentally friendly.



EACH MODULE KIT INCLUDES



1 ea. Module



13" Power Cord
Connector



2 ea. Mounting
Brackets



Linking
End-to-End
Connector



End Cap

Note: Warranty and Qualifications can vary per item, see technical data sheets (TDS) for specific information. • Not all product variations listed are DLC® qualified. Visit www.designlights.org/search to confirm qualification. • Published lumens on LED products are approximate and may vary slightly. • Specifications are subject to change without notice. • Photos and drawings may not be to scale and are for general reference only.



PREMIUM QUALITY LIGHTING® • Phone: 800-323-8107
© P.Q.L., Inc. • 2285 Ward Avenue • Simi Valley, CA 93065

www.PQLighting.com
Rev: 08/25/2022

LED INTERIOR LIGHTING SNAP & GO™ MINI MODULES



LED MINI MODULES

WATTS	ITEM#	DESCRIPTION	DLC*	CCT	LUMENS	LPW	BEAM	CRI	MOL	VOLTS	FINISH	LIFE HOURS	TRAD. EQUIV.	CASE
2' - NON-DIMMABLE														
9	87005	2FT MINI SNAP & GO™ MODULE/10W/40K/FR/120V	5.0	4000K	1269	137	120°	80	21.5"	120	WHITE	50,000	75W	36
	87006	2FT MINI SNAP & GO™ MODULE/10W/50K/FR/120V	5.0	5000K	1289	138	120°	80	21.5"	120	WHITE	50,000	75W	36
3' - NON-DIMMABLE														
11	87010	3FT MINI SNAP & GO™ MODULE/12W/40K/FR/120V	5.0	4000K	1513	139	120°	80	33.3"	120	WHITE	50,000	75W	36
	87011	3FT MINI SNAP & GO™ MODULE/12W/50K/FR/120V	5.0	5000K	1538	141	120°	80	33.3"	120	WHITE	50,000	75W	36
4' - NON-DIMMABLE														
11	87015	4FT MINI SNAP & GO™ MODULE/12W/40K/FR/120V	5.0	4000K	1511	135	120°	80	45.6"	120	WHITE	50,000	75W	36
	87016	4FT MINI SNAP & GO™ MODULE/12W/50K/FR/120V	5.0	5000K	1535	137	120°	80	45.6"	120	WHITE	50,000	75W	36
14	87020	4FT MINI SNAP & GO™ MODULE/15W/40K/FR/120V	5.0	4000K	1824	129	120°	80	45.6"	120	WHITE	50,000	100W	36
	87021	4FT MINI SNAP & GO™ MODULE/15W/50K/FR/120V	5.0	5000K	1853	131	120°	80	45.6"	120	WHITE	50,000	100W	36
18	87025	4FT MINI SNAP & GO™ MODULE/18W/40K/FR/120V	5.0	4000K	2321	129	120°	80	45.6"	120	WHITE	50,000	100W	36
	87026	4FT MINI SNAP & GO™ MODULE/18W/50K/FR/120V	5.0	5000K	2359	131	120°	80	45.6"	120	WHITE	50,000	100W	36

ACCESSORIES

ITEM#	DESCRIPTION	CASE
87036	MINI SNAP & GO™ SET OF (2) MAGNETIC BRACKETS	1
87038	MINI SNAP & GO™ 6" FLEXIBLE LINKING CORD CONNECTOR	1
87030	MINI SNAP & GO™ 33" POWER CONNECTOR FOR 2 FIXTURES	1
87031	MINI SNAP & GO™ 33" POWER CONNECTOR FOR 3 FIXTURES	1
87032	MINI SNAP & GO™ 33" POWER CONNECTOR FOR 4 FIXTURES	1

Maximum linked wattage of 150W combined.

Maximum total power per input cord should not exceed 250W.



87036



87038



87030



87031



87032

Key: FR = Frosted Lens / P = Pending / LPW = Lumens Per Watt / TRAD. EQUIV. = Traditional Equivalent

Note: Warranty and Qualifications can vary per item, see technical data sheets (TDS) for specific information. - Not all product variations listed are DLC* qualified. Visit www.designlights.org/search to confirm qualification. - Published lumens on LED products are approximate and may vary slightly. - Specifications are subject to change without notice. - Photos and drawings may not be to scale and are for general reference only.



PREMIUM QUALITY LIGHTING® - Phone: 800-323-8107
© P.Q.L., Inc. • 2285 Ward Avenue • Simi Valley, CA 93065

www.PQLighting.com

Rev: 08/25/2022