



LED INTERIOR LIGHTING


PREMIUM PANELS

Premium Panels are our most efficient, highest lumen-per-watt line of panel LEDs. Their slim design is up to 23% more efficient than standard LED panels. They provide bright, uniform light with long life (50,000hrs), quickly paying for themselves by significantly reducing energy usage and maintenance costs over the life of the panel compared to traditional fluorescent lighting. Premium design allows makes them easy to install.

Application: Ideal for commercial and industrial applications; offices, conference rooms, hospitals, lobbies, hotels, classrooms, workshops, cafeterias and other common areas.

FEATURES

- High Efficiency, Energy Saving
- Premium Construction
- High Performance LEDs - Highest lumens per watt light output.
- Low glare, bright consistent lighting
- Simple Installation - Ideal for t-grid and drywall ceilings.
- Low heat reduces AC costs
- Dimmable (1-10V, Range 10% - 100%)



1X4



2X2



2X4

Note: Warranty and Qualifications can vary per item, see technical data sheets (TDS) for specific information. • Not all product variations listed are DLC® qualified. Visit www.designlights.org/search to confirm qualification. • Published lumens on LED products are approximate and may vary slightly. • Specifications are subject to change without notice. • Photos and drawings may not be to scale and are for general reference only.



LED INTERIOR LIGHTING PREMIUM PANELS



SPEC-SELECT™ BACK-LIT PANELS/BLP - 120-277V (Selectable Wattage & CCT - 3500K / 4000K / 5000K)

WATTS	ITEM#	DESCRIPTION	DLC®	UL/ETL	CCT	LUMENS	LPW	BEAM	CRI	VOLTS	LIFE HOURS	TRAD. EQUIV.	CASE
1X4 - INTEGRATED SENSOR OPTION													
20/25/30	55750	1X4 PANEL/20-25-30W/35-50K/DIMM/ISO/120-277V	★	UL	35-50K	2500-3750	125	120°	83	120-277	50,000	50W	2
	55750-8WEM	1X4 PANEL/20-25-30W/35-50K/DIMM/ISO/120-277V/8W EMB	P	P	35-50K	2500-3750	125	120°	83	120-277	50,000	50W	2
2X2 - INTEGRATED SENSOR OPTION													
20/25/30	55751	2X2 PANEL/20-25-30W/35-50K/DIMM/ISO/120-277V	★	UL	35-50K	2500-3750	125	120°	83	120-277	50,000	50W	2
	55751-8WEM	2X2 PANEL/20-25-30W/35-50K/DIMM/ISO/120-277V/8W EMB	P	P	35-50K	2500-3750	125	120°	83	120-277	50,000	50W	2
2X4 - INTEGRATED SENSOR OPTION													
30/35/40	55752	2X4 PANEL/30-35-40W/35-50K/DIMM/ISO/120-277V	★	UL	35-50K	3780-5040	126	120°	83	120-277	50,000	150W	2
30/40/50	55753	2X4 PANEL/30-40-50W/35-50K/DIMM/ISO/120-277V	★	UL	35-50K	3780-6300	126	120°	83	120-277	50,000	200W	2
	55753-8WEM	2X4 PANEL/30-40-50W/35-50K/DIMM/ISO/120-277V/8W EMB	P	P	35-50K	3780-6300	126	120°	83	120-277	50,000	200W	2

PREMIUM BACK-LIT PANELS

WATTS	ITEM#	DESCRIPTION	DLC®	UL/ETL	CCT	LUMENS	LPW	BEAM	CRI	VOLTS	LIFE HOURS	TRAD. EQUIV.	CASE
2X2 - 0-10V DIMMING													
28	55669	2X2 PANEL/BLP/28W/35K/DIMM/120-277V	★	UL	3500K	3584	128	120°	84	120-277	50,000	50W	2
	55670	2X2 PANEL/BLP/28W/40K/DIMM/120-277V	★	UL	4000K	3612	129	120°	84	120-277	50,000	50W	2
36	55562	2X2 PANEL/BLP/36W/35K/DIMM/120-277V	5.0	UL	3500K	4500	125	120°	82	120-277	50,000	100W	4
2X4 - 0-10V DIMMING													
40	55565	2X4 PANEL/40W/35K/DIMM/120-277V	5.0	UL	3500K	5000	125	120°	82	120-277	50,000	150W	4
	55676	2X4 PANEL/BLP/40W/50K/DIMM/120-277V	★	UL	5000K	4760	119	120°	82	120-277	50,000	150W	4

PREMIUM EDGE-LIT PANELS

WATTS	ITEM#	DESCRIPTION	DLC®	UL/ETL	CCT	LUMENS	LPW	BEAM	CRI	VOLTS	LIFE HOURS	TRAD. EQUIV.	CASE
2X4 - 0-10V DIMMING													
40	55416	2X4 PANEL/40W/35K/DIMM/120-277V	5.0	UL/ETL	3500K	5000	125	120°	83	120-277	50,000	150W	2

Accessories on the next page...

Key: P = Pending / LPW = Lumens Per Watt / TRAD. EQUIV. = Traditional Equivalent

Note: Warranty and Qualifications can vary per item, see technical data sheets (TDS) for specific information. - Not all product variations listed are DLC® qualified. Visit www.designlights.org/search to confirm qualification. - Published lumens on LED products are approximate and may vary slightly. - Specifications are subject to change without notice. - Photos and drawings may not be to scale and are for general reference only.



PREMIUM QUALITY LIGHTING® - Phone: 800-323-8107
© P.Q.L., Inc. • 2285 Ward Avenue • Simi Valley, CA 93065

www.PQLighting.com
Rev: 01/21/2025

LED INTERIOR LIGHTING PREMIUM PANEL ACCESSORIES



ACCESSORIES

Check fixture TDS to confirm compatibility of accessories.

	ITEM#	DESCRIPTION	CASE
MOUNTING KITS			
1X4	55127	1X4 FLANGE KIT FOR PANEL & TROFFER/WHT	1
	55440	1X4 SURFACE MOUNT KIT FOR LED PANEL/WHT	25
	55530	1X4 SURFACE MOUNTED KIT FOR LED BACK-LIT PANEL/WHT	1
2X2	55128	2X2 FLANGE KIT FOR PANEL & TROFFER/WHT	1
	55441	2X2 SURFACE MOUNT KIT FOR LED PANEL/WHT	50
	55531	2X2 SURFACE MOUNTED KIT FOR LED BACK-LIT PANEL/WHT	1
2X4	55129	2X4 FLANGE KIT FOR PANEL & TROFFER/WHT	1
	55442	2X4 SURFACE MOUNT KIT FOR LED PANEL/WHT	25
	55532	2X4 SURFACE MOUNTED KIT FOR LED BACK-LIT PANEL/WHT	1
	55445	5FT SUSPENDED CABLE MOUNTING KIT FOR LED PANEL	100
	55446	10FT SUSPENDED CABLE MOUNTING KIT FOR LED PANEL	100
SENSORS FOR ISO FIXTURES			
	54880	BI-LEVEL AND DAYLIGHT PIR SENSOR FOR LED PANEL/UP TO 12FT HEIGHT - 12-24V DC	100
EMERGENCY PACKS			
8	55706	EEMERGENCY PACK FOR LED BLP PANEL 8W/90 MIN	10
25	55450	EMERGENCY PACK FOR LED PANEL 25W/90 MIN - T20C	6



Key: P = Pending / LM = Lumens / TRAD. EQUIV. = Traditional Equivalent

Note: Not all product variations listed on this page are DLC® qualified. Visit www.designlights.org/search to confirm qualification. • CEC Status identifies items listed on the MAEDBS database that are in compliance with Title 20 or Title 24 Regulations. Visit www.cacertappliances.energy.ca.gov to confirm compliance. • Published lumens on LED products are approximate and may vary slightly. • Specifications are subject to change without notice. • Photos and drawings may not be to scale and are for general reference only.

