



LED INTERIOR LIGHTING

RETROFIT CANS & DISKS

LED Retrofit Cans are convenient and easy-to-install replacements for less efficient incandescent and compact fluorescent (CFL) light sources. They consume up to 80% less energy, thereby significantly reducing operating costs. The superior life hours of these retrofits make them ideal for hard to reach places, reducing maintenance.

Application: Ideal for commercial and industrial applications; offices, conference rooms, hospitals, lobbies, hotels, classrooms, workshops, cafeterias and other common areas.

FEATURES

- Energy efficient
- Superior lighting performance
- Long life design
- Lightweight and easy installation
- Mercury Free - Environmentally friendly.
- Low heat reduces AC costs
- For covered ceilings only



90901 (4")



90902 (6")



90897 (4")



90898 (6")



93090 (4")



93091 (6")



90910 (4")



90919 (4")



90922 - 90928 (6")



91000 / 90998 (5 1/2")

LED INTERIOR LIGHTING RETROFIT CANS & DISKS



tone-select™ FIXTURES (Selectable CCT - 2700K / 3000K / 3500K / 4000K / 5000K)

WATTS	ITEM#	DESCRIPTION	ENERGY STAR®	CEC STATUS	CCT	LUMENS	LPW	BEAM	CRI	MOL	VOLTS	BASE	LIFE HOURS	TRAD. EQUIV.	CASE
RETROFIT CANS - 120V DIMMING															
10	90901	4IN RETROFIT CAN/10W/27-50K/DIMM/120V/MED	★	T20	27-50K	650-750	65	105°	91	2.6"	120	MEDIUM	50,000	60W	12
15	90902	6IN RETROFIT CAN/15W/27-50K/DIMM/120V/MED	★	T20	27-50K	1000-1200	73	104°	91	3"	120	MEDIUM	50,000	75W	12
RETROFIT EYEBALL CANS - 120V DIMMING															
10	90897	4IN RETROFIT EYEBALL CAN/10W/27-50K/DIMM/120V/MED	★		27-50K	630	63	90°	90	3"	120	MEDIUM	50,000	60W	12
15	90898	6IN RETROFIT EYEBALL CAN/15W/27-50K/DIMM/120V/MED	★		27-50K	1000	67	90°	90	3"	120	MEDIUM	50,000	75W	12
SLIM DOWNLIGHTS - 120V DIMMING															
10	93090	4IN SLIM DOWNLIGHT/10W/27-50K//DIMM/120V	★		27-50K	650	65	112°	92	2.8"	120	WIRED	50,000	60W	12
15	93091	6IN SLIM DOWNLIGHT/15W/27-50K/DIMM/120V	★		27-50K	1100	73	112°	92	2.4"	120	WIRED	50,000	75W	12
RETROFIT DISK - 120V DIMMING															
15	91000	5IN/6IN RETROFIT DISK LIGHT/15W/27-50K/DIMM/120V/MED	★		27-50K	1150	77	159°	93	2.9"	120	MEDIUM	50,000	75W	12
	90998	5IN/6IN RETROFIT DISK LIGHT/15W/27-50K/DIMM/120V/MED	★		27-50K	1150	77	159°	90	0.9"	120	MEDIUM	50,000	75W	12


RETROFIT CANS

WATTS	ITEM#	DESCRIPTION	ENERGY STAR®	CEC STATUS	CCT	LUMENS	LPW	BEAM	CRI	MOL	VOLTS	BASE	LIFE HOURS	TRAD. EQUIV.	CASE
120V DIMMING															
10	90910	4IN RETROFIT CAN/10W/30K/DIMM/120V/MED	★		3000K	700	70	95°	83	2.8"	120	MEDIUM	50,000	60W	12
	90919	4IN SQ RETROFIT CAN/10W/30K/DIMM/120V/MED	★		3000K	610	61	100°	83	2.8"	120	MEDIUM	50,000	60W	12
10.5	90925	6IN RETROFIT CAN/10.5W/30K/DIMM/120V/MED	★	T20	3000K	760	72	95°	93	2.4"	120	MEDIUM	50,000	60W	12
	90927	6IN RETROFIT CAN/10.5W/40K/DIMM/120V/MED	★	T20	4000K	760	72	95°	93	2.4"	120	MEDIUM	50,000	60W	12
15	90922	6IN RETROFIT CAN/15W/30K/DIMM/120V/MED	★	T20	3000K	1000	67	95°	93	2.4"	120	MEDIUM	50,000	75W	12
	90928	6IN RETROFIT CAN/15W/50K/DIMM/120V/MED	★	T20	5000K	1000	67	95°	95	2.4"	120	MEDIUM	50,000	75W	12

ACCESSORY

Check fixture TDS to confirm compatibility of accessories.

ITEM#	DESCRIPTION	CASE
90905-QC	CONNECTOR FOR GU24 BASE ON 4IN AND 5IN/6IN CAN/DISK	1



90905-QC

Key: P = Pending / LPW = Lumens Per Watt / TRAD. EQUIV. = Traditional Equivalent

Note: Warranty and Qualifications can vary per item, see technical data sheets (TDS) for specific information. - Not all product variations listed on this page are Energy Star® qualified. Visit www.energystar.gov to confirm qualification - CEC Status identifies items listed on the MAEDBS database that are in compliance with Title 20 Regulations. Visit www.cacertappliances.energy.ca.gov to confirm compliance. - Published lumens on LED products are approximate and may vary slightly. - Specifications are subject to change without notice. - Photos and drawings may not be to scale and are for general reference only.



PREMIUM QUALITY LIGHTING® - Phone: 800-323-8107
© P.Q.L., Inc. • 2285 Ward Avenue • Simi Valley, CA 93065



www.PQLighting.com
Rev: 08/30/2022