



4" CAN



5"/6" DISK LIGHT



TONE-SELECT™ CAN



5"/6" CAN



8" CAN



TONE-SELECT™ SLIM DOWNLIGHT

LED RETROFIT CANS

INDOOR • INTERIOR LIGHTING • DIMMABLE

Superior Life® LED Retrofit Cans are convenient and easy-to-install replacements for less efficient incandescent and compact fluorescent (CFL) light sources. They consume up to 80% less energy, thereby significantly reducing operating costs. The superior life hours of these retrofits make them ideal for hard to reach places, reducing maintenance.

FEATURES

- Energy efficient
- Superior lighting performance
- Long life design
- Lightweight and easy installation
- Mercury Free - Environmentally friendly.
- Low heat reduces AC costs
- For covered ceilings only

APPLICATION

COMMERCIAL & INDUSTRIAL



Offices	Airports
Retail / Malls	Lobbies
Hospitals	General Lighting

WARRANTY*



QUALIFICATIONS*



*Warranty and Qualifications can vary per item, see technical data sheets (TDS) for specific information.



PREMIUM QUALITY LIGHTING® • Phone: 800-323-8107
© P.Q.L., Inc. • 2285 Ward Avenue • Simi Valley, CA 93065

www.PQLighting.com
Rev: 02/22/2021



TONE-SELECT™ RETROFIT CANS (Selectable CCT 27K / 30K / 40K / 50K)

WATTS	ITEM#	DESCRIPTION	ENERGY STAR®	CEC STATUS	CCT	LUMENS	LM/W	BEAM	CRI	MOL	VOLTS	BASE	AVG. LIFE HOURS	TRAD. EQUIV.	CASE
120V DIMMING															
10	90901	RETROFIT 4" CAN 10W - 27/30/40/50K/DIMM - SL®	★		27-50K	650-750	65	105°	91	2.6"	120	MEDIUM	50,000	60W	12
15	90902	RETROFIT 6" CAN 15W - 27/30/40/50K/DIMM - SL®	★		27-50K	1000-1200	73	104°	91	3"	120	MEDIUM	50,000	75W	12

TONE-SELECT™ SLIM DOWNLIGHTS (Selectable CCT 27K / 30K / 35K / 40K / 50K)

WATTS	ITEM#	DESCRIPTION	ENERGY STAR®	CEC STATUS	CCT	LUMENS	LM/W	BEAM	CRI	MOL	VOLTS	BASE	AVG. LIFE HOURS	TRAD. EQUIV.	CASE
120V DIMMING															
10	93090	SLIM DOWNLIGHT 4" 10W - 27/30/35/40/50K/DIMM - SL®	★		27-50K	650	65	112°	92	2.8"	120	WIRED	50,000	60W	12
15	93091	SLIM DOWNLIGHT 6" 15W - 27/30/35/40/50K/DIMM - SL®	★		27-50K	1100	73	112°	92	2.4"	120	WIRED	50,000	75W	12

RETROFIT CANS

WATTS	ITEM#	DESCRIPTION	ENERGY STAR®	CEC STATUS	CCT	LUMENS	LM/W	BEAM	CRI	MOL	VOLTS	BASE	AVG. LIFE HOURS	TRAD. EQUIV.	CASE
120V DIMMING															
10	90910	RETROFIT 4" CAN 10W/30K/DIMM/V4- SL®	★		3000K	700	70	95°	83	2.8"	120	MEDIUM	50,000	60W	12
	90919	RETROFIT 4" SQUARE CAN 10W/30K/DIMM/V4 - SL®	★		3000K	610	61	100°	83	2.8"	120	MEDIUM	50,000	60W	12
10.5	90925	RETROFIT 5"/6" CAN 10.5W/30K/DIMM - SL®	★		3000K	760	72	95°	93	2.4"	120	MEDIUM	50,000	60W	12
	90927	RETROFIT 5"/6" CAN 10.5W/40K/DIMM - SL®	★		4000K	760	72	95°	93	2.4"	120	MEDIUM	50,000	60W	12
	90916	RETROFIT 5"/6" CAN 10.5W/50K/DIMM - SL®	★		5000K	760	72	95°	93	2.4"	120	MEDIUM	50,000	60W	12
15	90922	RETROFIT 5"/6" CAN 15W/30K/DIMM - SL®	★		3000K	1000	67	95°	93	2.4"	120	MEDIUM	50,000	75W	12
	90928	RETROFIT 5"/6" CAN 15W/50K/DIMM - SL®	★		5000K	1000	67	95°	95	2.4"	120	MEDIUM	50,000	75W	12
	91003	RETROFIT 6" CAN 15W/30K/110-277/DIMM - SL®	★		3000K	1100	73	95°	92	4.7"	110-277	WIRED	50,000	75W	12
	91004	RETROFIT 6" CAN 15W/50K/110-277/DIMM - SL®	★		5000K	1100	73	95°	93	4.7"	110-277	WIRED	50,000	75W	12
25	90993-120D	RETROFIT 8" CAN 25W/50K/100-277/DIMM - SL®	★		5000K	1950	78	95°	83	5.3"	100-277	WIRED	50,000	100W	6

0-10V DIMMING

25	90992	RETROFIT 8" CAN 25W/30K/100-277/DIMM - SL®	★		3000K	1950	78	95°	83	5.3"	100-277	WIRED	50,000	100W	6
	90993	RETROFIT 8" CAN 25W/50K/100-277/DIMM - SL®	★		5000K	1950	78	95°	83	5.3"	100-277	WIRED	50,000	100W	6
30	90994	RETROFIT 8" CAN 30W/30K/100-277/DIMM - SL®			3000K	2350	78	95°	83	5.3"	100-277	WIRED	50,000	100W	6
	90995	RETROFIT 8" CAN 30W/50K/100-277/DIMM - SL®			5000K	2350	78	95°	83	5.3"	100-277	WIRED	50,000	100W	6

RETROFIT DISK LIGHTS

WATTS	ITEM#	DESCRIPTION	ENERGY STAR®	CEC STATUS	CCT	LUMENS	LM/W	BEAM	CRI	MOL	VOLTS	BASE	AVG. LIFE HOURS	TRAD. EQUIV.	CASE
120V DIMMING															
15	91013	RETROFIT 5"/6" DISK LIGHT 15W/30K/DIMM - SL®	★	JA8	3000K	1100	63	105°	90	1.2"	120	MEDIUM	50K	75W	12
	91014	RETROFIT 5"/6" DISK LIGHT 15W/40K/DIMM - SL®	★	JA8	4000K	1150	67	105°	90	1.2"	120	MEDIUM	50K	75W	12
	91015	RETROFIT 5"/6" DISK LIGHT 15W/50K/DIMM - SL®	★		5000K	1200	70	105°	90	1.2"	120	MEDIUM	50K	75W	12

ACCESSORY

ITEM#	DESCRIPTION	CASE
90905-QC	CONNECTOR FOR GU24 BASE ON 4" AND 5"/6" CAN/DISK - SL®	1



90905-QC

Key: DIMM = Dimmable / SL = Superior Life® / P = Pending / LM = Lumens / TRAD. EQUIV. = Traditional Equivalent

Note: For covered ceilings only. • Not all product variations listed on this page are Energy Star® qualified. Visit www.energystar.gov to confirm qualification • CEC Status identifies items listed on the MAEDBS database that are in compliance with Title 20 Regulations. Visit www.cacertappliances.energy.ca.gov to confirm compliance. • Published lumens on LED products are approximate and may vary slightly. • Specifications are subject to change without notice. • Photos and drawings may not be to scale and are for general reference only.

