



LED SPEC-SELECT™

SELECTABLE WATTAGE & CCT • INTERIOR LIGHTING • INTEGRATED LED

The Superior Life® LED Spec-Select™ Fixtures feature adjustable wattage and color temperature for the perfect balance of light in any application. There are 9 possible combinations in one fixture - use the slide switches located near the driver to select from 1 of 3 wattages and 1 of 3 color temperatures.

FEATURES

- Selectable Wattage & Color Temperature - 9 Combinations
- High Efficiency, Energy Saving
- Commercial grade construction
- Lightweight and easy installation
- Mercury Free - Environmentally friendly
- Low heat reduces AC costs
- Dimmable (0-10V, Range 10% - 100%)

APPLICATION

COMMERCIAL & INDUSTRIAL



- | | |
|---------------|-------------|
| Offices | Schools |
| Retail Stores | Warehouses |
| Banking | Work Spaces |

WARRANTY



QUALIFICATIONS*

*Qualifications can vary per item, see technical data sheets (TDS) for specific information.

LESS SKU'S TO STOCK



PREMIUM QUALITY LIGHTING® • Phone: 800-323-8107
© P.Q.L., Inc. • 2285 Ward Avenue • Simi Valley, CA 93065

www.PQLighting.com
Rev: 08/03/2020

LESS SKU'S TO STOCK

LED SPEC-SELECT™ - Selectable Wattage & CCT (Warm White / Cool White / Sky-Brite®)



INTERIOR SURFACE MOUNT FIXTURES - 120-277V

WATTS	ITEM#	DESCRIPTION	DLC®	CCT	LUMENS	LM/W	BEAM	CRI	AVG. LIFE HOURS	TRAD. EQUIV.	CASE
DESIGNER STRIP - 0-10V DIMMING											
18/25/30	55610	48" DESIGNER STRIP - 18/25/30W/35-50K/DIMM - SL®	★	35-50K	2340-3900	130	130°	82	50,000	100W	6
	55610-8WEM	48" DESIGNER STRIP - 18/25/30W/35-50K/DIMM/8W EM BATTERY - SL®	P	35-50K	2340-3900	130	130°	82	50,000	100W	6
34/38/45	55611	48" DESIGNER STRIP - 34/38/45W/35-50K/DIMM - SL®	★	35-50K	4454-5895	131	130°	82	50,000	150W	6
	55611-8WEM	48" DESIGNER STRIP - 34/38/45W/35-50K/DIMM/8W EM BATTERY - SL®	P	35-50K	4454-5895	131	130°	82	50,000	150W	6
38/46/54	55612	96" DESIGNER STRIP - 38/46/54W/35-50K/DIMM - SL®	★	35-50K	4940-7020	130	130°	82	50,000	150W	4
	55612-8WEM	96" DESIGNER STRIP - 38/46/54W/35-50K/DIMM/8W EM BATTERY - SL®	P	35-50K	4940-7020	130	130°	82	50,000	150W	4
65/75/90	55613	96" DESIGNER STRIP - 65/75/90W/35-50K/DIMM - SL®	★	35-50K	8450-11790	131	130°	82	50,000	200W	4
	55613-16WEM	96" DESIGNER STRIP - 65/75/90W/35-50K/DIMM/16W EM BATTERY - SL®	P	35-50K	8450-11790	131	130°	82	50,000	200W	4

DESIGNER STRIP RETROFIT - 0-10V DIMMING

22/30/40	55594	48" DESIGNER STRIP RETROFIT - 22/30/40W/35-50K/DIMM - SL®	P	35-50K	2860-5200	130	130°	82	50,000	150W	2
45/60/75	55597	96" DESIGNER STRIP RETROFIT - 45/60/75W/35-50K/DIMM - SL®	P	35-50K	5850-9750	130	130°	82	50,000	200W	1

WRAP-A-ROUND - 0-10V DIMMING

30/35/40	55617	48" WRAP-A-ROUND - 30/35/40W/35-50K/DIMM - SL®	★	35-50K	3990-5320	133	100°	82	50,000	150W	4
	55617-8WEM	48" WRAP-A-ROUND - 30/35/40W/35-50K/DIMM/8W EM BATTERY - SL®	P	35-50K	3990-5320	133	100°	82	50,000	150W	4

INTERIOR TROFFER FIXTURES - 120-277V

WATTS	ITEM#	DESCRIPTION	DLC®	CCT	LUMENS	LM/W	BEAM	CRI	AVG. LIFE HOURS	TRAD. EQUIV.	CASE
CENTER BASKET TROFFER - 0-10V DIMMING											
30/35/40	55600	2X2 CB TROFFER - 30/35/40W/35-50K/DIMM - SL®	★	35-50K	3750-5000	125	100°	82	50,000	150W	1
	55600-8WEM	2X2 CB TROFFER - 30/35/40W/35-50K/DIMM/8W EM BATTERY - SL®	P	35-50K	3750-5000	125	100°	82	50,000	150W	1
34/38/45	55602	2X4 CB TROFFER - 34/38/45W/35-50K/DIMM - SL®	★	35-50K	4318-5715	127	100°	82	50,000	175W	1
	55602-8WEM	2X4 CB TROFFER - 34/38/45W/35-50K/DIMM/8W EM BATTERY - SL®	P	35-50K	4318-5715	127	100°	82	50,000	175W	1

CENTER BASKET TROFFER RETROFIT - 0-10V DIMMING

30/35/40	55620	2X2 CB TROFFER RETROFIT - 30/35/40W/35-50K/DIMM - SL®	★	35-50K	3780-5040	126	100°	82	50,000	150W	1
34/38/45	55622	2X4 CB TROFFER RETROFIT - 34/38/45W/35-50K/DIMM - SL®	★	35-50K	4386-5805	129	100°	82	50,000	175W	1

PANELS - 120-277V

WATTS	ITEM#	DESCRIPTION	DLC®	CCT	LUMENS	LM/W	BEAM	CRI	AVG. LIFE HOURS	TRAD. EQUIV.	CASE
0-10V DIMMING											
25/30/40	55580	1X4 PANEL - 25/30/40W/35-50K/DIMM - SL®	★	35-50K	2750-4400	110	120°	82	50,000	100W	4
	55580-8WEM	1X4 PANEL - 25/30/40W/35-50K/DIMM/8W EM BATTERY - SL®	P	35-50K	2750-4400	110	120°	82	50,000	100W	4
25/30/40	55581	2X2 PANEL - 25/30/40W/35-50K/DIMM - SL®	★	35-50K	2750-4400	110	120°	82	50,000	100W	4
	55581-8WEM	2X2 PANEL - 25/30/40W/35-50K/DIMM/8W EM BATTERY - SL®	P	35-50K	2750-4400	110	120°	82	50,000	100W	4
30/40/50	55582	2X4 PANEL - 30/40/50W/35-50K/DIMM - SL®	★	35-50K	3330-5550	111	120°	82	50,000	150W	4
	55582-8WEM	2X4 PANEL - 30/40/50W/35-50K/DIMM /8W EM BATTERY - SL®	P	35-50K	3330-5550	111	120°	82	50,000	150W	4

RETROFIT COMMERCIAL CANS - 110-277V

WATTS	ITEM#	DESCRIPTION	ENERGY STAR®	CCT	LUMENS	LM/W	BEAM	CRI	AVG. LIFE HOURS	TRAD. EQUIV.	CASE
0-10V DIMMING											
10/15/22	90996	6" COMMERCIAL CAN - 10/15/22W/30-50K/DIMM - SL	★	30-50K	870-1950	87	92°	92	50,000	75W	6
12/20/30	90997	8" COMMERCIAL CAN - 12/20/30W/30-50K/DIMM - SL	★	30-50K	1000-2500	83	93°	92	50,000	100W	6

Continued on next page...

Key: DIMM = Dimmable / SL = Superior Life® / P = Pending / LM = Lumens / TRAD. EQUIV. = Traditional Equivalent

NOTE: Not all product variations listed on this page are DLC® or Energy Star® qualified. Visit www.designlights.org/search or www.energystar.gov to confirm qualification. • Published lumens on LED products are approximate and may vary slightly. • Specifications are subject to change without notice. • Photos and drawings may not be to scale and are for general reference only.



PREMIUM QUALITY LIGHTING® - Phone: 800-323-8107
© P.Q.L., Inc. • 2285 Ward Avenue • Simi Valley, CA 93065

www.PQLighting.com
Rev: 08/03/2020

LESS SKU'S TO STOCK

LED SPEC-SELECT™ - Selectable Wattage & CCT (Warm White / Cool White / Sky-Brite®)



VAPOR TIGHTS - 120-277V

WATTS	ITEM#	DESCRIPTION	DLC®	CCT	LUMENS	LM/W	BEAM	CRI	AVG. LIFE HOURS	TRAD. EQUIV.	CASE
0-10V DIMMING											
25/30/34	55605	4' VAPOR TIGHT - 25/30/34W/35-50K/FR/DIMM - SL®	★	35-50K	3325-4522	133	120°	81	50,000	150W	4
	55605-8WEM	4' VAPOR TIGHT - 25/30/34W/35-50K/FR/DIMM/8W EM BATTERY - SL®	P	35-50K	3325-4522	133	120°	81	50,000	150W	4
34/38/45	55606	4' VAPOR TIGHT - 34/38/45W/35-50K/FR/DIMM - SL®	★	35-50K	4420-5850	130	120°	82	50,000	175W	4
	55606-8WEM	4' VAPOR TIGHT - 34/38/45W/35-50K/FR/DIMM/8W EM BATTERY - SL®	P	35-50K	4420-5850	130	120°	82	50,000	175W	4
65/75/90	55608	8' VAPOR TIGHT - 65/75/90W/35-50K/FR/DIMM - SL®	★	35-50K	8450-11700	130	120°	82	50,000	250W	4

Key: DIMM = Dimmable / SL = Superior Life® / P = Pending / LM = Lumens / TRAD. EQUIV. = Traditional Equivalent

NOTE: Not all product variations listed on this page are DLC® or Energy Star® qualified. Visit www.designlights.org/search or www.energystar.gov to confirm qualification. • Published lumens on LED products are approximate and may vary slightly. • Specifications are subject to change without notice. • Photos and drawings may not be to scale and are for general reference only.



PREMIUM QUALITY LIGHTING® - Phone: 800-323-8107

© P.Q.L., Inc. • 2285 Ward Avenue • Simi Valley, CA 93065

www.PQLighting.com

Rev: 08/03/2020