



LED SPEC-SELECT™

SELECTABLE WATTAGE & CCT • INTERIOR LIGHTING • INTEGRATED LED

The Superior Life® LED Spec-Select™ Fixtures feature adjustable wattage and color temperature for the perfect balance of light in any application. There are 9 possible combinations in one fixture - use the slide switches located near the driver to select from 1 of 3 wattages and 1 of 3 color temperatures.

FEATURES

- Selectable Wattage & Color Temperature - 9 Combinations
- High Efficiency, Energy Saving
- Commercial grade construction
- Lightweight and easy installation
- Mercury Free - Environmentally friendly
- Low heat reduces AC costs
- Dimmable (0-10V, Range 10% - 100%)

APPLICATION

COMMERCIAL & INDUSTRIAL



Offices

Schools

Retail Stores

Warehouses

Banking

Work Spaces

WARRANTY*



QUALIFICATIONS*

*Warranty and Qualifications can vary per item, see technical data sheets (TDS) for specific information.

LESS SKU'S TO STOCK



PREMIUM QUALITY LIGHTING® • Phone: 800-323-8107

© P.Q.L., Inc. • 2285 Ward Avenue • Simi Valley, CA 93065

www.PQLighting.com

Rev: 01/16/2020

LESS SKU'S TO STOCK

LED SPEC-SELECT™ - Selectable Wattage & CCT (Warm White / Cool White / Sky-Brite®)



INTERIOR SURFACE MOUNT FIXTURES - 120-277V

WATTS	ITEM#	DESCRIPTION	DLC®	CCT	LUMENS	LM/W	BEAM	CRI	AVG. LIFE HOURS	TRAD. EQUIV.	CASE
DESIGNER STRIP - 0-10V DIMMING LED INDOOR FIXTURE - LED DESIGNER STRIP SPEC-SELECT											
18/25/30	55610	48" DESIGNER STRIP - 18/25/30W/35-50K/120-277V/DIMM - SL®	P	35-50K	2340-3960	130-132	130°	80	50,000	100W	6
34/38/45	55611	48" DESIGNER STRIP - 34/38/45W/35-50K/120-277V/DIMM - SL®	P	35-50K	4420-5940	130-132	130°	80	50,000	150W	6
38/46/54	55612	96" DESIGNER STRIP - 38/46/54W/35-50K/120-277V/DIMM - SL®	P	35-50K	4940-7128	130-132	130°	80	50,000	150W	4
65/75/90	55613	96" DESIGNER STRIP - 65/75/90W/35-50K/120-277V/DIMM - SL®	P	35-50K	8450-11880	130-132	130°	80	50,000	200W	4
WRAP-A-ROUND - 0-10V DIMMING LED INDOOR FIXTURE - LED WRAP SPEC-SELECT											
30/35/40	55617	48" WRAP-A-ROUND - 30/35/40W/35-50K/120-277V/DIMM - SL®	P	35-50K	3900-5280	130-132	100°	80	50,000	150W	4

INTERIOR TROFFER FIXTURES - 120-277V

WATTS	ITEM#	DESCRIPTION	DLC®	CCT	LUMENS	LM/W	BEAM	CRI	AVG. LIFE HOURS	TRAD. EQUIV.	CASE
CENTER BASKET TROFFER - 0-10V DIMMING LED INDOOR FIXTURE - LED TROFFER SPEC-SELECT											
30/35/40	55600	2X2 CB TROFFER - 30/35/40W/35-50K/120-277V/DIMM - SL®	P	35-50K	3750-5080	125-127	100°	80	50,000	150W	1
34/38/45	55602	2X4 CB TROFFER - 34/38/45W/35-50K/120-277V/DIMM - SL®	P	35-50K	4250-5715	125-127	100°	80	50,000	175W	1
CENTER BASKET TROFFER RETROFIT - 0-10V DIMMING LED INDOOR FIXTURE - LED TROFFER RETROFIT											
30/35/40	55620	2X2 CB TROFFER RETROFIT - 30/35/40W/35-50K/120-277V/DIMM - SL®	P	35-50K	3750-5080	125-127	100°	80	50,000	150W	1
34/38/45	55622	2X4 CB TROFFER RETROFIT - 34/38/45W/35-50K/120-277V/DIMM - SL®	P	35-50K	4250-5715	125-127	100°	80	50,000	175W	1

PANELS - 120-277V

WATTS	ITEM#	DESCRIPTION	DLC®	CCT	LUMENS	LM/W	BEAM	CRI	AVG. LIFE HOURS	TRAD. EQUIV.	CASE
0-10V DIMMING LED PANELS - PANEL SPEC-SELECT											
25/30/40	55580	1X4 PANEL - 25/30/40W/35-50K/120-277V/DIMM - SL®	P	35-50K	2900-4480	110-118	120°	80	50,000	100W	4
25/30/40	55581	2X2 PANEL - 25/30/40W/35-50K/120-277V/DIMM - SL®	P	35-50K	2900-4480	110-118	120°	80	50,000	100W	4
30/40/50	55582	2X4 PANEL - 30/40/50W/35-50K/120-277V/DIMM - SL®	P	35-50K	3480-5600	110-118	120°	80	50,000	150W	4

RETROFIT COMMERCIAL CANS - 110-277V

WATTS	ITEM#	DESCRIPTION	ENERGY STAR®	CCT	LUMENS	LM/W	BEAM	CRI	AVG. LIFE HOURS	TRAD. EQUIV.	CASE
0-10V DIMMING LED COMMERCIAL CAN											
10/15/22	90996	COMMERCIAL 6" CAN - 10/15/22W/30-50K/110-277V/DIMM - SL	P	30-50K	850-1950	85-89	92°	90	50,000	75W	6
12/20/30	90997	COMMERCIAL 8" CAN - 12/20/30W/30-50K/110-277V/DIMM - SL	P	30-50K	1000-2500	83	93°	90	50,000	100W	6

VAPOR TIGHTS - 120-277V

WATTS	ITEM#	DESCRIPTION	DLC®	CCT	LUMENS	LM/W	BEAM	CRI	AVG. LIFE HOURS	TRAD. EQUIV.	CASE
0-10V DIMMING LED VAPOR TIGHT / LED INTEGRATED SPEC-SELECT											
25/30/34	55605	VAPOR TIGHT 4' - 25/30/34W/35-50K/FR LENS/120-277V/DIMM - SL®	P	35-50K	3250-4488	130-132	120°	80	50,000	150W	4
34/38/45	55606	VAPOR TIGHT 4' - 34/38/45W/35-50K/FR LENS/120-277V/DIMM - SL®	P	35-50K	4420-5490	130-132	120°	80	50,000	175W	4
65/75/90	55608	VAPOR TIGHT 8' - 65/75/90W/35-50K/FR LENS/120-277V/DIMM - SL®	P	35-50K	8450-11880	130-132	120°	80	50,000	250W	4

Key: DIMM = Dimmable / SL = Superior Life® / P = Pending / LM = Lumens / TRAD. EQUIV. = Traditional Equivalent

NOTE: Not all product variations listed on this page are DLC® or Energy Star® qualified. Visit www.designlights.org/search or www.energystar.gov to confirm qualification. - Published lumens on LED products are approximate and may vary slightly. - Specifications are subject to change without notice. - Photos and drawings may not be to scale and are for general reference only.



PREMIUM QUALITY LIGHTING® - Phone: 800-323-8107
© P.Q.L., Inc. • 2285 Ward Avenue • Simi Valley, CA 93065

www.PQLighting.com
Rev: 01/16/2020

