



LED STANDARD PANELS

INDOOR • INTERIOR LIGHTING • DIMMABLE

Superior Life® LED Panels are energy efficient, lightweight with a slim low profile design. Our panels reduce energy usage and deliver bright, edge to edge uniform light with a long life (50,000 hrs) significantly reducing maintenance costs over the life of the panel, quickly paying for itself. The construction allows excellent heat dispersion and convenient installation.

FEATURES

- High Efficiency, Energy Saving
- Up to 36% Savings vs. T8 Fluorescent
- Slim Profile Design
- 120° Wide Beam Angle - Great for area lighting.
- Low glare, bright consistent lighting
- Simple Installation - Ideal for t-grid and drywall ceilings.
- Low heat reduces AC costs
- Dimmable (1-10V, Range 10% - 100%)

APPLICATIONS

COMMERCIAL & INDUSTRIAL



- | | |
|-------------------|-------------|
| Conference Rooms | Hospitality |
| Office Lighting | Classrooms |
| Convention Center | Workshops |
| Hospitals | Large Areas |
| Lobbies | Cafeterias |

WARRANTY



QUALIFICATIONS



Qualifications vary, see technical data for specific information.





PANELS

WATTS	ITEM#	DESCRIPTION	DLC*	UL/ETL	CCT	LUMENS	LM/W	BEAM	CRI	VOLTS	FINISH	LIFE	TRAD. EQUIV.	CASE
1X4 PANELS LED PANELS - PANEL 1X4 - STANDARD														
40	55425	1X4 PANEL - 40W/35K/120-277V/DIMMABLE/V6 - SL*	★	ETL	3500K	4050	101	120°	83	120-277	WHITE	50K	75W	2
	55339	1X4 PANEL - 40W/40K/120-277V/DIMMABLE/V5 - SL*	★	UL	4000K	4320	108	120°	82	120-277	WHITE	50K	75W	2
	55426	1X4 PANEL - 40W/40K/120-277V/DIMMABLE/V6 - SL*	★	ETL	4000K	4100	103	120°	83	120-277	WHITE	50K	75W	2
	55340	1X4 PANEL - 40W/50K/120-277V/DIMMABLE/V5 - SL*	★	UL	5000K	4360	109	120°	82	120-277	WHITE	50K	75W	2
	55427	1X4 PANEL - 40W/50K/120-277V/DIMMABLE/V6 - SL*	★	ETL	5000K	4150	104	120°	83	120-277	WHITE	50K	75W	2
2X2 PANELS LED PANELS - PANEL 2X2 - STANDARD														
40	55341	2X2 PANEL - 40W/35K/120-277V/DIMMABLE/V5 - SL*	★	UL	3500K	4200	105	120°	80	120-277	WHITE	50K	75W	2
	55428	2X2 PANEL - 40W/35K/120-277V/DIMMABLE/V6 - SL*	★	ETL	3500K	4050	101	120°	83	120-277	WHITE	50K	75W	2
	55429	2X2 PANEL - 40W/40K/120-277V/DIMMABLE/V6 - SL*	★	ETL	4000K	4100	103	120°	83	120-277	WHITE	50K	75W	2
	55430	2X2 PANEL - 40W/50K/120-277V/DIMMABLE/V6 - SL*	★	ETL	5000K	4150	104	120°	83	120-277	WHITE	50K	75W	2
2X4 PANELS LED PANELS - PANEL 2X4 - STANDARD														
50	55287	2X4 PANEL - 50W/30K/120-277V/DIMMABLE/V5 - SL*	★	UL	3000K	5255	104	120°	83	120-277	WHITE	50K	150W	2
	55431	2X4 PANEL - 50W/35K/120-277V/DIMMABLE/V6 - SL*	★	ETL	3500K	5100	102	120°	83	120-277	WHITE	50K	150W	2
	55288	2X4 PANEL - 50W/40K/120-277V/DIMMABLE/V5 - SL*	★	UL	4000K	5311	105	120°	83	120-277	WHITE	50K	150W	2
	55432	2X4 PANEL - 50W/40K/120-277V/DIMMABLE/V6 - SL*	★	ETL	4000K	5200	104	120°	82	120-277	WHITE	50K	150W	2
	55433	2X4 PANEL - 50W/50K/120-277V/DIMMABLE/V6 - SL*	★	ETL	5000K	5300	106	120°	83	120-277	WHITE	50K	150W	2
65	55348	2X4 PANEL - 65W/40K/120-277V/DIMMABLE/V5 - SL*	★	UL	4000K	6630	102	120°	80	120-277	WHITE	50K	200W	2
	55349	2X4 PANEL - 65W/50K/120-277V/DIMMABLE/V5 - SL*	★	UL	5000K	6760	104	120°	80	120-277	WHITE	50K	200W	2
75	55290	2X4 PANEL - 75W/30K/120-277V/DIMMABLE/V5 - SL*	★	UL	3000K	7426	99	120°	83	120-277	WHITE	50K	200W	2
	55436	2X4 PANEL - 75W/50K/120-277V/DIMMABLE/V6 - SL*	★	ETL	5000K	7500	100	120°	83	120-277	WHITE	50K	200W	2

ACCESSORIES

ITEM#	DESCRIPTION	ACCESSORY	CASE
MOUNTING KITS			
1X4	55127	1X4 FLANGE KIT FOR PANEL & TROFFER/WHITE - SUPERIOR LIFE®	1
	55317	1X4 SURFACE MOUNTED KIT FOR LED PANEL/WHITE - SUPERIOR LIFE®	1
	55440	1X4 SURFACE MOUNTED KIT FOR LED PANEL/WHITE/V6 - SUPERIOR LIFE®	25
2X2	55128	2X2 FLANGE KIT FOR PANEL & TROFFER/WHITE - SUPERIOR LIFE®	1
	55323	2X2 SURFACE MOUNTED KIT FOR LED PANEL/WHITE - SUPERIOR LIFE®	1
	55441	2X2 SURFACE MOUNTED KIT FOR LED PANEL/WHITE/V6 - SUPERIOR LIFE®	50
2X4	55129	2X4 FLANGE KIT FOR PANEL & TROFFER/WHITE - SUPERIOR LIFE®	1
	55325	2X4 SURFACE MOUNTING KIT FOR LED PANEL/WHITE - SUPERIOR LIFE®	1
	55442	2X4 SURFACE MOUNTED KIT FOR LED PANEL/WHITE/V6 - SUPERIOR LIFE®	25
	55296	2X2 SUSPENDED CABLE MOUNTING KIT FOR LED PANEL - SUPERIOR LIFE®	1
	55324	2X2 OR 2X4 SUSPENDED CABLE MOUNTING KIT FOR LED PANEL - SUPERIOR LIFE®	1
	55445	SUSPENDED CABLE MOUNTING KIT FOR LED PANEL/V6 - SUPERIOR LIFE®	100
EMERGENCY PACKS			
8	55319	EMERGENCY PACK FOR LED FIXTURE 8W/90 MIN - INTEGRATION TYPE	1
16	55320	EMERGENCY PACK FOR LED FIXTURE 16W/90 MIN - INTEGRATION TYPE	1
25	55321	EMERGENCY PACK FOR LED FIXTURE 25W/90 MIN - INTEGRATION TYPE	1
15	55449	EMERGENCY PACK FOR LED PANEL 15W/90 MIN - SUPERIOR LIFE®	6
25	55450	EMERGENCY PACK FOR LED PANEL 25W/90 MIN - SUPERIOR LIFE®	6
	55356	MOUNTING BRACKET FOR EMERGENCY BATTERY FOR 1X4 LED PANEL	60
	55357	MOUNTING BRACKET FOR EMERGENCY BATTERY FOR 2X2 OR 2X4 LED PANEL	60
WALL SWITCH			
IP710-LFZ	W/I/LA SLIDE DIM 0-10V SP-3W 1200VA120V		10

Key: SL = Superior Life® / LM = Lumens

NOTE: Not all product variations listed on this page are DLC qualified. Visit www.designlights.org/search to confirm qualification. • Published lumens on LED products are approximate and may vary slightly. • Specifications are subject to change without notice. • Photos and drawings may not be to scale and are for general reference only.

