



LED VAPOR TIGHT

INTEGRATED LED

The Superior Life® LED Vapor Tight Fixtures are high quality with integrated LEDs for excellent efficiency and optimal performance. They consume less energy than traditional lighting, significantly reducing operating costs and are environmentally friendly.

FEATURES

- High Efficiency, Energy Saving
- Sturdy construction - withstands harsh environments.
- Stainless steel clips
- Full perimeter silicone gasket
- UV-Stabilized Polycarbonate
- IP65 Rated
- Low-Profile
- Mercury Free - Environmentally friendly.
- Dimmable (0-10V, Range 10% - 100%)

APPLICATION

COMMERCIAL & INDUSTRIAL



Car Wash	Cold Storage
Parking Garage	Tunnels
Airports	Stairwells

WARRANTY*



QUALIFICATIONS*



*Warranty and Qualifications can vary per item, see technical data sheets (TDS) for specific information.



PREMIUM QUALITY LIGHTING® • Phone: 800-323-8107
© P.Q.L., Inc. • 2285 Ward Avenue • Simi Valley, CA 93065

www.PQLighting.com
Rev: 08/03/2020



120-277V FIXTURES

WATTS	ITEM#	DESCRIPTION	DLC*	CCT	LUMENS	LM/W	BEAM	CRI	VOLTS	AVG. LIFE HOURS	TRAD. EQUIV.	CASE
2FT - 0-10V DIMMING												
20	55371	2' VAPOR TIGHT - 20W/40K/FR LENS/DIMMABLE/V2 - SL*	★	4000K	2620	131	120°	82	120-277	50,000	100W	4
	55372	2' VAPOR TIGHT - 20W/50K/FR LENS/DIMMABLE/V2 - SL*	★	5000K	2640	132	120°	82	120-277	50,000	100W	4
4FT - 0-10V DIMMING												
34	55374	4' VAPOR TIGHT - 34W/40K/FR LENS/DIMMABLE/V2 - SL*	★	4000K	4420	130	120°	82	120-277	50,000	150W	4
	55375	4' VAPOR TIGHT - 34W/50K/FR LENS/DIMMABLE/V2 - SL*	★	5000K	4454	131	120°	82	120-277	50,000	150W	4
52	55377	4' VAPOR TIGHT - 52W/40K/FR LENS/DIMMABLE/V2 - SL*	★	4000K	6760	130	120°	82	120-277	50,000	175W	4
	55378	4' VAPOR TIGHT - 52W/50K/FR LENS/DIMMABLE/V2 - SL*	★	5000K	6812	131	120°	82	120-277	50,000	175W	4
8FT - 0-10V DIMMING												
75	55380	8' VAPOR TIGHT - 75W/40K/FR LENS/DIMMABLE/V2 - SL*	★	4000K	9750	130	120°	82	120-277	50,000	250W	4
	55381	8' VAPOR TIGHT - 75W/50K/FR LENS/DIMMABLE/V2 - SL*	★	5000K	9825	131	120°	82	120-277	50,000	250W	4

SPEC-SELECT™ FIXTURES - 120-277V (Selectable Wattage & CCT - Warm White / Cool White / Sky-Brite®)

WATTS	ITEM#	DESCRIPTION	DLC*	CCT	LUMENS	LM/W	BEAM	CRI	VOLTS	AVG. LIFE HOURS	TRAD. EQUIV.	CASE
4FT - 0-10V DIMMING												
25/30/34	55605	4' VAPOR TIGHT - 25/30/34W/35-50K/FR/DIMM - SL*	★	35-50K	3325-4522	133	120°	82	120-277	50,000	150W	4
	55605-8WEM	4' VAPOR TIGHT - 25/30/34W/35-50K/FR/DIMM/8W EM BATTERY - SL*	P	35-50K	3325-4522	133	120°	82	120-277	50,000	150W	4
34/38/45	55606	4' VAPOR TIGHT - 34/38/45W/35-50K/FR/DIMM - SL*	★	35-50K	4420-5850	130	120°	82	120-277	50,000	175W	4
	55606-8WEM	4' VAPOR TIGHT - 34/38/45W/35-50K/FR/DIMM/8W EM BATTERY - SL*	P	35-50K	4420-5850	130	120°	82	120-277	50,000	175W	4
8FT - 0-10V DIMMING												
65/75/90	55608	8' VAPOR TIGHT - 65/75/90W/35-50K/FR/DIMM - SL*	★	35-50K	8450-11700	130	120°	82	120-277	50,000	250W	4

ACCESSORIES

WATTS	ITEM#	DESCRIPTION	CEC STATUS	CASE
8	55390	EMERGENCY PACK FOR LED FIXTURE 8W/90 MIN - SPLIT TYPE/L - SL* (For use with drivers that are 100W or less.)	T20	10
16	55391	EMERGENCY PACK FOR LED FIXTURE 16W/90 MIN - SPLIT TYPE/L - SL* (For use with drivers that are 100W or less.)	T20	10
25	55392	EMERGENCY PACK FOR LED FIXTURE 25W/90 MIN - SPLIT TYPE/L - SL* (For use with drivers that are 100W or less.)	T20	1



55390 / 55391
55392

Key: DIMM = Dimmable / SL = Superior Life® / P = Pending / LM = Lumens / TRAD. EQUIV. = Traditional Equivalent

Note: Not all product variations listed on this page are DLC* qualified. Visit www.designlights.org/search to confirm qualification. • CEC Status identifies items listed on the MAEDBS database that are in compliance with Title 20 or Title 24 Regulations. Visit www.cacertappliances.energy.ca.gov to confirm compliance. • Published lumens on LED products are approximate and may vary slightly. • Specifications are subject to change without notice. • Photos and drawings may not be to scale and are for general reference only.

