



MINI WALL PACKS



WALL PACKS

LED WALL PACKS

OUTDOOR • EXTERIOR LIGHTING • WALL MOUNTED

Superior Life® LED Wall Packs are high quality, designed for outdoor use. Perfect for illuminating entrances, architectural features, walls, walkways and providing added security lighting. Our energy-saving wall packs deliver bright, uniform light with a long life (50,000 hrs) significantly reducing maintenance costs and energy use over the life of the fixture, quickly paying for itself.

FEATURES

- High Efficiency, Energy Saving
- High Performance LEDs - High lumens per watt light output.
- Durable Construction
- Mercury Free - Environmentally friendly.
- Vibration and shock resistant
- Wet Location Rated
- Customizable - available in a variety of finishes and color temperatures. Contact your sales representative to discuss your specific needs.

APPLICATION

COMMERCIAL & INDUSTRIAL



Architectural Warehouses

Entrances Doorways

Building Security

Perimeter Lighting

WARRANTY*



QUALIFICATIONS*



*Warranty and Qualifications can vary per item, see technical data sheets (TDS) for specific information.

Fixtures are available in a variety of finishes and color temperatures.
Contact your sales representative to discuss your specific needs.



MINI WALL PACKS (Typical use: Entrance & Doorways)

WATTS	ITEM#	DESCRIPTION	DLC°	UL/ETL	CCT	LUMENS	LM/W	BEAM	CRI	VOLTS	FINISH	AVG. LIFE HOURS	TRAD. EQUIV.	CASE
NON-DIMMABLE														
13	83170-NP	MINI WALL PACK 13W/30K/FR/120V - SL°		UL	3000K	1200	92	95°	80	120	BLACK	50,000	25W	12
15	83116	MINI WALL PACK 15W/41K/CL - SL°		N/A	4100K	1500	100	120°	85	90-264	BLACK	50,000	25W	8
17	83354	MINI WALL PACK 17W/40K/CL/PC/120-277V - SL° <i>Qualification Model # L-MWP-17-40K-B-PC2</i>	★	UL	4000K	1900	112	81°	70	120-277	BLACK	50,000	25W	12
	83355	MINI WALL PACK 17W/40K/CL/120-277V - SL° <i>Qualification Model # L-MWP-17-40K-B</i>	★	UL	4000K	1900	112	81°	70	120-277	BLACK	50,000	25W	12
25	83691	MINI WALL PACK 25W/40K/CL/PC/120-277V/DIMM - SL° <i>Qualification Model # MWP-25-[D,P]-40K</i>	★	ETL	4000K	3174	136	90°	70	120-277	BLACK	50,000	50W	8
	83357	MINI WALL PACK 25W/40K/CL/120-277V - SL° <i>Qualification Model # L-MWP-25-40K-B</i>	★	UL	4000K	2500	100	84°	70	120-277	BLACK	50,000	50W	12
	83284	MINI WALL PACK 25W/40K/WHITE/CL/120-277V - SL°	★	UL	4000K	2500	100	81°	70	120-277	WHITE	50,000	50W	12
	83285	MINI WALL PACK 25W/40K/WHITE/CL/120-277V - SL° <i>Qualification Model # L-MWP-25-40K-W</i>	★	UL	4000K	2500	100	81°	70	120-277	WHITE	50,000	50W	12

WALL PACKS (Typical use: Building Security, Perimeter Lighting)

WATTS	ITEM#	DESCRIPTION	DLC°	UL/ETL	CCT	LUMENS	LM/W	BEAM	CRI	VOLTS	FINISH	AVG. LIFE HOURS	TRAD. EQUIV.	CASE
0-10V DIMMING														
60	84172	WALL PACK 60W/50K/120-277V/DIMM/BRZ/V2 - SL°	★	ETL	5000K	7200	120	110° x 105°	80	120-277	BRONZE	50,000	250W	1
120	84176	WALL PACK 120W/50K/120-277V/DIMM/BRZ/V2 - SL°	★	ETL	5000K	15800	132	110° x 105°	70	120-277	BRONZE	50,000	400W	1
NON-DIMMABLE														
25	83328	WALL PACK 25W/50K/120-277V - SL°	★	ETL	5000K	2930	117	110° x 105°	80	120-277	BRONZE	50,000	100W	1
40	84170	WALL PACK 40W/50K/120-277V/BRZ/V2 - SL°	★	ETL	5000K	4800	120	110° x 105°	80	120-277	BRONZE	50,000	175W	1
80	84174	WALL PACK 80W/50K/120-277V/BRZ/V2 - SL°	★	ETL	5000K	9760	120	110° x 105°	80	120-277	BRONZE	50,000	320W	1

ACCESSORIES

ITEM#	DESCRIPTION	CASE
83335	SHIELD ONLY FOR LED WALL PACK - SL°	1
83336	BUTTON STYLE PHOTO CELL FOR LED WALL PACK/120-277V - SL°	1



83335



83336

Key: FR = Frosted Lens / CL = Clear Lens / PC = Photo Cell / SL = Superior Life® / P = Pending / LM = Lumens / TRAD. EQUIV. = Traditional Equivalent

NOTE: Not all product variations listed on this page are DLC° qualified. Visit www.designlights.org/search to confirm qualification. • Published lumens on LED products are approximate and may vary slightly. • Specifications are subject to change without notice. • Photos and drawings may not be to scale and are for general reference only.



PREMIUM QUALITY LIGHTING® • Phone: 800-323-8107
© P.Q.L., Inc. • 2285 Ward Avenue • Simi Valley, CA 93065

www.PQLighting.com
Rev: 02/03/2021