



LED LIGHTING

A-LAMPS

These Superior Life® lamps are an efficient way to light sockets once reserved for traditional lamps. They consume up to 80% less energy, thereby significantly reducing operating costs. The superior life hours of these lamps make them ideal for hard to reach places, reducing maintenance.

Application: A general purpose replacement for traditional light bulbs around the home and office; table and floor lamps, wall sconces and ceiling or pendant fixtures.

FEATURES

- Superior lighting performance
- Energy efficient
- Lightweight and easy installation
- Superior Life® design
- Resembles traditional lighting
- Mercury Free - Environmentally friendly.
- Low heat reduces AC costs

Dimmable Superior Life® dimmable LED lamps function with wall dimmers just as normal incandescent lamps do by allowing full linear dimming control. *(When applicable)*



A15



A19



A19/BUG LIGHT



A19/GU24



A21



A23

Note: Warranty and Qualifications can vary per item, see technical data sheets (TDS) for specific information. • Not all product variations listed on this page are Energy Star® qualified. Visit www.energystar.gov to confirm qualification • CEC Status identifies items listed on the MAEDBS database that are in compliance with Title 20 or Title 24 Regulations. Visit www.cacertappliances.energy.ca.gov to confirm compliance. • Published lumens on LED products are approximate and may vary slightly. • Specifications are subject to change without notice. • Photos and drawings may not be to scale and are for general reference only.



LED LIGHTING A-LAMPS



A15 LAMPS

WATTS	ITEM#	DESCRIPTION	ENERGY STAR®	CEC STATUS	CCT	LUMENS	LPW	BEAM	CRI	MOL	VOLTS	BASE	LIFE HOURS	TRAD. EQUIV.	CASE
NON-DIMMABLE															
4.5	91236	4.5WA15/30K			3000K	300	67	150°	80	3.3"	120	MEDIUM	15,000	40W	48
	91237	4.5WA15/40K			4000K	300	67	150°	80	3.3"	120	MEDIUM	15,000	40W	48
	91238	4.5WA15/50K			5000K	300	67	150°	80	3.3"	120	MEDIUM	15,000	40W	48

A19 LAMPS

WATTS	ITEM#	DESCRIPTION	ENERGY STAR®	CEC STATUS	CCT	LUMENS	LPW	BEAM	CRI	MOL	VOLTS	BASE	LIFE HOURS	TRAD. EQUIV.	CASE
DIMMABLE															
5	91881	5.5WA19/27K/DIMM	★		2700K	450	82	220°	83	4.1"	120	MEDIUM	25,000	40W	96
	91882	5.5WA19/30K/DIMM	★		3000K	450	82	220°	83	4.1"	120	MEDIUM	25,000	40W	96
	91883	5.5WA19/40K/DIMM	★		4000K	450	82	220°	82	4.1"	120	MEDIUM	25,000	40W	96
	91884	5.5WA19/50K/DIMM	★		5000K	450	82	220°	84	4.1"	120	MEDIUM	25,000	40W	96
9	91885	9WA19/27K/DIMM			2700K	800	89	220°	83	4.1"	120	MEDIUM	25,000	60W	96
	91886	9WA19/30K/DIMM			3000K	800	89	220°	83	4.1"	120	MEDIUM	25,000	60W	96
	91887	9WA19/40K/DIMM			4000K	800	89	220°	83	4.1"	120	MEDIUM	25,000	60W	96
	91888	9WA19/50K/DIMM			5000K	800	89	220°	83	4.1"	120	MEDIUM	25,000	60W	96
10	91902	10WA19/27K/DIMM	★	T20	2700K	800	80	220°	92	4.3"	120	MEDIUM	25,000	60W	96
	91903	10WA19/30K/DIMM	★	T20	3000K	800	80	220°	90	4.3"	120	MEDIUM	25,000	60W	96
	91918	10WA19/50K/DIMM	★	T20	5000K	800	80	220°	90	4.3"	120	MEDIUM	25,000	60W	96
11	91904	11WA19/27K/DIMM	★	T20	2700K	1100	110	220°	91	4.5"	120	MEDIUM	25,000	75W	96
	91905	11WA19/30K/DIMM	★	T20	3000K	1100	110	220°	94	4.5"	120	MEDIUM	25,000	75W	96
	91919	11WA19/50K/DIMM	★	T20	5000K	1100	110	220°	90	4.5"	120	MEDIUM	25,000	75W	96
	91889	11WA19/27K/DIMM	★		2700K	1100	110	220°	83	4.5"	120	MEDIUM	25,000	75W	96
	91890	11WA19/30K/DIMM	★		3000K	1100	110	220°	84	4.5"	120	MEDIUM	25,000	75W	96
	91891	11WA19/40K/DIMM	★		4000K	1100	110	220°	84	4.5"	120	MEDIUM	25,000	75W	96
	91892	11WA19/50K/DIMM	★		5000K	1100	110	220°	82	4.5"	120	MEDIUM	25,000	75W	96
	91893	15WA19/27K/DIMM			2700K	1600	107	220°	82	4.6"	120	MEDIUM	25,000	100W	96
91894	15WA19/30K/DIMM			3000K	1600	107	220°	82	4.6"	120	MEDIUM	25,000	100W	96	
91895	15WA19/40K/DIMM			4000K	1600	107	220°	82	4.6"	120	MEDIUM	25,000	100W	96	
91896	15WA19/50K/DIMM			5000K	1600	107	220°	81	4.6"	120	MEDIUM	25,000	100W	96	

NON-DIMMABLE

6	91865	6WA19/27K			2700K	450	75	220°	80	4.1"	120	MEDIUM	25,000	40W	96
	91866	6WA19/30K			3000K	450	75	220°	80	4.1"	120	MEDIUM	25,000	40W	96
	91867	6WA19/40K			4000K	450	75	220°	80	4.1"	120	MEDIUM	25,000	40W	96
	91868	6WA19/50K			5000K	450	75	220°	80	4.1"	120	MEDIUM	25,000	40W	96
9	91869	9WA19/27K			2700K	800	89	220°	80	4.1"	120	MEDIUM	25,000	60W	96
	91870	9WA19/30K			3000K	800	89	220°	80	4.1"	120	MEDIUM	25,000	60W	96
	91871	9WA19/40K			4000K	800	89	220°	80	4.1"	120	MEDIUM	25,000	60W	96
	91872	9WA19/50K			5000K	800	89	220°	80	4.1"	120	MEDIUM	25,000	60W	96
9.5	90965	9.5WA19/24K/BUG LIGHT		N/A	2400K	650	68	140°	80	4.4"	120	MEDIUM	15,000	60W	48
11	91873	11WA19/27K			2700K	1100	110	200°	80	4.3"	120	MEDIUM	25,000	75W	96
	91874	11WA19/30K			3000K	1100	110	200°	80	4.3"	120	MEDIUM	25,000	75W	96
	91875	11WA19/40K			4000K	1100	110	200°	80	4.3"	120	MEDIUM	25,000	75W	96
	91876	11WA19/50K			5000K	1100	110	200°	80	4.3"	120	MEDIUM	25,000	75W	96

Key: P = Pending / N/A = Not Applicable / LPW = Lumens Per Watt / TRAD. EQUIV. = Traditional Equivalent

Note: Warranty and Qualifications can vary per item, see technical data sheets (TDS) for specific information. • Not all product variations listed on this page are Energy Star® qualified. Visit www.energystar.gov to confirm qualification • CEC Status identifies items listed on the MAEDBS database that are in compliance with Title 20 or Title 24 Regulations. Visit www.cacertappliances.energy.ca.gov to confirm compliance. • Published lumens on LED products are approximate and may vary slightly. • Specifications are subject to change without notice. • Photos and drawings may not be to scale and are for general reference only.



PREMIUM QUALITY LIGHTING® • Phone: 800-323-8107
© P.Q.L., Inc. • 2285 Ward Avenue • Simi Valley, CA 93065

www.PQLighting.com
Rev: 05/06/2022

LED LIGHTING A-LAMPS



A19 LAMPS

WATTS	ITEM#	DESCRIPTION	ENERGY STAR®	CEC STATUS	CCT	LUMENS	LPW	BEAM	CRI	MOL	VOLTS	BASE	LIFE HOURS	TRAD. EQUIV.	CASE
NON-DIMMABLE															
15	91877	15WA19/27K			2700K	1600	107	220°	80	4.6"	120	MEDIUM	25,000	100W	96
	91878	15WA19/30K			3000K	1600	107	220°	80	4.6"	120	MEDIUM	25,000	100W	96
	91879	15WA19/40K			4000K	1600	107	220°	80	4.6"	120	MEDIUM	25,000	100W	96
	91880	15WA19/50K			5000K	1600	107	220°	80	4.6"	120	MEDIUM	25,000	100W	96

A19/GU24 LAMPS

WATTS	ITEM#	DESCRIPTION	ENERGY STAR®	CEC STATUS	CCT	LUMENS	LPW	BEAM	CRI	MOL	VOLTS	BASE	LIFE HOURS	TRAD. EQUIV.	CASE
DIMMABLE															
9	91910	9WA19/27K/DIMM/GU24	★		2700K	800	89	220°	83	3.7"	120	GU24	25,000	60W	96
	91911	9WA19/30K/DIMM/GU24	★		3000K	800	89	220°	82	3.7"	120	GU24	25,000	60W	96
	91912	9WA19/40K/DIMM/GU24	★		4000K	800	89	220°	83	3.7"	120	GU24	25,000	60W	96
	91913	9WA19/50K/DIMM/GU24	★		5000K	800	89	220°	85	3.7"	120	GU24	25,000	60W	96
10	91914	10WA19/27K/DIMM/GU24			2700K	1100	110	220°	80	3.7"	120	GU24	25,000	75W	96
	91915	10WA19/30K/DIMM/GU24			3000K	1100	110	220°	80	3.7"	120	GU24	25,000	75W	96
	91916	10WA19/40K/DIMM/GU24			4000K	1100	110	220°	80	3.7"	120	GU24	25,000	75W	96
	91917	10WA19/50K/DIMM/GU24			5000K	1100	110	220°	80	3.7"	120	GU24	25,000	75W	96

A21 LAMPS

WATTS	ITEM#	DESCRIPTION	ENERGY STAR®	CEC STATUS	CCT	LUMENS	LPW	BEAM	CRI	MOL	VOLTS	BASE	LIFE HOURS	TRAD. EQUIV.	CASE
NON-DIMMABLE															
5/9/16	91083	5-9-16WA21/3 WAY/30K			3000K	450-1600	90-100	230°	82	5.2"	120	MEDIUM	15,000	30/50/100W	48
14	91073	14WA21/27K			2700K	1521	109	140°	80	5.2"	120	MEDIUM	15,000	100W	48
17	91897	17WA21/27K/120-277V	★		2700K	2000	118	220°	81	4.9"	120-277	MEDIUM	25,000	125W	48
	91898	17WA21/30K/120-277V	★		3000K	2000	118	220°	83	4.9"	120-277	MEDIUM	25,000	125W	48
	91899	17WA21/40K/120-277V	★		4000K	2000	118	220°	82	4.9"	120-277	MEDIUM	25,000	125W	48
	91900	17WA21/50K/120-277V	★		5000K	2000	118	220°	82	4.9"	120-277	MEDIUM	25,000	125W	48
20	91906	20WA21/30K/120-277V	P		3000K	2600	130	230°	80	5.4"	120-277	MEDIUM	25,000	150W	48
	91908	20WA21/50K/120-277V	P		5000K	2600	130	230°	80	5.4"	120-277	MEDIUM	25,000	150W	48

A23 LAMPS

WATTS	ITEM#	DESCRIPTION	ENERGY STAR®	CEC STATUS	CCT	LUMENS	LPW	BEAM	CRI	MOL	VOLTS	BASE	LIFE HOURS	TRAD. EQUIV.	CASE
DIMMABLE															
23	91686	23WA23/30K/DIMM/120-277V	★		3000K	2550	111	230°	82	5.9"	120-277	MEDIUM	25,000	150W	48
	91687	23WA23/40K/DIMM/120-277V	★		4000K	2550	111	230°	82	5.9"	120-277	MEDIUM	25,000	150W	48
	91688	23WA23/50K/DIMM/120-277V	★		5000K	2550	111	230°	86	5.9"	120-277	MEDIUM	25,000	150W	48

Key: P = Pending / N/A = Not Applicable / LPW = Lumens Per Watt / TRAD. EQUIV. = Traditional Equivalent

Note: Warranty and Qualifications can vary per item, see technical data sheets (TDS) for specific information. • Not all product variations listed on this page are Energy Star® qualified. Visit www.energystar.gov to confirm qualification • CEC Status identifies items listed on the MAEDBS database that are in compliance with Title 20 or Title 24 Regulations. Visit www.cacertappliances.energy.ca.gov to confirm compliance. • Published lumens on LED products are approximate and may vary slightly. • Specifications are subject to change without notice. • Photos and drawings may not be to scale and are for general reference only.



PREMIUM QUALITY LIGHTING® • Phone: 800-323-8107
© P.Q.L., Inc. • 2285 Ward Avenue • Simi Valley, CA 93065

www.PQLighting.com
Rev: 05/06/2022