



PLUG & GO™ LAMPS



180° LAMPS



360° LAMPS

LED CFL STYLE LAMPS

DIRECT REPLACEMENT • DIRECT WIRE • G24q • MEDIUM BASE

Superior Life® LED CFL style lamps are an efficient way to light sockets once reserved for traditional CFL downlights with a G24q 4-Pin or medium base. They consume up to 50% less energy, thereby significantly reducing operating costs. The superior life hours of these lamps make them ideal for hard to reach places, reducing maintenance.

FEATURES

- Superior lighting performance.
- Lightweight and easy installation.
- Long life design.
- Energy efficient - Replacement for: CFL G24q 4 Pin and Medium base lamps.
- Vertical or horizontal applications.
- Mercury Free - Environmentally friendly.
- Low heat reduces AC costs.

APPLICATIONS

COMMERCIAL & INDUSTRIAL



- Walkway Lighting
- Office & Retail Lighting
- Hospitality Areas
- Recessed Downlights
- Wall Sconces

WARRANTY



QUALIFICATIONS



Qualifications vary, see technical data for specific information.



LED CFL STYLE LAMPS



PLUG & GO™ • DIRECT REPLACEMENT LAMPS (CFL ballast required.)

LED CFL PLUG & GO

WATTS	ITEM#	DESCRIPTION	DLC*	CCT	LUMENS	LM/W	BEAM	CRI	MOL	VOLTS	BASE	LIFE	TRAD. EQUIV.	CASE
4 PIN G24q BASE - NON-DIMMABLE														
9	90470	9W/G24q/4 PIN/PLUG & GO/30K/V - SL*	★	3000K	850	77	120°	83	3.7"	120-277	G24q 4 PIN	50K	13-42W	10
	90471	9W/G24q/4 PIN/PLUG & GO/40K/V - SL*	★	4000K	900	82	120°	83	3.7"	120-277	G24q 4 PIN	50K	13-42W	10
	90472	9W/G24q/4 PIN/PLUG & GO/30K/VL - SL*	★	3000K	850	77	120°	83	4.7"	120-277	G24q 4 PIN	50K	13-42W	10
	90473	9W/G24q/4 PIN/PLUG & GO/40K/VL - SL*	★	4000K	900	82	120°	83	4.7"	120-277	G24q 4 PIN	50K	13-42W	10
	90474	9W/G24q/4 PIN/PLUG & GO/30K/H - SL*	★	3000K	800	73	120°	83	5.2"	120-277	G24q 4 PIN	50K	13-42W	10
	90475	9W/G24q/4 PIN/PLUG & GO/40K/H - SL*	★	4000K	850	77	120°	83	5.2"	120-277	G24q 4 PIN	50K	13-42W	10

DIRECT WIRE LAMPS (Disconnect CFL Ballast; lamp runs off the main.)


WATTS	ITEM#	DESCRIPTION	DLC*	CCT	LUMENS	LM/W	BEAM	CRI	MOL	VOLTS	BASE	LIFE	TRAD. EQUIV.	CASE
180° - 4 PIN G24q BASE - NON-DIMMABLE														
LED 180° • LED PLUG IN														
6	91240	6WT10/180°/FR/35K/G24q/4 PIN - SL*		3500K	500	83	180°	83	5.4"	120-277	G24q 4 PIN	50K	13W	50
	91241	6WT10/180°/FR/40K/G24q/4 PIN - SL*		4000K	500	83	180°	83	5.4"	120-277	G24q 4 PIN	50K	13W	50
	91242	6WT10/180°/FR/50K/G24q/4 PIN - SL*		5000K	500	83	180°	83	5.4"	120-277	G24q 4 PIN	50K	13W	50
8	91252	8WT11/180°/FR/35K/G24q/4 PIN - SL*		3500K	700	88	180°	83	6.4"	120-277	G24q 4 PIN	50K	18W	50
	91253	8WT11/180°/FR/40K/G24q/4 PIN - SL*		4000K	700	88	180°	83	6.4"	120-277	G24q 4 PIN	50K	18W	50
	91254	8WT11/180°/FR/50K/G24q/4 PIN - SL*		5000K	700	88	180°	83	6.4"	120-277	G24q 4 PIN	50K	18W	10/50
180° - MEDIUM BASE - NON-DIMMABLE														
LED 180° • LED SCREW IN														
6	91246	6WT10/180°/FR/35K/MED/120-277V - SL*		3500K	500	83	180°	83	5.9"	120-277	MEDIUM	50K	13W	50
	91248	6WT10/180°/FR/50K/MED/120-277V - SL*		5000K	500	83	180°	83	5.9"	120-277	MEDIUM	50K	13W	50
8	91256	8WT11/180°/FR/35K/MED/120-277V - SL*		3500K	700	88	180°	83	6.9"	120-277	MEDIUM	50K	18W	50
	91258	8WT11/180°/FR/50K/MED/120-277V - SL*		5000K	700	88	180°	83	6.9"	120-277	MEDIUM	50K	18W	50
360° - 4 PIN G24q BASE - NON-DIMMABLE														
LED 360° • LED PLUG IN														
12	91017	12WT10/360°/FR/35K/G24q 4 PIN - SL*		3500K	1320	110	360°	80	6.2"	100-277	G24q 4 PIN	50K	18W	50
	91018	12WT10/360°/FR/40K/G24q 4 PIN - SL*		4000K	1320	110	360°	80	6.2"	100-277	G24q 4 PIN	50K	18W	50
	91019	12WT10/360°/FR/50K/G24q 4 PIN - SL*		5000K	1320	110	360°	80	6.2"	100-277	G24q 4 PIN	50K	18W	50
360° - MEDIUM BASE - NON-DIMMABLE														
LED 360° • LED PLUG IN														
12	91022	12WT10/360°/FR/35K/MED/100-277V - SL*		3500K	1320	110	360°	80	6.5"	100-277	MEDIUM	50K	18W	50
	91023	12WT10/360°/FR/40K/MED/100-277V - SL*		4000K	1320	110	360°	80	6.5"	100-277	MEDIUM	50K	18W	50
	91024	12WT10/360°/FR/50K/MED/100-277V - SL*		5000K	1320	110	360°	80	6.5"	100-277	MEDIUM	50K	18W	50
G24 RETROFIT - NON-DIMMABLE														
LED INDOOR LAMPS - LED CFL														
5	90629	5W/G24q-3 RETROFIT/35K/120° - SL*		3500K	400	80	120°	80	5.6"	110-277	G24q-3	30K	13W	10

ACCESSORY

ITEM#	DESCRIPTION	CASE
149-26725-411	G24q AND GX24q BASE / 4 PIN	1



90629



149-26725-411

Key: SL = Superior Life® / LM = Lumens / TRAD. EQUIV. = Traditional Equivalent

Note: Not all product variations listed on this page are DLC qualified. Visit www.designlights.org/search to confirm qualification. • The wattage listed above is the lamp power, DLC lists the wattage of the system power. • Published lumens on LED products are approximate and may vary slightly. • Specifications are subject to change without notice. • Photos and drawings may not be to scale and are for general reference only.

