



360° LAMPS  
910XX

TONE-SELECT™  
LAMPS  
915XX

# LED CFL STYLE LAMPS

DIRECT WIRE • G24q • MEDIUM BASE

Superior Life® LED CFL style lamps are an efficient way to light sockets once reserved for traditional CFL downlights with a G24q 4-Pin or medium base. They consume up to 50% less energy, thereby significantly reducing operating costs. The superior life hours of these lamps make them ideal for hard to reach places, reducing maintenance.

## FEATURES

- Superior lighting performance
- Lightweight and easy installation
- Superior Life® design.
- Energy efficient - Replacement for: CFL G24q 4 Pin and Medium base lamps.
- Vertical or horizontal applications
- Mercury Free - Environmentally friendly.

## APPLICATION

### COMMERCIAL & INDUSTRIAL



- |                   |              |
|-------------------|--------------|
| Walkways          | Retail       |
| Offices           | Wall Sconces |
| Hospitality Areas | Downlights   |

### WARRANTY\*



### QUALIFICATIONS\*



\*Warranty and Qualifications can vary per item, see technical data sheets (TDS) for specific information.





### DIRECT WIRE LAMPS (Disconnect CFL Ballast; lamp runs off the main.)

WATTS	ITEM#	DESCRIPTION	CEC STATUS	CCT	LUMENS	LM/W	BEAM	CRI	MOL	VOLTS	BASE	AVG. LIFE HOURS	TRAD. EQUIV.	CASE
<b>360° - 4 PIN G24q BASE - NON-DIMMABLE</b>														
12	91017	12WT10/360°/FR/35K/G24q 4 PIN - SL®	N/A	3500K	1320	110	360°	80	6.2"	100-277	G24q 4 PIN	50,000	18W	50
	91018	12WT10/360°/FR/40K/G24q 4 PIN - SL®	N/A	4000K	1320	110	360°	80	6.2"	100-277	G24q 4 PIN	50,000	18W	50
	91019	12WT10/360°/FR/50K/G24q 4 PIN - SL®	N/A	5000K	1320	110	360°	80	6.2"	100-277	G24q 4 PIN	50,000	18W	50
<b>360° - MEDIUM BASE - NON-DIMMABLE</b>														
12	91022	12WT10/360°/FR/35K/MED - SL®		3500K	1320	110	360°	80	6.5"	100-277	MEDIUM	50,000	18W	50
	91023	12WT10/360°/FR/40K/MED - SL®		4000K	1320	110	360°	80	6.5"	100-277	MEDIUM	50,000	18W	50
	91024	12WT10/360°/FR/50K/MED - SL®		5000K	1320	110	360°	80	6.5"	100-277	MEDIUM	50,000	18W	50

### TONE-SELECT™ DIRECT WIRE LAMPS (Disconnect CFL Ballast; lamp runs off the main. Selectable CCT 27K / 30K / 35K / 40K / 50K)

WATTS	ITEM#	DESCRIPTION	CEC STATUS	CCT	LUMENS	LM/W	BEAM	CRI	MOL	VOLTS	BASE	AVG. LIFE HOURS	TRAD. EQUIV.	CASE
<b>4 PIN G24q BASE - NON-DIMMABLE</b>														
6	91546	6WT10/120°/FR - 27/30/35/40/50K/G24q/4 PIN - SL®	N/A	27-50K	550-625	92-104	120°	83	5.4"	120-277	G24q 4 PIN	50,000	13W	50
8	91548	8WT10/120°/FR - 27/30/35/40/50K/G24q/4 PIN - SL®	N/A	27-50K	950-1050	119-131	120°	83	6.4"	120-277	G24q 4 PIN	50,000	18W	50
11	91550	11WT10/120°/FR - 27/30/35/40/50K/G24q/4 PIN - SL®	N/A	27-50K	1400-1500	127-136	120°	83	6.4"	120-277	G24q 4 PIN	50,000	24W	50
<b>MEDIUM BASE - NON-DIMMABLE</b>														
6	91545	6WT10/120°/FR - 27/30/35/40/50K/MED - SL®	T20	27-50K	550-625	92-104	120°	83	5.9"	120-277	MEDIUM	50,000	13W	50
8	91547	8WT10/120°/FR - 27/30/35/40/50K/MED - SL®	T20	27-50K	950-1050	119-131	120°	83	6.9"	120-277	MEDIUM	50,000	18W	50
11	91549	11WT10/120°/FR - 27/30/35/40/50K/MED - SL®	T20	27-50K	1400-1500	127-136	120°	83	6.9"	120-277	MEDIUM	50,000	24W	50

Key: SL = Superior Life® / P = Pending / N/A = Not Applicable / LM = Lumens / TRAD. EQUIV. = Traditional Equivalent

Note: CEC Status identifies items listed on the MAEDBS database that are in compliance with Title 20 or Title 24 Regulations. Visit [www.cacertappliances.energy.ca.gov](http://www.cacertappliances.energy.ca.gov) to confirm compliance. • Published lumens on LED products are approximate and may vary slightly. • Specifications are subject to change without notice. • Photos and drawings may not be to scale and are for general reference only.



**PREMIUM QUALITY LIGHTING® - Phone: 800-323-8107**  
© P.Q.L., Inc. • 2285 Ward Avenue • Simi Valley, CA 93065

**www.PQLighting.com**  
Rev: 09/21/2020

