



LED DIRECT WIRE TUBES

8FT DUAL POWER

The Superior Life® LED linear tube provides exceptional LED lighting with reduced energy and maintenance costs. The linear LED does not use a fluorescent ballast to work; instead it features a built in universal line voltage driver, making it a top of the line replacement for standard fluorescent tubes.

Application: Ideal for retrofitting fluorescent fixtures in commercial and industrial applications; offices, school, warehouses, factories, retail stores, workshops, hospitality, and storage areas.

LED DIRECT WIRE TUBES
8FT DUAL POWER - UL TYPE B



FEATURES

- High Efficiency, Energy Saving
- Premium Construction - Longer lamp life and durability.
- High Performance LEDs - Bright and high lumens per watt light output.
- Mercury Free - Environmentally friendly.
- Little to no UV or Projected Heat - Reduces fading and AC costs.
- Vibration and Shock Resistant
- No Ballast Required - Lamp runs off the main.
- Double Ended Connection*

* See install instructions for specific wiring and further details.



Note: Warranty and Qualifications can vary per item, see technical data sheets (TDS) for specific information. • Not all product variations listed are DLC® qualified. Visit www.designlights.org/search to confirm qualification. • Published lumens on LED products are approximate and may vary slightly. • Specifications are subject to change without notice. • Photos and drawings may not be to scale and are for general reference only.



LED DIRECT WIRE TUBES 8FT DUAL POWER - UL TYPE B



WATTS	ITEM#	DESCRIPTION	DLC®	CCT	LUMENS	LPW	BEAM	CRI	MOL	VOLTS	BASE	AVG. LIFE HOURS	CASE
8' - FROST - SINGLE PIN													
32	91816	8FT 32WT8/50K/TYPE B/DE/SINGLE PIN	P	5000K	4400	138	210°	82	94"	120-277	SINGLE PIN	50,000	10
34	90744	8FT 34WT8/40K/TYPE B/DE/SINGLE PIN	★	4000K	4400	129	210°	82	94"	120-277	SINGLE PIN	50,000	10
	90745	8FT 34WT8/50K/TYPE B/DE/SINGLE PIN	★	5000K	4400	129	210°	82	94"	120-277	SINGLE PIN	50,000	10
40	91818	8FT 40WT8/50K/TYPE B/DE/SINGLE PIN	P	5000K	5500	138	210°	82	94"	120-277	SINGLE PIN	50,000	10
43	90740	8FT 43WT8/40K/TYPE B/DE/SINGLE PIN	★	4000K	5500	128	210°	82	94"	120-277	SINGLE PIN	50,000	10
	90741	8FT 43WT8/50K/TYPE B/DE/SINGLE PIN	★	5000K	5500	128	210°	82	94"	120-277	SINGLE PIN	50,000	10
8' - FROST - RDC													
40	91819	8FT 40WT8/HO/50K/TYPE B/DE		5000K	5500	138	210°	82	94"	120-277	RDC	50,000	10
43	90816	8FT 43WT8/HO/50K/TYPE B/DE		5000K	5500	128	210°	82	94"	120-277	RDC	50,000	10

Key: P = Pending / LPW = Lumens Per Watt / TRAD. EQUIV. = Traditional Equivalent

Note: Warranty and Qualifications can vary per item, see technical data sheets (TDS) for specific information. - Not all product variations listed are DLC® qualified. Visit www.designlights.org/search to confirm qualification. - Published lumens on LED products are approximate and may vary slightly. - Specifications are subject to change without notice. - Photos and drawings may not be to scale and are for general reference only.



PREMIUM QUALITY LIGHTING® - Phone: 800-323-8107
© P.Q.L., Inc. • 2285 Ward Avenue • Simi Valley, CA 93065

www.PQLighting.com
Rev: 05/24/2022