



LED LINEAR DIRECT WIRE DUAL POWER 8'

DOUBLE ENDED CONNECTION • SINGLE PIN • RDC • UL TYPE B

The Superior Life® LED linear tube provides exceptional LED lighting with reduced energy and maintenance costs. The linear LED does not use a fluorescent ballast to work; instead it features a built in universal line voltage driver, making it a top of the line replacement for standard fluorescent tubes.

FEATURES

- High Efficiency, Energy Saving
- Premium Construction - Longer lamp life and durability.
- High Performance LEDs - Bright and high lumens per watt light output.
- Mercury Free - Environmentally friendly.
- Little to no UV or Projected Heat - Reduces fading and AC costs.
- Vibration and Shock Resistant
- No Ballast Required - Lamp runs off the main.
- Double Ended Connection*

* See install instructions for specific wiring and further details.

APPLICATIONS

COMMERCIAL & INDUSTRIAL



Offices

Schools

Retail Stores

Warehouses

Banking

Work Spaces

WARRANTY



QUALIFICATIONS



Qualifications vary, see technical data for specific information.

T8 TUBES

WATTS	ITEM#	DESCRIPTION	DLC*	UL/ETL	CCT	LUMENS	LM/W	BEAM	CRI	MOL	VOLTS	BASE	LIFE	CASE
												LED TUBE - 8FT LED TUBE DIRECT WIRE		
8' - FROST - SINGLE PIN														
34	90744	34WT8/40K/FR/SINGLE PIN - SL®	★	UL	4000K	4400	129	210°	82	96"	120-277	SINGLE PIN	50K	10
	90745	34WT8/50K/FR/SINGLE PIN - SL®	★	UL	5000K	4400	129	210°	82	96"	120-277	SINGLE PIN	50K	10
43	90740	43WT8/40K/FR/SINGLE PIN - SL®	★	UL	4000K	5500	128	210°	82	96"	120-277	SINGLE PIN	50K	10
	90741	43WT8/50K/FR/SINGLE PIN - SL®	★	UL	5000K	5500	128	210°	82	96"	120-277	SINGLE PIN	50K	10
												LED TUBE - 8FT LED TUBE DIRECT WIRE		
8' - FROST - RDC														
43	90816	43WT8/50K/FR/HO - SL®		UL	5000K	5500	128	210°	82	96"	120-277	RDC	50K	10

Key: SL = Superior Life® / LM = Lumens

Not all product variations listed on this page are DLC qualified. Visit www.designlights.org/search to confirm qualification. • Published lumens on LED products are approximate and may vary slightly. • Specifications are subject to change without notice. • Photos and drawings may not be to scale and are for general reference only.



PREMIUM QUALITY LIGHTING® • www.PQLighting.com
© P.Q.L., Inc. • 2285 Ward Avenue • Simi Valley, CA 93065 • 800-323-8107 • Fax: 877-619-7053

GO GREEN
12/2018