

# LED LINEAR DIRECT WIRE SIGN LAMPS

SINGLE ENDED CONNECTION • BI PIN / R17D • UL TYPE B

The Superior Life® LED Sign lamps provide exceptional LED lighting with reduced energy and maintenance costs. The linear LED Sign lamp does not use a fluorescent ballast to work; instead it features a built in universal line voltage driver, making it a top of the line retrofit for standard fluorescent tubes.

## FEATURES

- **High Efficiency, Energy Saving** - Up to 141 lumens per watt
- **Back-to-Back LED Strips** - For illuminating 2-sided signs
- **Premium Construction** - Longer lamp life and durability
- **High Performance LEDs** - Bright light output
- **End Cap Rotates 90°** - For precise positioning
- **Multi-Use End Cap Design** - Can be used in both HO and Medium Bi Pin Sockets
- **Mercury Free** - Environmentally friendly
- **No Ballast Required** - Lamp runs off the main
- **Single Ended Connection** - Non-Shunted Sockets are required

See install instructions for wiring and further details.

## APPLICATION COMMERCIAL & INDUSTRIAL



Signs


## WARRANTY\*



## QUALIFICATIONS\*



\*Warranty and Qualifications can vary per item, see technical data sheets (TDS) for specific information.



PREMIUM QUALITY LIGHTING® • Phone: 800-323-8107

© P.Q.L., Inc. • 2285 Ward Avenue • Simi Valley, CA 93065

www.PQLighting.com

Rev: 12/18/2020



### T8 - MED BI PIN / R17D (HO) *(Includes pre-installed R17d Adapter)*

WATTS	ITEM#	DESCRIPTION	CCT	LUMENS	LM/W	BEAM	CRI	MOL	VOLTS	BASE	AVG. LIFE HOURS	CASE
<b>CLEAR - NON-DIMMABLE</b>												
11	84999	SIGN 30" 11WT8/65K/CL/HO/120-277V - SL°	6500K	1500	136	330°	83	27.8"	120-277	MED BI PIN/R17D	50,000	10
15	85001	SIGN 42" 15WT8/65K/CL/HO/120-277V - SL°	6500K	2100	140	330°	83	39.8"	120-277	MED BI PIN/R17D	50,000	10
18	85003	SIGN 48" 18WT8/65K/CL/HO/120-277V - SL°	6500K	2500	139	330°	83	45.8"	120-277	MED BI PIN/R17D	50,000	10
24	85005	SIGN 60" 24WT8/65K/CL/HO/120-277V - SL°	6500K	3350	140	330°	83	57.8"	120-277	MED BI PIN/R17D	50,000	10
26	85007	SIGN 64" 26WT8/65K/CL/HO/120-277V - SL°	6500K	3650	140	330°	83	61.8"	120-277	MED BI PIN/R17D	50,000	10
30	85009	SIGN 72" 30WT8/65K/CL/HO/120-277V - SL°	6500K	4200	140	330°	83	69.8"	120-277	MED BI PIN/R17D	50,000	10
32	85011	SIGN 84" 32WT8/65K/CL/HO/120-277V - SL°	6500K	4500	141	330°	83	81.8"	120-277	MED BI PIN/R17D	50,000	10
36	85013	SIGN 96" 36WT8/65K/CL/HO/120-277V - SL°	6500K	5000	139	330°	83	93.8"	120-277	MED BI PIN/R17D	50,000	10
42	85015	SIGN 108" 42WT8/65K/CL/HO/120-277V - SL°	6500K	5800	138	330°	83	105.8"	120-277	MED BI PIN/R17D	50,000	10
45	85017	SIGN 117" 45WT8/65K/CL/HO/120-277V - SL°	6500K	6300	140	330°	83	114.8"	120-277	MED BI PIN/R17D	50,000	10

Key: SL = Superior Life° / P = Pending / N/A = Not Applicable / LM = Lumens

Note: Published lumens on LED products are approximate and may vary slightly. - Specifications are subject to change without notice. - Photos and drawings may not be to scale and are for general reference only.



**PREMIUM QUALITY LIGHTING®** • Phone: 800-323-8107  
© P.Q.L., Inc. • 2285 Ward Avenue • Simi Valley, CA 93065

**www.PQLighting.com**  
Rev: 12/18/2020

