



LED PAR LAMPS

REFLECTOR • NARROW FLOOD

Superior Life® PAR lamps are an efficient way to light sockets once reserved for traditional lamps. They consume up to 86% less energy, thereby significantly reducing operating costs. The superior life hours of these lamps make them ideal for hard to reach places, reducing maintenance.

FEATURES

- Superior lighting performance
- Energy efficient
- Lightweight and easy installation
- Superior Life® design
- Resembles traditional lighting
- Mercury Free - Environmentally friendly.
- Low heat reduces AC costs

Dimmable Superior Life® dimmable LED lamps function with wall dimmers just as normal incandescent lamps do by allowing full linear dimming control. *(When applicable)*

APPLICATION

RESIDENTIAL & COMMERCIAL



General Lighting

Recessed Cans

Track Lighting

Ceiling & Pendant Fixtures

WARRANTY



QUALIFICATIONS*



*Qualifications can vary per item, see technical data sheets (TDS) for specific information.



PREMIUM QUALITY LIGHTING® • Phone: 800-323-8107

© P.Q.L., Inc. • 2285 Ward Avenue • Simi Valley, CA 93065

www.PQLighting.com

Rev: 01/05/2021



PAR20 LAMPS

WATTS	ITEM#	DESCRIPTION	ENERGY STAR®	CEC STATUS	CCT	LUMENS	LM/W	BEAM	CRI	MOL	VOLTS	BASE	AVG. LIFE HOURS	TRAD. EQUIV.	CASE
DIMMABLE															
7	91362	7WPAR20/30K/25°/DIMMABLE/V5 - SL®			3000K	520	74	25°	80	3.4"	120	MEDIUM	10,000	50W	48
	91930	7WPAR20/27K/40°/DIMMABLE/V7 - SL®	★	JA8	2700K	575	82	40°	96	3.1"	120	MEDIUM	25,000	50W	96
	91950	7WPAR20/30K/40°/DIMMABLE/V7 - SL®	★	T20	3000K	575	82	40°	96	3.1"	120	MEDIUM	25,000	50W	96
	91951	7WPAR20/50K/40°/DIMMABLE/V7 - SL®	★	T20	5000K	575	82	40°	96	3.1"	120	MEDIUM	25,000	50W	96
8	91735	8WPAR20/30K/25°/DIMMABLE/V6 - SL®	★		3000K	500	63	25°	91	3.4"	120	MEDIUM	15,000	50W	48
	91736	8WPAR20/40K/25°/DIMMABLE/V6 - SL®	★		4000K	500	63	25°	94	3.4"	120	MEDIUM	15,000	50W	48

PAR30 SN LAMPS

WATTS	ITEM#	DESCRIPTION	ENERGY STAR®	CEC STATUS	CCT	LUMENS	LM/W	BEAM	CRI	MOL	VOLTS	BASE	AVG. LIFE HOURS	TRAD. EQUIV.	CASE
DIMMABLE															
12	91741	12WPAR30/SN/50K/DIMMABLE/V6 - SL®	★	T20	5000K	800	67	25°	96	3.3"	120	MEDIUM	15,000	75W	24
	91952	12WPAR30/SN/30K/40°/DIMMABLE/V7 - SL®	★	T20	3000K	975	81	40°	95	3.7"	120	MEDIUM	25,000	75W	24
	91934	12WPAR30/SN/27K/40°/DIMMABLE/V7 - SL®	★	JA8	2700K	975	81	40°	96	3.7"	120	MEDIUM	25,000	75W	24
	91936	12WPAR30/SN/40K/40°/DIMMABLE/V7 - SL®	★	JA8	4000K	975	81	40°	96	3.7"	120	MEDIUM	25,000	75W	24
	91953	12WPAR30/SN/50K/40°/DIMMABLE/V7 - SL®	★	T20	5000K	975	81	40°	97	3.7"	120	MEDIUM	25,000	75W	24
13	91367	13WPAR30/SN/27K/DIMMABLE/V5 - SL®	★		2700K	800	62	25°	92	3.5"	120	MEDIUM	25,000	75W	24

PAR30 LN LAMPS

WATTS	ITEM#	DESCRIPTION	ENERGY STAR®	CEC STATUS	CCT	LUMENS	LM/W	BEAM	CRI	MOL	VOLTS	BASE	AVG. LIFE HOURS	TRAD. EQUIV.	CASE
DIMMABLE															
11	91392	11WPAR30/LN/27K/BLACK/DIMM/V5 - SL®	★		2700K	800	62	40°	91	4.6"	120	MEDIUM	25,000	75W	24
12	91746	12WPAR30/LN/30K/DIMMABLE/V6 - SL®	★	T20	3000K	800	67	25°	95	4.3"	120	MEDIUM	15,000	75W	24
	91747	12WPAR30/LN/40K/DIMMABLE/V6 - SL®	★	T20	4000K	800	67	25°	95	4.3"	120	MEDIUM	15,000	75W	24
	91748	12WPAR30/LN/50K/DIMMABLE/V6 - SL®	★	T20	5000K	800	67	25°	96	4.3"	120	MEDIUM	15,000	75W	24
	91938	12WPAR30/LN/27K/40°/DIMMABLE/V7 - SL®	★	JA8	2700K	975	81	40°	96	4.4"	120	MEDIUM	25,000	75W	24
	91954	12WPAR30/LN/30K/40°/DIMMABLE/V7 - SL®	★	T20	3000K	975	81	40°	95	4.4"	120	MEDIUM	25,000	75W	24
	91955	12WPAR30/LN/50K/40°/DIMMABLE/V7 - SL®	★	T20	5000K	975	81	40°	97	4.4"	120	MEDIUM	25,000	75W	24

NON-DIMMABLE

20	91756	20WPAR30/LN/40K/25°/120-277V/V7 - SL®	★	T20	4000K	1800	90	25°	90	4.7"	120-277	MEDIUM	50,000	75W	12
25	91480	25WPAR30/LN/40K/25°/120-277V/V6 - SL®			4000K	2500	100	25°	80	4.7"	120-277	MEDIUM	25,000	75W	12

PAR38 LAMPS

WATTS	ITEM#	DESCRIPTION	ENERGY STAR®	CEC STATUS	CCT	LUMENS	LM/W	BEAM	CRI	MOL	VOLTS	BASE	AVG. LIFE HOURS	TRAD. EQUIV.	CASE
DIMMABLE															
15	91942	15WPAR38/27K/40°/DIMMABLE/V7 - SL®		JA8	2700K	1250	83	40°	90	4.9"	120	MEDIUM	25,000	90W	24
	91943	15WPAR38/30K/40°/DIMMABLE/V7 - SL®	★	JA8	3000K	1250	83	40°	95	4.9"	120	MEDIUM	25,000	90W	24
	91944	15WPAR38/40K/40°/DIMMABLE/V7 - SL®	★	JA8	4000K	1250	83	40°	95	4.9"	120	MEDIUM	25,000	90W	24
	91945	15WPAR38/50K/40°/DIMMABLE/V7 - SL®		T20	5000K	1250	83	40°	90	4.9"	120	MEDIUM	25,000	90W	24
	91956	15WPAR38/30K/40°/DIMMABLE/V7 - SL®	★	T20	3000K	1250	83	40°	96	4.9"	120	MEDIUM	25,000	100W	24
17	91767	17WPAR38/30K/40°/DIMMABLE/V6 - SL®	★	T20	3000K	1200	73	40°	95	4.8"	120	MEDIUM	15,000	120W	24
	91754	17WPAR38/40K/25°/DIMMABLE/V6 - SL®	★	T20	4000K	1200	73	25°	95	4.8"	120	MEDIUM	15,000	120W	24
19	91381	19WPAR38/30K/25°/DIMMABLE/V5 - SL®	★		3000K	1200	63	25°	92	5.1"	120	MEDIUM	25,000	120W	24

NON-DIMMABLE

15	90775	15WPAR38/FL/50K/38°/AC 100-277V - SL®			5000K	1500	100	38°	80	5.0"	100-277	MEDIUM	50,000	120W	50
17	91758	17WPAR38/30K/25°/V6 - SL®	★		3000K	1200	71	25°	90	4.8"	120-277	MEDIUM	40,000	120W	24
25	91761	25WPAR38/40K/25°/120-277V/V7 - SL®	★	T20	4000K	2500	100	25°	91	4.8"	120-277	MEDIUM	50,000	250W	12
	91762	25WPAR38/50K/25°/120-277V/V7 - SL®	★	T20	5000K	2500	100	25°	92	4.8"	120-277	MEDIUM	50,000	250W	12

Key: SL = Superior Life® / P = Pending / N/A = Not Applicable / LM = Lumens / TRAD. EQUIV. = Traditional Equivalent

Note: Not all product variations listed on this page are Energy Star® qualified. Visit www.energystar.gov to confirm qualification. CEC Status identifies items listed on the MAEDBS database that are in compliance with Title 20 or Title 24 Regulations. Visit www.cacertappliances.energy.ca.gov to confirm compliance. Published lumens on LED products are approximate and may vary slightly. Specifications are subject to change without notice. Photos and drawings may not be to scale and are for general reference only.

