



LED PAR LAMPS

REFLECTOR • NARROW FLOOD

Superior Life® PAR lamps are an efficient way to light sockets once reserved for traditional lamps. They consume up to 86% less energy, thereby significantly reducing operating costs. The superior life hours of these lamps make them ideal for hard to reach places, reducing maintenance.

FEATURES

- Superior lighting performance
- Energy efficient
- Lightweight and easy installation
- Superior Life® design
- Resembles traditional lighting
- Mercury Free - Environmentally friendly.
- Low heat reduces AC costs

Dimmable Superior Life® dimmable LED lamps function with wall dimmers just as normal incandescent lamps do by allowing full linear dimming control. *(When applicable)*

APPLICATION

RESIDENTIAL & COMMERCIAL



- General Lighting
- Recessed Cans
- Track Lighting
- Ceiling & Pendant Fixtures

WARRANTY



QUALIFICATIONS*



*Qualifications can vary per item, see technical data sheets (TDS) for specific information.



PREMIUM QUALITY LIGHTING® • Phone: 800-323-8107

© P.Q.L., Inc. • 2285 Ward Avenue • Simi Valley, CA 93065

www.PQLighting.com

Rev: 04/04/2022



PAR20 LAMPS

WATTS	ITEM#	DESCRIPTION	ENERGY STAR®	CEC STATUS	CCT	LUMENS	LM/W	BEAM	CRI	MOL	VOLTS	BASE	AVG. LIFE HOURS	TRAD. EQUIV.	CASE
DIMMABLE															
7	91362	7WPAR20/30K/25°/DIMMABLE/V5 - SL®			3000K	520	74	25°	80	3.4"	120	MEDIUM	10,000	50W	48
	91930	7WPAR20/27K/40°/DIMMABLE/V7 - SL®	★	JA8	2700K	575	82	40°	96	3.1"	120	MEDIUM	25,000	50W	96
	91950	7WPAR20/30K/40°/DIMMABLE/V7 - SL®	★	T20	3000K	575	82	40°	96	3.1"	120	MEDIUM	25,000	50W	96
	91951	7WPAR20/50K/40°/DIMMABLE/V7 - SL®	★	T20	5000K	575	82	40°	96	3.1"	120	MEDIUM	25,000	50W	96
	91933	7WPAR20/50K/40°/DIMMABLE/V7 - SL®	★		5000K	575	82	40°	96	3.1"	120	MEDIUM	25,000	50W	96
8	91735	8WPAR20/30K/25°/DIMMABLE/V6 - SL®	★		3000K	500	63	25°	91	3.4"	120	MEDIUM	15,000	50W	48
	91736	8WPAR20/40K/25°/DIMMABLE/V6 - SL®			4000K	500	63	25°	94	3.4"	120	MEDIUM	15,000	50W	48

PAR30 SN LAMPS

WATTS	ITEM#	DESCRIPTION	ENERGY STAR®	CEC STATUS	CCT	LUMENS	LM/W	BEAM	CRI	MOL	VOLTS	BASE	AVG. LIFE HOURS	TRAD. EQUIV.	CASE
DIMMABLE															
12	91952	12WPAR30/SN/30K/40°/DIMMABLE/V7 - SL®	★	T20	3000K	975	81	40°	95	3.7"	120	MEDIUM	25,000	75W	24
	91934	12WPAR30/SN/27K/40°/DIMMABLE/V7 - SL®	★	JA8	2700K	975	81	40°	96	3.7"	120	MEDIUM	25,000	75W	24
	91936	12WPAR30/SN/40K/40°/DIMMABLE/V7 - SL®	★	JA8	4000K	975	81	40°	96	3.7"	120	MEDIUM	25,000	75W	24
	91953	12WPAR30/SN/50K/40°/DIMMABLE/V7 - SL®	★	T20	5000K	975	81	40°	97	3.7"	120	MEDIUM	25,000	75W	24

PAR30 LN LAMPS

WATTS	ITEM#	DESCRIPTION	ENERGY STAR®	CEC STATUS	CCT	LUMENS	LM/W	BEAM	CRI	MOL	VOLTS	BASE	AVG. LIFE HOURS	TRAD. EQUIV.	CASE
DIMMABLE															
11	91392	11WPAR30/LN/27K/BLACK/DIMM/V5 - SL®	★		2700K	800	62	40°	91	4.6"	120	MEDIUM	25,000	75W	24
12	91938	12WPAR30/LN/27K/40°/DIMMABLE/V7 - SL®	★	JA8	2700K	975	81	40°	96	4.4"	120	MEDIUM	25,000	75W	24
	91954	12WPAR30/LN/30K/40°/DIMMABLE/V7 - SL®	★	T20	3000K	975	81	40°	95	4.4"	120	MEDIUM	25,000	75W	24
	91955	12WPAR30/LN/50K/40°/DIMMABLE/V7 - SL®	★	T20	5000K	975	81	40°	97	4.4"	120	MEDIUM	25,000	75W	24
NON-DIMMABLE															
20	91756	20WPAR30/LN/40K/25°/120-277V/V7 - SL®	★	T20	4000K	1800	90	25°	90	4.7"	120-277	MEDIUM	50,000	75W	12

PAR38 LAMPS

WATTS	ITEM#	DESCRIPTION	ENERGY STAR®	CEC STATUS	CCT	LUMENS	LM/W	BEAM	CRI	MOL	VOLTS	BASE	AVG. LIFE HOURS	TRAD. EQUIV.	CASE
DIMMABLE															
15	91942	15WPAR38/27K/40°/DIMMABLE/V7 - SL®		JA8	2700K	1250	83	40°	90	4.9"	120	MEDIUM	25,000	90W	24
	91943	15WPAR38/30K/40°/DIMMABLE/V7 - SL®	★	JA8	3000K	1250	83	40°	95	4.9"	120	MEDIUM	25,000	90W	24
	91944	15WPAR38/40K/40°/DIMMABLE/V7 - SL®	★	JA8	4000K	1250	83	40°	95	4.9"	120	MEDIUM	25,000	90W	24
	91945	15WPAR38/50K/40°/DIMMABLE/V7 - SL®		T20	5000K	1250	83	40°	90	4.9"	120	MEDIUM	25,000	90W	24
	91956	15WPAR38/30K/40°/DIMMABLE/V7 - SL®	★	T20	3000K	1250	83	40°	96	4.9"	120	MEDIUM	25,000	100W	24
17	91754	17WPAR38/40K/25°/DIMMABLE/V6 - SL®	★	T20	4000K	1200	73	25°	95	4.8"	120	MEDIUM	15,000	120W	24
NON-DIMMABLE															
15	90775	15WPAR38/FL/50K/38°/AC 100-277V - SL®			5000K	1500	100	38°	80	5.0"	100-277	MEDIUM	50,000	120W	50
17	91758	17WPAR38/30K/25°/V6 - SL®	★		3000K	1200	71	25°	90	4.8"	120-277	MEDIUM	40,000	120W	24
25	91761	25WPAR38/40K/25°/120-277V/V7 - SL®	★	T20	4000K	2500	100	25°	91	4.8"	120-277	MEDIUM	50,000	250W	12
	91762	25WPAR38/50K/25°/120-277V/V7 - SL®	★	T20	5000K	2500	100	25°	92	4.8"	120-277	MEDIUM	50,000	250W	12

Key: SL = Superior Life® / P = Pending / N/A = Not Applicable / LM = Lumens / TRAD. EQUIV. = Traditional Equivalent

Note: Not all product variations listed on this page are Energy Star® qualified. Visit www.energystar.gov to confirm qualification. CEC Status identifies items listed on the MAEDBS database that are in compliance with Title 20 or Title 24 Regulations. Visit www.cacertappliances.energy.ca.gov to confirm compliance. - Published lumens on LED products are approximate and may vary slightly. - Specifications are subject to change without notice. - Photos and drawings may not be to scale and are for general reference only.



PREMIUM QUALITY LIGHTING® - Phone: 800-323-8107

© P.Q.L., Inc. • 2285 Ward Avenue • Simi Valley, CA 93065

www.PQLighting.com

Rev: 04/04/2022