



PLUG & GO™ LAMPS
9047X



TONE-SELECT™
PLUG & GO™ LAMPS
9155X

LED PLUG & GO™ CFL STYLE LAMPS

DIRECT REPLACEMENT • G24q 4 PIN BASE

Superior Life® LED CFL style lamps are an efficient way to light sockets once reserved for traditional CFL downlights with a G24q 4-Pin or medium base. They consume up to 50% less energy, thereby significantly reducing operating costs. The superior life hours of these lamps make them ideal for hard to reach places, reducing maintenance.

FEATURES

- Superior lighting performance
- Lightweight and easy installation
- Superior Life® design.
- Energy efficient - Replacement for: CFL G24q 4 Pin and Medium base lamps.
- Vertical or horizontal applications
- Mercury Free - Environmentally friendly.
- Exempt from Title 20

APPLICATION

COMMERCIAL & INDUSTRIAL



Walkways	Retail
Offices	Wall Sconces
Hospitality Areas	Downlights

WARRANTY*



QUALIFICATIONS*



*Warranty and Qualifications can vary per item, see technical data sheets (TDS) for specific information.



PREMIUM QUALITY LIGHTING® • Phone: 800-323-8107
© P.Q.L., Inc. • 2285 Ward Avenue • Simi Valley, CA 93065

www.PQLighting.com
Rev: 09/18/2020



PLUG & GO™ - DIRECT REPLACEMENT LAMPS (CFL ballast required.)

WATTS	ITEM#	DESCRIPTION	DLC*	CCT	LUMENS	LM/W	BEAM	CRI	MOL	VOLTS	BASE	AVG. LIFE HOURS	TRAD. EQUIV.	CASE
4 PIN G24q BASE														
9	90470	9W/G24q/4 PIN/PLUG & GO/30K/V - SL*	★	3000K	950	86	120°	83	3.7"	120-277	G24q 4 PIN	50,000	13-42W	50
	90471	9W/G24q/4 PIN/PLUG & GO/40K/V - SL*	★	4000K	1050	95	120°	83	3.7"	120-277	G24q 4 PIN	50,000	13-42W	50
	90472	9W/G24q/4 PIN/PLUG & GO/30K/VL - SL*	★	3000K	950	86	120°	83	4.7"	120-277	G24q 4 PIN	50,000	13-42W	50
	90473	9W/G24q/4 PIN/PLUG & GO/40K/VL - SL*	★	4000K	1050	95	120°	83	4.7"	120-277	G24q 4 PIN	50,000	13-42W	50
	90474	9W/G24q/4 PIN/PLUG & GO/30K/H - SL*	★	3000K	900	82	120°	83	5.2"	120-277	G24q 4 PIN	50,000	13-42W	50
	90475	9W/G24q/4 PIN/PLUG & GO/40K/H - SL*	★	4000K	1000	91	120°	83	5.2"	120-277	G24q 4 PIN	50,000	13-42W	50

TONE-SELECT PLUG & GO™ - DIRECT REPLACEMENT LAMPS (CFL ballast required. CCT Selectable 30K / 35K / 40K)

WATTS	ITEM#	DESCRIPTION	DLC*	CCT	LUMENS	LM/W	BEAM	CRI	MOL	VOLTS	BASE	AVG. LIFE HOURS	TRAD. EQUIV.	CASE
4 PIN G24q BASE														
9	91552	9W/G24q/4 PIN/PLUG & GO - 30/35/40K/VL - SL*	★	30-40K	1025-1100	93	120°	83	4.7"	120-277	G24q 4 PIN	50,000	13-42W	50
	91553	9W/G24q/4 PIN/PLUG & GO - 30/35/40K/H - SL*	★	30-40K	1025-1100	93	120°	83	5.9"	120-277	G24q 4 PIN	50,000	13-42W	50

DLC* lists wattage and lumens efficacy of the system. Specifications above for the lamp only.

Key: SL = Superior Life® / P = Pending / LM = Lumens / TRAD. EQUIV. = Traditional Equivalent

Note: Not all product variations listed on this page are DLC qualified. Visit www.designlights.org/search to confirm qualification. • Published lumens on LED products are approximate and may vary slightly. • Specifications are subject to change without notice. • Photos and drawings may not be to scale and are for general reference only.



PREMIUM QUALITY LIGHTING® • Phone: 800-323-8107
© P.Q.L., Inc. • 2285 Ward Avenue • Simi Valley, CA 93065

www.PQLighting.com
Rev: 09/18/2020

