



LED PL & PLL LAMPS

HYBRID • DIRECT WIRE • G23 • 2G11 BASE

These Superior Life® lamps are an efficient way to light sockets once traditionally reserved for compact fluorescent plug-in lamps. They consume up to 50% less energy, thereby significantly reducing operating costs. The superior life hours of these lamps make them ideal for hard to reach places, reducing maintenance.

FEATURES

- Superior lighting performance.
- Energy efficient.
- Lightweight and easy installation.
- Long life design.
- Vertical or horizontal applications.
- Mercury Free - Environmentally friendly.
- Low heat reduces AC costs.

APPLICATIONS

COMMERCIAL & INDUSTRIAL



- General Lighting
- Walkway Lighting
- Office & Retail Lighting
- Hospitality Areas

WARRANTY



QUALIFICATIONS



Qualifications vary, see technical data for specific information.



LED PL & PLL LAMPS



HYBRID PL LAMPS *(Works with or without a magnetic ballast.)*

LED 180° - LED PLUG IN

WATTS	ITEM#	DESCRIPTION	DLC*	UL/ETL	CCT	LUMENS	LM/W	BEAM	CRI	MOL	VOLTS	BASE	LIFE	TRAD. EQUIV.	CASE
2 PIN G23 & GX23 BASE - NON-DIMMABLE															
4.5	91330	4.5WPL/180°/FR/30K/G23/2 PIN/HYBRID - SL*		ETL	3000K	450	100	180°	83	6.5"	120-277	G23 2 PIN	50K	9W	20
	91331	4.5WPL/180°/FR/40K/G23/2 PIN/HYBRID - SL*		ETL	4000K	450	100	180°	83	6.5"	120-277	G23 2 PIN	50K	9W	20
	91332	4.5WPL/180°/FR/50K/G23/2 PIN/HYBRID - SL*		ETL	5000K	450	100	180°	83	6.5"	120-277	G23 2 PIN	50K	9W	20
6	91333	6WPL/180°/FR/30K/GX23/2 PIN/HYBRID - SL*		ETL	3000K	600	100	180°	83	7.1"	120-277	GX23 2 PIN	50K	13W	20
	91334	6WPL/180°/FR/40K/GX23/2 PIN/HYBRID - SL*		ETL	4000K	600	100	180°	83	7.1"	120-277	GX23 2 PIN	50K	13W	20
	91335	6WPL/180°/FR/50K/GX23/2 PIN/HYBRID - SL*		ETL	5000K	600	100	180°	83	7.1"	120-277	GX23 2 PIN	50K	13W	20

DIRECT WIRE PLL LAMPS *(Disconnect CFL Ballast; lamp runs off the main.)*

LED PLL BYPASS - LED PLUG IN

WATTS	ITEM#	DESCRIPTION	DLC*	UL/ETL	CCT	LUMENS	LM/W	BEAM	CRI	MOL	VOLTS	BASE	LIFE	TRAD. EQUIV.	CASE
4 PIN 2G11 BASE - NON-DIMMABLE															
15	91262	PLL 15WT5/120°/FR/40K/2G11/100-277V - SL*		UL	4000K	1200	80	120°	80	16.3"	100-277	2G11 4 PIN	50K	36W	30
	91263	PLL 15WT5/120°/FR/50K/2G11/100-277V - SL*		UL	5000K	1200	80	120°	80	16.3"	100-277	2G11 4 PIN	50K	36W	30
23	91270	PLL 23WT5/115°/FR/35K/2G11/120-277V - SL*	★	UL	3500K	2600	113	115°	82	22.5"	120-277	2G11 4 PIN	50K	40W	50
	91271	PLL 23WT5/115°/FR/40K/2G11/120-277V - SL*	★	UL	4000K	2800	122	115°	82	22.5"	120-277	2G11 4 PIN	50K	40W	50
	91272	PLL 23WT5/115°/FR/50K/2G11/120-277V - SL*	★	UL	5000K	2800	122	115°	82	22.5"	120-277	2G11 4 PIN	50K	40W	50

ACCESSORIES

ITEM#	DESCRIPTION	CASE
149-26725-411	G24q AND GX24q BASE / 4 PIN	1
LH0270	2G11 4PIN CFL SOCKET WITH TWO HOLE & SWIVEL BRACKET HORIZONTAL MOUNTING	1



149-26725-411



LH0270

Key: SL = Superior Life® / LM = Lumens / TRAD. EQUIV. = Traditional Equivalent

Note: Not all product variations listed on this page are DLC qualified. Visit www.designlights.org/search to confirm qualification. • Published lumens on LED products are approximate and may vary slightly. • Specifications are subject to change without notice. • Photos and drawings may not be to scale and are for general reference only.

