



LED LIGHTING

PL & PLL LAMPS

These Superior Life® lamps are an efficient way to light sockets once traditionally reserved for compact fluorescent plug-in lamps. They consume up to 50% less energy, thereby significantly reducing operating costs. The superior life hours of these lamps make them ideal for hard to reach places, reducing maintenance.

Application: A general purpose replacement for traditional plug-in CFL lamps around the home and office; frequently used in downlights and sconces.

FEATURES

- Superior lighting performance
- Energy efficient
- Lightweight and easy installation
- Superior Life® design
- Vertical or horizontal applications
- Mercury Free - Environmentally friendly.
- Low heat reduces AC costs
- Exempt from Title 20



91330-91332



91333-91335



91262 / 91263



91270-91272

Note: Warranty and Qualifications can vary per item, see technical data sheets (TDS) for specific information. • Not all product variations listed are DLC® qualified. Visit www.designlights.org/search to confirm qualification. • Published lumens on LED products are approximate and may vary slightly. • Specifications are subject to change without notice. • Photos and drawings may not be to scale and are for general reference only.



LED LIGHTING PL & PLL LAMPS



HYBRID PL LAMPS *(Works with or without a magnetic ballast.)*

WATTS	ITEM#	DESCRIPTION	DLC®	UL/ETL	CCT	LUMENS	LPW	BEAM	CRI	MOL	VOLTS	BASE	LIFE HOURS	TRAD. EQUIV.	CASE
2 PIN G23 & GX23 BASE - NON-DIMMABLE															
4.5	91330	4.5WPL/30K/180°/FR/120-277V/G23 2 PIN		ETL	3000K	450	100	180°	83	6.5"	120-277	G23 2 PIN	50,000	9W	20
	91331	4.5WPL/40K/180°/FR/120-277V/G23 2 PIN		ETL	4000K	450	100	180°	83	6.5"	120-277	G23 2 PIN	50,000	9W	20
	91332	4.5WPL/50K/180°/FR/120-277V/G23 2 PIN		ETL	5000K	450	100	180°	83	6.5"	120-277	G23 2 PIN	50,000	9W	20
6	91333	6WPL/30K/180°/FR/120-277V/GX23 2 PIN		ETL	3000K	600	100	180°	83	7.1"	120-277	GX23 2 PIN	50,000	13W	20
	91334	6WPL/40K/180°/FR/120-277V/GX23 2 PIN		ETL	4000K	600	100	180°	83	7.1"	120-277	GX23 2 PIN	50,000	13W	20
	91335	6WPL/50K/180°/FR/120-277V/GX23 2 PIN		ETL	5000K	600	100	180°	83	7.1"	120-277	GX23 2 PIN	50,000	13W	20

DIRECT WIRE PLL LAMPS *(Disconnect CFL Ballast; lamp runs off the main.)*

WATTS	ITEM#	DESCRIPTION	DLC®	UL/ETL	CCT	LUMENS	LPW	BEAM	CRI	MOL	VOLTS	BASE	LIFE HOURS	TRAD. EQUIV.	CASE
4 PIN 2G11 BASE - NON-DIMMABLE															
15	91262	15WT5/PLL/40K/120°/FR/100-277V/2G11		UL	4000K	1200	80	120°	80	16.3"	100-277	2G11 4 PIN	50,000	36W	30
	91263	15WT5/PLL/50K/120°/FR/100-277V/2G11		UL	5000K	1200	80	120°	80	16.3"	100-277	2G11 4 PIN	50,000	36W	30
23	91270	23WT5/PLL/35K/115°/FR/120-277V/2G11	★	UL	3500K	2800	122	115°	82	22.5"	120-277	2G11 4 PIN	50,000	40W	50
	91271	23WT5/PLL/40K/115°/FR/120-277V/2G11	★	UL	4000K	2800	122	115°	82	22.5"	120-277	2G11 4 PIN	50,000	40W	50
	91272	23WT5/PLL/50K/115°/FR/120-277V/2G11	★	UL	5000K	2800	122	115°	82	22.5"	120-277	2G11 4 PIN	50,000	40W	50

ACCESSORY

ITEM#	DESCRIPTION	CASE
LH0270	2G11 4PIN CFL SOCKET WITH TWO HOLE & SWIVEL BRACKET HORIZONTAL MOUNTING	1



LH0270

Key: P = Pending / LPW = Lumens Per Watt / TRAD. EQUIV. = Traditional Equivalent

Note: Warranty and Qualifications can vary per item, see technical data sheets (TDS) for specific information. • Not all product variations listed are DLC® qualified. Visit www.designlights.org/search to confirm qualification. • Published lumens on LED products are approximate and may vary slightly. • Specifications are subject to change without notice. • Photos and drawings may not be to scale and are for general reference only.



PREMIUM QUALITY LIGHTING® • Phone: 800-323-8107
© P.Q.L., Inc. • 2285 Ward Avenue • Simi Valley, CA 93065



www.PQLighting.com

Rev: 08/25/2022