

SPEC-SELECT™ 8FT T8

Our T8 LED tube lamp provides exceptional LED lighting with reduced energy and maintenance costs. The linear LED does not use a fluorescent ballast to work; instead they feature a built-in universal line voltage driver, making it a top of the line replacement for standard fluorescent lamps.

DOUBLE ENDED DIRECT WIRE

- No ballast required, lamp runs off main
- Easily convert from Single Pin (FA8) to RDC (R17D)
- Exceptional efficacy
- 50,000-hour lifespan reduces replacements and labor costs.

Swapable end cap from
Single Pin (FA8) to RDC (R17D)



| | |
|-----------------|---------------------------|
| Project _____ | Date _____ |
| Catalog # _____ | Quantity _____ Type _____ |

PRODUCT INFORMATION

| ELECTRICAL | |
|-----------------------|-----------------|
| Wattages (Selectable) | 24W / 32W / 40W |
| Voltage | 120-277V |
| Current | 480mA |
| Power Factor | 0.9 |
| THD | 20 |

| OPTICAL | |
|-----------------------|---------------------------------------|
| Lumens | 3120 / 4160 / 5200 |
| Lumens Per Watt (LPW) | 130 |
| CCT (Selectable) | 3000K / 3500K / 4000K / 5000K / 6500K |
| CRI | 82 |
| Beam Angle | 210° |
| Dimming | See Install Instructions |

| ENVIRONMENT | |
|-----------------------|-------------|
| Operating Temperature | -4° ~ 113°F |
| Suitable Location | Damp |
| IP Rating | IP20 |

| CONSTRUCTION | |
|---------------------|--------------------------|
| Housing | Glass / Plastic End Caps |
| Lens | Frosted |
| Base / Power Supply | Single Pin or RDC |
| Finish | White |

| WARRANTY <i>(Complete terms can be found on our website.)</i> | |
|---|--------|
| Standard | 5-year |

LISTINGS




Visit www.designlights.org/qpl to confirm qualification.

ORDERING CODE

LT88BP405C1



DIMENSIONS



ORDERING

| LT8 | 8 | B | P40 | 5C | 1 |
|-----------------------|----------|----------------|----------------------------------|---|-----|
| SERIES | SIZE | TYPE | OUTPUT | CCT | GEN |
| LT8 Linear T8 Tube | 8 8FT | B UL Type B | P40 Selectable: 24W, 32W, 40W | 5C Selectable: 3000K, 3500K, 4000K, 5000K, 6500K | |

ACCESSORIES

| CODE | DESCRIPTION | CASE |
|-------|---|------|
| 90405 | LED 5W/90MIN EMERGENCY DRIVER FOR (1) T8 DIRECT WIRE TUBE/120-277V - T20C | 25 |
| 90415 | LED 10W/90MIN. EMERGENCY DRIVER FOR (1) T8 DIRECT WIRE TUBE/120-277V | 10 |

PACKAGING

| MASTER CASE | |
|--------------------|---------------------|
| Quantity | 10 Pack |
| Size (LxWxH) | 95.9" x 7.6" x 3.9" |
| Gross Weight (Lbs) | 12 |
| UPC | 10811768020806 |
| UPC Item | 811768029321 |

COO: China • Tariff: --