



T12 LINEAR FLUORESCENT

LOW MERCURY/ENVIRO-LUME™



Enjoy top lamp performance with Superior Life® fluorescent lamps. Built stronger to last longer, these lamps outperform the competition, giving you the best overall value for a superior product.

• **ENERGY EFFICIENT**

use about 1/5 as much electricity as an incandescent lamp to produce the same amount of light. Not impacted by new DOE energy efficiency targets.

• **ENHANCED COLOR**

up to 90 CRI (Color Rendering Index) provides excellent color consistency throughout the life of the lamp

• **BALLAST COMPATIBILITY**

Direct retrofit for existing T12 lighting, operates on both magnetic or electronic ballast.

LOW MERCURY ENVIRO-LUME™ CERTIFIED



All of our Superior Life® linear fluorescents are certified to protect the environment and allow for convenient domestic disposal.

ENVIRONMENTAL FEATURES:

- Passes EPA tests for substances that might dissolve into the ecosystem.
- 80% less mercury protects the environment from excess mercury in discarded lamps. Use a cleaner, low-mercury gas for a more crisp, clean light output Approved for domestic disposal.
- Saves money on lamp disposal costs and offers you more disposal options.
- Krypton/Argon Gas mixture for reduced energy consumption.
- No loss in performance – high efficiency offers the same color temperature as a standard fluorescent lamp.

| ITEM# | DESCRIPTION | WATTS | COLOR | LUMENS (INITIAL) | LUMENS (MEAN) | CRI | LENGTH (INCHES) | BASE | HOURS (AVERAGE) | CASE |
|-------------------|--|-------|-------|------------------|---------------|-----|-----------------|------------|-----------------|------|
| 90107 | F40T12/CW/ENVIRO LUME - SUPERIOR LIFE® | 40 | 4100K | 2600 | 2392 | 90 | 48 | SINGLE PIN | 24,000 | 30 |
| 90162 | F60T12/CW - SUPERIOR LIFE® | 50 | 4100K | 3800 | 3256 | 62 | 60 | SINGLE PIN | 12,000 | 15 |
| 90163 | F60T12/CW/HO - SUPERIOR LIFE® | 75 | 4100K | 4945 | 4500 | 82 | 60 | RDC | 12,000 | 15 |
| 90136 | F96T12/DAY-BRITE™/HO - SUPERIOR LIFE® | 110 | 6500K | 6750 | 5800 | 90 | 96 | RDC | 12,000 | 15 |
| T12 U-BEND | | | | | | | | | | |
| 90111 | FB40T12/CW/U/6 - SUPERIOR LIFE® | 40 | 4100K | 2200 | 2024 | 90 | 22.5 | MED BI PIN | 18,000 | 12 |

INITIAL LUMENS: Lumen output based upon the performance after 100 hours of operating life.

MEAN LUMENS: Lumen output at 40% of the lamps rated average life.

AVERAGE LIFE: Lamps turned off and restarted no more frequently than once every 3 operating hours, lamp life can be considerably longer if started less frequently.

E EISA COMPLIANT - Meets United States Minimum Efficiency Standards.

Hg This lamp contains mercury. For proper lamp disposal contact your local municipal solid waste agency directly, call 888-537-4874 or visit lamprecycle.org for state-specific lamp recycling options.



PREMIUM QUALITY LIGHTING® • www.PQLighting.com

© P.Q.L., Inc. • 2285 Ward Avenue • Simi Valley, Ca 93065 • 800.323.8107 • Fax: 877.619.7053

