

T12 LINEAR FLUORESCENT

LOW MERCURY ENVIRO-LUME™

Enjoy top lamp performance and energy efficiency with Superior Life® fluorescent lamps. Built stronger to last longer, these lamps out-perform the competition, giving you the best overall value for a superior product.

FEATURES

- **Energy Efficient** - uses about 1/5 as much electricity as an incandescent lamp to produce the same amount of light.
- **Enhanced Color** - up to 90 CRI (Color Rendering Index) provides excellent color consistency throughout the life of the lamp.
- **Ballast Compatibility** - direct retrofit for existing T12 lighting, operates on both magnetic or electronic ballast.



All of our Superior Life® linear fluorescents are certified to protect the environment and allow for convenient domestic disposal.

ENVIRONMENTAL FEATURES:

- Passes EPA tests for substances that might dissolve into the ecosystem.
- 80% less mercury protects the environment from excess mercury in discarded lamps. Use a cleaner, low-mercury gas for a more crisp, clean light output Approved for domestic disposal.
- Saves money on lamp disposal costs and offers you more disposal options.
- Krypton/Argon Gas mixture for reduced energy consumption.
- No loss in performance - high efficiency offers the same color temperature as a standard fluorescent lamp.

Note: These lamps contain mercury. For proper lamp disposal contact your local municipal solid waste agency directly, call 888-537-4874 or visit lamprecycle.org for state-specific lamp recycling options.



APPLICATION

COMMERCIAL & INDUSTRIAL



Offices Warehouses
Schools Banking
Retail Stores Work Spaces

WARRANTY



QUALIFICATIONS



EISA COMPLIANT - Meets United States Minimum Efficiency Standards. Highly Efficient.

WATTS	ITEM#	DESCRIPTION	CCT	(INITIAL) LUMENS	(MEAN) LUMENS	CRI	LENGTH	BASE	LIFE HOURS	CASE
40	90107	F40T12/CW - SUPERIOR LIFE®	4100K	2600	2392	90	48"	MED BI PIN	24,000	30
50	90162	F60T12/CW - SUPERIOR LIFE®	4100K	3450	--	69	60"	SINGLE PIN	12,000	15
75	90163	F60T12/CW/HO - SUPERIOR LIFE®	4100K	4945	4500	82	60"	RDC	12,000	15
110	90136	F96T12/DAY-BRITE™/HO - SUPERIOR LIFE®	6500K	6750	5800	90	96"	RDC	12,000	15
T12 - U-BEND										
40	90111	FB40T12/CW/U6 - SUPERIOR LIFE®	4100K	2200	2024	90	22.5"	MED BI PIN	18,000	10

INITIAL LUMENS: Lumen output based upon the performance after 100 hours of operating life.

MEAN LUMENS: Lumen output at 40% of the lamps rated average life.

AVERAGE LIFE: Lamps turned off and restarted no more frequently than once every 3 operating hours, lamp life can be considerably longer if started less frequently.

Note: Published lumens are approximate and may vary slightly. • Specifications are subject to change without notice. • Photos and drawings may not be to scale and are for general reference only.

