

TRA1P15

SPEC-SELECT™ TRACK LIGHT 5W/10W/15W

TEST CONDITIONS

Input 120V • Output: 36V - 150-250-350mA

BRAND	MODEL	ILED (mA)		DIMMING RANGE (%)		1 pcs LAMP/DIMMER					3 pcs LAMP/DIMMER					5 pcs LAMP/DIMMER					NOISE TEST RESULTS	
		Max.	Min.	Max.	Min.	Max.	75%	50%	25%	Min.	Max.	75%	50%	25%	Min.	Max.	75%	50%	25%	Min.		
LEVITON	IP106*	351	0	100.3	0	✓	✓	✓	✓	X	✓	✓	✓	✓	X	✓	✓	✓	✓	✓	X	A
LEVITON	IP1106	350	0	100.0	0	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	A
LEVITON	6633-P	352	6	100.6	1.7	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	A
LEVITON	6613-P	349	18	99.7	5.1	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	A
LUTRON DIVA	DVCL-153P	344	3	98.3	0.8	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	A
LUTRON DIVA	DVELV-300P	349	14	99.7	4	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	A
LUTRON SKYLARK	CTCL-153P	346	3	98.9	0.8	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	A
LUTRON SKYLARK	S-600	349	5	99.7	1.4	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	A
LUTRON TOGGLE	TGCL-153P	352	11	100.6	3.1	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	A

*LEVITON IP106: The dimming isn't smooth and shows slight flicker at the 150, 250, and 350 mA levels.

KEY		DIMMING RATIO		NOISE TEST	
✓	Pass (No Flicker)	According to output current.		A	Distance 3.9"
X	Failed (Flicker Unacceptable)	Max = Highest Level		B	Distance 7.9"
OK	Acceptable (Slight Flicker)	Min = Lowest Level		C	Distance 11.8"

TRA1P25

SPEC-SELECT™ TRACK LIGHT 15W/20W/25W

TEST CONDITIONS

Input 120V • Output: 36V - 350-500-600mA

BRAND	MODEL	ILED (mA)		DIMMING RANGE (%)		1 pcs LAMP/DIMMER					3 pcs LAMP/DIMMER					5 pcs LAMP/DIMMER					NOISE TEST RESULTS	
		Max.	Min.	Max.	Min.	Max.	75%	50%	25%	Min.	Max.	75%	50%	25%	Min.	Max.	75%	50%	25%	Min.		
COOPER	MLV-600	595	4	99.2	0.7	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	A
LEVITON	IP106	597	0	99.5	0	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	A
LEVITON	IP1106	598	0	99.6	0	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	A
LEVITON	6633-P	596	4	99.3	0.7	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	A
LEVITON	6613-P	594	17	99	2.8	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	A
LUTRON DIVA	DVCL-153P	596	1	99.3	0.2	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	A
LUTRON DIVA	DVELV-300P	596	8	99.3	1.3	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	A
LUTRON MAESTRO	MS-OP600G	520	2	86.7	0.3	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	A
LUTRON SKYLARK	CTCL-153P	598	1	99.6	0.2	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	A
LUTRON SKYLARK	S-600	596	7	99.3	1.2	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	A
LUTRON TOGGLE	TGCL-153P	595	8	99.2	1.3	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	A

KEY		DIMMING RATIO		NOISE TEST	
✓	Pass (No Flicker)	According to output current.		A	Distance 3.9"
X	Failed (Flicker Unacceptable)	Max = Highest Level		B	Distance 7.9"
OK	Acceptable (Slight Flicker)	Min = Lowest Level		C	Distance 11.8"

TRA1P35

SPEC-SELECT™ TRACK LIGHT 25W/30W/35W

TEST CONDITIONS

Input 120V • Output: 36V - 600-750-850mA

BRAND	MODEL	ILED (mA)		DIMMING RANGE (%)		1 pcs LAMP/DIMMER					3 pcs LAMP/DIMMER					5 pcs LAMP/DIMMER					NOISE TEST RESULTS	
		Max.	Min.	Max.	Min.	Max.	75%	50%	25%	Min.	Max.	75%	50%	25%	Min.	Max.	75%	50%	25%	Min.		
COOPER	MLV-600	855	12	100.5	1.4	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	B
LEVITON	IP106	849	0	99.8	0	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	B
LEVITON	IP1106	856	4	100.7	0.4	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	B
LEVITON	6633-P	847	10	99.6	1.1	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	B
LEVITON	6613-P	845	25	99.4	2.9	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	B
LUTRON DIVA	DVCL-153P	822	0	96.7	0	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	B
LUTRON DIVA	DVELV-300P	854	17	100.4	2	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	B
LUTRON SKYLARK	CTCL-153P	812	4	95.5	0.4	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	B
LUTRON SKYLARK	S-600	852	7	100.2	0.8	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	B
LUTRON TOGGLE	TGCL-153P	842	16	99	1.8	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	B

KEY		DIMMING RATIO		NOISE TEST	
✓	Pass (No Flicker)	According to output current.		A	Distance 3.9"
X	Failed (Flicker Unacceptable)	Max = Highest Level		B	Distance 7.9"
OK	Acceptable (Slight Flicker)	Min = Lowest Level		C	Distance 11.8"