



ORDERING CODE

VTY1S1

FEATURES

Vanity fixtures offer both elegance and versatility, ideal for modern interiors. Available in multiple lengths, they complement a variety of design style.

- Selectable CCT: Easily switch between three color temperature options
- Contemporary design
- Easy installation

APPLICATION

Ideal for a wide range of settings, these fixtures perform beautifully in bathroom vanities, accent and decorative lighting, hallways, hospitality spaces, offices, healthcare facilities, and other residential or commercial environments.



Project _____

Date _____

Catalog # _____

Quantity _____

Type _____

PRODUCT INFORMATION

ELECTRICAL	
Wattage	20W / 30W / 40W
Voltage	120V
Power Factor	0.9
THD	20
PERFORMANCE	
Lumens	2000 / 3000 / 4000
Efficiency (LPW)	100
CCT (Selectable)	3000K / 4000K / 5000K
CRI	80
Beam Angle	120°
Dimming	Refer to page 2 for compatibility.
ENVIRONMENT	
Operating Temperature	-4°F ~ 104°F
Suitable Location	Damp
IP Rating	IP50
CONSTRUCTION	
Lens	Acrylic White
Base / Power Supply	Hard Wired
Finish	Brushed Nickel
LIFESPAN <small>(Complete terms can be found on our website.)</small>	
Warranty	3-Year Standard
LISTINGS	
Model Number	VTY1-[2,3,4]-[20,30,40]-3C-S1



ORDERING CODE

VTY1S1**PQL**
PREMIUM QUALITY LIGHTING®**ORDERING**

VTY1	S1			3C	BN
SERIES	SHAPE	LENGTH*	OUTPUT	CCT	FINISH
VTY1 Vanity Fixtures	S1 Square	2 2FT	20 20W	3C Selectable: 3000K, 4000K, 5000K	BN Brushed Nickel
		3 3FT	30 30W		
		4 4FT	40 40W		

* Certain lengths may be special order. Please consult a sales representative for minimum quantities and lead times.

† Default settings: 4000K.

PACKAGING

MASTER CASE	VTY1S12203CBN	VTY1S13303CBN	VTY1S14403CBN
Quantity	4	--	--
Size (LxWxH)	--	--	--
UPC	--	--	--
INDIVIDUAL BOX			
Size (LxWxH)	25.3" x 6.3" x 5"	37.3" x 6.3" x 5"	--
UPC	--	--	--

Tariff: 9405.11.6020

DIMMER COMPATIBILITY

BRAND	MODEL
Leviton	6683
	2C3005
	IE1606
	IPL06

Lutron	3-WAY
	AYCL-153P
	CTCL-153P
	DV-600P
	DVCL-153P
	DVCL-253P
	MACL-153M
	MRF25-6CL
	S-603PG
	SCL-153P
	SFTU-5A3P
	TGCL-153P

DIMENSIONS